Joker.com FAQ

Table of Content

2.3 Email Gateway 3
Basics 3
How does the PGP/GPG-Mailinterface work? 3
Where are the replies of the mail-gateway sent? 5
How do I change my robot-email-address? 6
What is the Joker.com public key? 7
Should I use PGP or GPG? 8
Differences to DMAPI 9
Requests 9
General Instructions 9
List of currently working requests 11
Macros 20
What is a macro? 20
E-mail Address 21
.com/.net Contacts 22
.com Contacts 24
.net Contacts 26
.org Contacts 28
.info Contacts 30
.biz Contacts 32
.mobi Contacts 35
.name Contacts 38
.us Contacts 40
.de Contacts 43
.cn Contacts 46
.eu Contacts 49
Valid domain names 52
Nameserver 53
Zonefile entries 54
IP 56
Domain renewal 57
Country code 58
Language code 64
.me Contacts 66
DNS/URL-Forwarding 68
Create a dns-configuration 68
Delete a dns-configuration 71
List a dns-configuration 72
Domains 73
Create an order 73
Modify a domain 97
Renew a domain 103

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Transfer a domain ... 107
Delete a domain ... 110
List domains ... 112
Lock a domain ... 114
Unlock a domain ... 115
Get Auth-id ... 116
Grant Roles/Domain Permissions, Internal Transfer ... 117
Contacts ... 119
Create a contact ... 119
Modify a contact ... 123
Change an address ... 126
Change an owner ... 128
.asia Contacts ... 132
Nameservers ... 134
Create a nameserver ... 134
Modify a nameserver ... 137
Other ... 139
Support ... 139
Tools ... 141
CheckD ... 141
Examples ... 142
Complete set of examples for download ... 142

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

2.3 Email Gateway
How does the PGP/GPG-Mailinterface work?

Using the Joker.com email interface, you may send 'commands' to a special address at Joker.com by email. Those commands may consist of registration orders, domain renewals or modifications.

The Joker.com mail interface address is disclosed once you signed up as a reseller.

The emails making up the commands follow a simple format, which is described here in section 'Requests'.

For security reasons, each request which is sent to the mail gateway has to be signed using PGP or GPG. This means, you need to have a pgp/gpg-installation on your machine. Some tools which can be used for this:

- Gnu GPG
- Enigmail for Thunderbird

Emails which are not signed correctly will not be processed. All requests to the gateway have to be sent as PGP/GPG signed mails to the Joker mail-robot (you will receive the exact address if you have registered yourself as a reseller).

Mails are expected to be sent in the "**traditional**" format (signature is part of the message body), **not** (for example) in MIME encapsulated format!

The actual request (the command to be peroformed) has to be put into the subject of the email. Further details (for example the full qualified domain name) have to be put in the message body.

Example:

Subject: modify domain

-----BEGIN PGP SIGNED MESSAGE-----

Hash: SHA1

tld:org

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

sld:dummy

ns1-handle:ns1.dummy.org

ns2-handle:ns2.dummy.org

-----BEGIN PGP SIGNATURE-----

Version: GnuPG v1.0.2 (GNU/Linux)

Comment: For info see http://www.gnupg.org

iD7DBQE6ZtMfzWqd+drNYRURAuW4AJ4nRewOrNc+yLMmmCouVcMP3v5nWQCdHUlf

tJk/gOuFmDnIs3JS+7eRjnA=

=Fwmc

-----END PGP SIGNATURE-----

Keywords: PGP GPG PGP/GPG mail-interface

Last update: 2012-10-11 10:19

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Basics

Where are the replies of the mail-gateway sent?

The replies of the gateway are generally sent to the "reply-to"-address. In order to specify that address, you will have to fill in the reply-to-field within the e-mails you send to the mail-gateway.

Keywords: replies mail-gateway reply-to

Last update: 2007-03-27 15:15

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Basics

How do I change my robot-email-address?

The Joker.com system identifies you using your pgp-signature and your email-address, so you have to provide a new pgp-key, if you want to change your robot-email-address. Without changing the pgp-key, our system cannot grant you access to the domains, you have registered at joker.com.

Please, follow the 3 steps below to **change your robot-email-address**.

1. Create a new contact with your new email-address using the mail-gateway.

2. Change the billing-c of **all** your domains using this new contact, which contains the new robot-email-address. Use the "list domains"-request for a listing of your domains.

3. Go to https://joker.com/index.joker?mode=resellerpages&stage=step13b and provide your new email-address and your new pgp-key and wait for our response mail.

Keywords: change robot-email-address robot e-mail address

Last update: 2007-03-27 15:23

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Basics

What is the Joker.com public key?

Please verify e-mails from Joker.com using the following public key:

```
-----BEGIN PGP PUBLIC KEY BLOCK-----
Version: GnuPG v1.0.7 (GNU/Linux)
mIsEPOorJQEEAJauWOOvusxn9GFEPjZnQ3x/48OfaPwSN4cIF5ezpUT6FycZQa+q
eUnNlS+bj80ULXnyyigmkUGwEtW/Qoyd55RM983pr4KtuHSMSU9gCN1syuHlDOAm
71u6irfv5RaHbJXauMCAgUKn+dBNZVZyUTm9aW2pudcwY45apF2tieTZAAYptClq
b2tlci5jb20gc2lnbmVyIHNlcnZpY2UgPGluZm9Aam9rZXIuY29tPoiyBBMBAgAc
BQI8/NifAhsDBAsHAwIDFQIDAxYCAQIeAQIXgAAKCRAm3eE0EUTiIx9RA/9HGDrD
cVM6PjZHr5jpT4svpv7xrjVRn2OIR+s80RuBAnLyAWOflqJ9342SYD8C7BMAqYm4
wXvC3/yvbQEAqsmJ5Bbq2NV+KDepahTtL8SUQ6TkOSUd9NDOvLoQWVI6o1Dz/3MG
HLJfNtx6067Sq8pP8PuYyscPyZ7/uiUilyOrqg==
=O/7Q
-----END PGP PUBLIC KEY BLOCK-----
```

Keywords: public pgp/gpg-key key

Last update: 2007-03-30 15:48

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Basics

Should I use PGP or GPG?

It does not matter if you use PGP or GPG, the version is not important as well. Just make sure that your program is able to put PGP signatures into your mail in the format described above.

Please have a look at the following web sites to get the newest versions and lots of explanation on the programs.

http://www.pgpi.org/

http://www.gnupg.org/

ATTENTION:

Users of GPG have to use the following flag:

gpg --clearsign --force-v3-sigs ....

Otherwise our system will reject your signed mails.

Keywords: PGP GPG signature

Last update: 2007-03-30 15:53

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Basics
General Instructions

All requests do follow the same scheme:

- each key:value pair is unique in application.
- each key:value pair is one line finished with carriage return
- each key is delimited by a colon ":" from the value

You have to send the request as signed email to the Joker.com mail gateway address. This address is disclosed once you signed up as a reseller of Joker.com.

Each email uses a simple, special format, which is described under the different request-types.

For security reasons you have to pgp-sign each mail you send to the mail-gateway, so you need a pgp-installation on your machine. Unsigned or invalid mails will be ignored.

Emails without a valid subject (request-type) will produce an error. In this case you will receive an error message as response.

Valid requests are normaly processed in realtime. Under certain circumstances (Registry-Downtimes, System maintenance, etc.) it is possible, that requests have to wait for processing. It is highly recommended to ask our support before you repeat such requests.

The descriptions for the requests do all follow the same scheme:

Topic 'introduction' - a short introduction of the request, what is the request for.

Topic 'request fields'

- which fields are required or allowed for a request
- which character are allowed for a request field (the valid character sets are described with PERL-REGULAR-EXPRESSIONS)
- one or more examples for a valid request

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Requests

Keywords: instructions introduction requests

Last update: 2012-10-11 10:29

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Requests

List of currently working requests

Here you will find the list of the currently working requests. there are 2 types of status for each request.

- available
- not yet implemented

All requests marked with "not yet implemented" will be available during the next weeks.

target	request-type	status
.com/.net	support	available
	create order	available
	change owner	available
	change address	available
	transfer domain	available
	renew domain	available
	delete domain	available
	modify domain	available
	create contact	available
	modify contact	available
	create nameserver	available
	modify nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
.org	support	available
	create org-order	available

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Requests

	change org-owner	available
	change org-address	available
	transfer org-domain	available
	renew org-domain	available
	delete org-domain	available
	modify org-domain	available
	create org-contact	available
	modify org-contact	available
	create org-nameserver	available
	modify org-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get auth-id	available
.info	support	available
	create info-order	available
	change info-owner	available
	change info-address	available
	transfer info-domain	available
	renew info-domain	available
	delete info-domain	available
	modify info-domain	available
	create info-contact	available
	modify info-contact	available
	create info-nameserver	available

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Requests

	modify info-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get auth-id	available
.biz	support	available
	create biz-order	available
	change biz-owner	available
	change biz-address	available
	transfer biz-domain	available
	renew biz-domain	available
	delete biz-domain	available
	modify biz-domain	available
	create biz-contact	available
	modify biz-contact	available
	create biz-nameserver	available
	modify biz-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get auth-id	available
.de	support	available
	create de-order	available
	change de-owner	available
	change de-address	available

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Requests

	transfer de-domain	available
	renew de-domain	available
	delete de-domain	available
	modify de-domain	available
	create de-contact	available
	modify de-contact	available
	create de-nameserver	available
	modify de-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
.eu	support	available
	create eu-order	available
	change eu-owner	available
	change eu-address	available
	transfer eu-domain	available
	renew eu-domain	available
	delete eu-domain	available
	modify eu-domain	available
	create eu-contact	available
	modify eu-contact	available
	create eu-nameserver	available
	modify eu-nameserver	available
	list domains	available
	lock domain	available

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Requests

	unlock domain	available
	get auth-id	available
.cn	support	available
	create cn-order	available
	change cn-owner	available
	change cn-address	available
	transfer cn-domain	available
	renew cn-domain	available
	delete cn-domain	available
	modify cn-domain	available
	create cn-contact	available
	modify cn-contact	available
	create cn-nameserver	available
	modify cn-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get auth-id	available
.us	support	available
	create us-order	available
	change us-owner	available
	change us-address	available
	transfer us-domain	available
	renew us-domain	available
	delete us-domain	available

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Requests

	modify us-domain	available
	create us-contact	available
	modify us-contact	available
	create us-nameserver	available
	modify us-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get auth-id	available
.me	support	available
	create me-order	available
	change me-owner	available
	change me-address	available
	transfer me-domain	available
	renew me-domain	available
	delete me-domain	available
	modify me-domain	available
	create me-contact	available
	modify me-contact	available
	create me-nameserver	available
	modify me-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get auth-id	available

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Requests

.asia	support	available
	create asia-order	available
	change asia-owner	available
	change asia-address	available
	transfer asia-domain	available
	renew asia-domain	available
	delete asia-domain	available
	modify asia-domain	available
	create asia-contact	available
	modify asia-contact	available
	create asia-nameserver	available
	modify asia-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get auth-id	available
.mobi	support	available
	create mobi-order	available
	change mobi-owner	available
	change mobi-address	available
	transfer mobi-domain	available
	renew mobi-domain	available
	delete mobi-domain	available
	modify mobi-domain	available
	create mobi-contact	available

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

	modify mobi-contact	available
	create mobi-nameserver	available
	modify mobi-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get auth-id	available
.name	support	available
	create name-order	available
	change name-owner	available
	change name-address	available
	transfer name-domain	available
	renew name-domain	available
	delete name-domain	available
	modify name-domain	available
	create name-contact	available
	modify name-contact	available
	create name-nameserver	available
	modify name-nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get auth-id	available
nameservice/urlforwarding	create dns-config	available
	delete dns-config	available

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

	list dns-config	available

Keywords: request requests, summary, email-gw, email-gateway

Last update: 2008-08-14 11:31

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Requests

What is a macro?

A macro is used within the definition of a request.

A macro starts with an @.

Example: @cont or @email or @ns

Every time you find a macro, please check the definition of this macro for further information.

Keywords: macro definition

Last update: 2007-04-02 15:20

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
E-mail Address

@email

This means an email address in the following format:

Valid values (.com/.net only):
foo@bar.com
foo@bar.com#1
foo@bar.com#15

Invalid values:
Hans Nase <hans@foo.com>
hans@foo.com (Hans Nase)

Valid values (.org/.info/.biz/.del.cn only):
foo@bar.com
foo-bar@bar.com

Invalid values:
Hans Nase <hans@foo.com>
hans@foo.com (Hans Nase)

foo@bar.com#15

Keywords: email address

Last update: 2011-08-11 15:34

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

.com/.net Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created and we will add a numerical suffix to the email address that starts with "0" and increases by "1" for every existing contact with such a emailaddress in the JOKER-DATABASE.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the "..." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "..." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "..." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "..." at the beginning of the fieldname with "billing-contact".

request-field	valid values	required
"..."-individual	[Y/N]	yes
"..."-name	[x20-x7e]{0,80}	yes, if individual = Y
"..."-frame	[x20-x7e]{0,80}	yes, if individual = Y
"..."-title	[x20-x7e]{0,80}	no
"..."-organization	[x20-x7e]{0,80}	yes, if individual = N
"..."-address-1	[x20-x7e]{1,80}	yes
"..."-address-2	[x20-x7e]{0,80}	no
"..."-postal-code	[x20-x7e]{1,50}	yes
"..."-city	[x20-x7e]{1,80}	yes
"..."-state	[x20-x7e]{0,80}	no
"..."-country	@country	yes
"..."-email	@email	yes
"..."-phone	[[x20-x7e]]{1,50}	yes
"..."-fax	[[x20-x7e]]{0,50}	no

An existing contact (**@cont** or **@same-as**) (.com/.net only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:foo@bar.com#0
admin-contact-handle:foo@bar.com
tech-contact-handle:foo@bar.com#15
billing-contact-handle:foo@bar.com#15

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for (.com/.net)-requests, contact handles for (.info)-contacts are not allowed. If you are referencing to a shortcut like C00763-LRMS, you will get an error.

Keywords: new-handle @cont @same-as admin tech billing

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

Last update: 2007-04-17 22:05

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
.com Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CCOM-<number>,

e.g. CCOM-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (**@comcont** or **@same-as**) (.com only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:CCOM-176269
admin-contact-handle:CCOM-176229
tech-contact-handle:CCOM-176269
billing-contact-handle:CCOM-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .com-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @comcont @same-as admin tech billing

Last update: 2015-11-09 17:47

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CNET-<number>, e.g. CNET-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (**@netcont** or **@same-as**) (.net only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:CNET-176269
admin-contact-handle:CNET-176229
tech-contact-handle:CNET-176269
billing-contact-handle:CNET-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .net-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @netcont @same-as admin tech billing

Last update: 2015-11-09 17:48

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
.org Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CORG-<number>, e.g. CORG-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (**@orgcont** or **@same-as**) (.org only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:CORG-176269
admin-contact-handle:CORG-176229
tech-contact-handle:CORG-176269
billing-contact-handle:CORG-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .org-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @orgcont @same-as admin tech billing

Last update: 2015-11-09 17:49

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
.info Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format C<number>-LRMS, e.g. C176269-LRMS.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@**infocont** or @**same-as**) (.info only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:C176269-LRMS
admin-contact-handle:CAFI-007
tech-contact-handle:C176269-LRMS
billing-contact-handle:CAFI-008

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

The @**same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .info-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @infocont @same-as admin tech billing

Last update: 2015-11-09 17:49

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
.biz Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created.

ATTENTION

According to the rules of NEULEVEL, the fieldlength for most of the requestfields are limited to 30 characters. Please check very carefully the definitions of the request fields.

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

Please, keep in mind, that if you are using the concatenation of **fname** and **lname**, you have to care that the sum of both fields should not be longer than 30 characters.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,30}	no, if name is given
".."-fname	[\x20-\x7e]{0,30}	no, if name is given
".."-name	[\x20-\x7e]{0,30}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,30}	no
".."-organization	[\x20-\x7e]{0,30}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,30}	yes
".."-address-2	[\x20-\x7e]{0,30}	no
".."-address-3	[\x20-\x7e]{0,30}	no
".."-postal-code	[\x20-\x7e]{1,10}	yes
".."-city	[\x20-\x7e]{1,30}	yes
".."-state	[\x20-\x7e]{0,30}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,17}	yes
".."-fax	[[\x20-\x7e]{0,17}	no

An existing contact (**@bizcont** or **@same-as**) (.biz only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle: CNEU-12345
admin-contact-handle: CNEU-12345
tech-contact-handle: CNEU-12345
billing-contact-handle: CNEU-12345

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .biz-requests the contact handles for (.com/.net/.org/.info)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Note that for .biz-requests the contacthandles for (.info)-contacts are not allowed. If you referencing to a shortcut like C176269-LRMS, you will get an error.

Keywords: new-handle @bizcont @same-as admin tech billing

Last update: 2015-11-09 17:51

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COMO-<number>, e.g. COMO-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (**@mobicont** or **@same-as**) (.mobi only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:COMO-176269
admin-contact-handle:COMO-176229
tech-contact-handle:COMO-176269
billing-contact-handle:COMO-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .mobi-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @mobicont @same-as admin tech billing owner

Last update: 2015-11-09 17:50

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

.name Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CNAM-<number>, e.g. CNAM-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the "_" at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "_" at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "_" at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "_" at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname** and **lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	field values	required
~individual	(Y/N)	yes
~fname	(*2D-*r7x)[0,80]	no, if name is given
~lname	(*2D-*r7x)[0,80]	no, if name is given
~name	(*2D-*r7x)[0,80]	yes, if fname **and/or** lname are not given
~title	(*2D-*r7x)[0,80]	no
~organization	(*2D-*r7x)[0,80]	yes, if individual = N
~address-1	(*2D-*r7x)[1,80]	yes
~address-2	(*2D-*r7x)[0,80]	no
~address-3	(*2D-*r7x)[0,80]	no
~postal-code	(*2D-*r7x)[1,50]	yes
~city	(*2D-*r7x)[1,80]	yes
~state	(*2D-*r7x)[0,80]	no

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

.."-country	@country	yes
.."-email	@email	yes
.."-phone	[\x20-\x7e]{1,50}	yes
.."-fax	[\x20-\x7e]{0,50}	no

An existing contact (**@namecont** or **@same-as**) (.name only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:CNAM-176269
admin-contact-handle:CNAM-176229
tech-contact-handle:CNAM-176269
billing-contact-handle:CNAM-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .name-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @namecont @same-as admin tech billing owner

Last update: 2007-06-21 11:11

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
.us Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COUS-<number>, e.g. COUS-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (**@uscont** or **@same-as**) (.us only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:COUS-176269
admin-contact-handle:COUS-176229
tech-contact-handle:COUS-176269
billing-contact-handle:COUS-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

billing-contact-handle:same-as-tech-contact

The @**same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .us-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @uscont @same-as admin tech billing owner

Last update: 2015-11-09 17:51

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
.de Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CODE-<number>, e.g. CODE-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	yes, but for admin-c and tech-c only

An existing contact (**@decont** or **@same-as**) (.de only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:CODE-176269
admin-contact-handle:CODE-176229
tech-contact-handle:CODE-176269
billing-contact-handle:CODE-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .de-requests the contact handles for (.com/.net/.org/.info/.biz/.cn)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @decont @same-as admin tech billing owner

Last update: 2015-11-09 17:50

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
.cn Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COCN-<number>, e.g. COCN-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (**@cncont** or **@same-as**) (.cn only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:COCN-176269
admin-contact-handle:COCN-176229
tech-contact-handle:COCN-176269
billing-contact-handle:COCN-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

billing-contact-handle:same-as-tech-contact

The @**same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .cn-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @cncont @same-as admin tech billing owner

Last update: 2015-11-09 17:51

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
.eu Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format C<number>, e.g. C176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (**@uscont** or **@same-as**) (.us only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:C176269
admin-contact-handle:C176229
tech-contact-handle:C176269
billing-contact-handle:C176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

billing-contact-handle:same-as-tech-contact

The @**same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .eu-requests the contact handles for (.com/.net/.org/.info/.biz/.de/.us)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @eucont @same-as admin tech billing owner

Last update: 2015-11-09 17:52

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
Valid domain names

@**dom** - a valid domain name under .com/.net

@**orgdom** - a valid domain name under .org

@**infodom** - a valid domain name under .info

@**dedom** - a valid domain name under .de

@**cndom** - a valid domain name under .cn

@**eudom** - a valid domain name under .eu

@**usdom** - a valid domain name under .us

@**fqdn** - a valid domain name under .com/.net/.org/.info/.mobi/.name/.biz/.de/.cn/.eu/.us

Keywords: @dom @orgdom @infodom @dedom @cndom @eudom @usdom @fqdn

Last update: 2007-03-28 15:45

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
Nameserver

@**ns** - the definition of an existing nameserver

You have to provide a valid nameserver handle. Implicit nameserver creation is not allowed.

Examples:

ns1.foo.bar.net
ns2.foo.bar.net

ns3.foo.bar.net

Keywords: @ns nameserver

Last update: 2015-11-09 17:53

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
Zonefile entries

@a_record

[a hostprefix without the domainname]:[IP-Address]

- trailing dots at the hostprefix are deleted
- an "@" will be expanded to the domainname

Example1:

a:www:194.233.101.99

Example2:

a:@:194.233.101.99

@mx_record

[a hostprefix without the domainname]:[priority]:[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" as the value of the hostprefix will be expanded to the domain name

Example 1:

mx:www:50:mail.hansnose.net

Example 2:

mx:www:90:mail.hansnose.net

Example 3:

mx:@:50:mail.hansnose.net

Example 4:

mx:@:90:mail.hansnose.net

@cname_record

[a hostprefix without the domainname]:[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" for the hostprefix is not supported within a CNAME-Record

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Example 1:

cname:www:mail.hansnose.net

Example 2:

cname:www2:mail.hansnose.net

@url_record

[a hostprefix without the domainname]::[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" as the value of the hostprefix will be expanded to the domain name

Example 1:

url:www:http://some.redirector.com

Example 2:

url:www2:http://some.redirector.com:9002

Example 3:

url:www3:https://some.redirector.com

Example 4:

url:www4:https://some.redirector.com:9002

Keywords: @a_record @mx_record @cname_record @url_record

Last update: 2007-04-20 14:49

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

IP

@ip - a valid ip-address

IP-addresses within the following range are NOT valid:

Ã,

min	max
10.0.0.0	10.255.255.255
127.0.0.0	127.255.255.255
192.168.0.0	192.168.255.255
172.16.0.0	172.31.255.255

Keywords: @ip

Last update: 2007-04-02 16:24

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros
Domain renewal

@renew

Here you have to provide the domain name and the renewal period or the desired expiration year on one line. You have to seperate the domain name and renewal period/expire year with an ":" (ASCII 058). The maximum for the renewal period is 9 years.

Examples:

domain1:blafasel.com:2
domain2:hansnose.net:3
domain2:hansnose.info:2005
domain2:hansnose.biz:2

Attention:

If you are using the expire year and the current expire year of the domain is equal or greater than the provided value for that field, the request will not processed.

Keywords: @renew

Last update: 2007-03-28 16:12

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

Country code

@country - one of the following countries:

country code	country
AF	AFGHANISTAN
AS	SAMOA
AU	AUSTRIA
AS	AMERICAN SAMOA
AD	ANDORRA
AO	ANGOLA
AI	ANGUILLA
AQ	ANTARCTICA
AG	ANTIGUA AND BARBUDA
AR	ARGENTINA
AM	ARMENIA
AW	ARUBA
AU	AUSTRALIA
AT	AUSTRIA
AZ	AZERBAIJAN
BS	BAHAMAS
BH	BAHRAIN
BD	BANGLADESH
BB	BARBADOS
BE	BELARUS
BE	BELGIUM
BZ	BELIZE
BJ	BENIN
BM	BERMUDA
BT	BHUTAN
BO	BOLIVIA
BA	BOSNIA AND HERZEGOVINA
BW	BOTSWANA
BV	BOUVET ISLAND
BR	BRAZIL
IO	BRITISH INDIAN OCEAN TERRITORY
BN	BRUNEI DARUSSALAM
BG	BULGARIA
BF	BURKINA FASO
BI	BURUNDI
KH	CAMBODIA
CM	CAMEROON
CA	CANADA
CV	CAPE VERDE
KY	CAYMAN ISLANDS
CF	CENTRAL AFRICAN REPUBLIC
TD	CHAD
CL	CHILE
CN	CHINA

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

C	CHRISTMAS ISLAND
C	COCOS (KEELING) ISLANDS
C	COLOMBIA
C	COMOROS
C	CONGO
C	CONGO, THE DEMOCRATIC REPUBLIC OF THE
C	COOK ISLANDS
C	COSTA RICA
C	COTE D'IVOIRE
C	CROATIA
C	CUBA
C	CYPRUS
C	CZECH REPUBLIC
D	DENMARK
D	DJIBOUTI
D	DOMINICA
D	DOMINICAN REPUBLIC
E	ECUADOR
E	EGYPT
E	EL SALVADOR
E	EQUATORIAL GUINEA
E	ERITREA
E	ESTONIA
E	ETHIOPIA
F	FALKLAND ISLANDS (MALVINAS)
F	FAROE ISLANDS
F	FJI
F	FINLAND
F	FRANCE
F	METROPOLITAN
F	FRENCH GUIANA
F	FRENCH POLYNESIA
F	FRENCH SOUTHERN TERRITORIES
G	GABON
G	GAMBIA
G	GEORGIA
G	GERMANY
G	GHANA
G	GIBRALTAR
G	GREECE
G	GREENLAND
G	GRENADA
G	GUADELOUPE
G	GUAM
G	GUATEMALA
G	GUINEA
G	GUIAU
G	GUYANA
H	HAITI

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

HM	HEARD ISLAND AND MCDONALD ISLANDS
VA	HOLY SEE (VATICAN CITY STATE)
HN	HONDURAS
HK	HONG KONG
HU	HUNGARY
IS	ICELAND
IN	INDIA
ID	INDONESIA
IR	IRAN, ISLAMIC REPUBLIC OF
IQ	IRAQ
IE	IRELAND
IL	ISRAEL
IT	ITALY
JM	JAMAICA
JP	JAPAN
JO	JORDAN
KZ	KAZAKHSTAN
KE	KENYA
KI	KIRIBATI
KP	KOREA, DEMOCRATIC PEOPLE'S REPUBLIC OF
KR	KOREA, REPUBLIC OF
KW	KUWAIT
KG	KYRGYZSTAN
LA	LAO PEOPLE'S DEMOCRATIC REPUBLIC
LV	LATVIA
LB	LEBANON
LS	LESOTHO
LR	LIBERIA
LY	LIBYAN ARAB JAMAHIRIYA
LI	LIECHTENSTEIN
LT	LITHUANIA
LU	LUXEMBOURG
MO	MACAU
MK	MACEDONIA, THE FORMER YUGOSLAV REPUBLIC OF
MG	MADAGASCAR
MW	MALAWI
MY	MALAYSIA
MV	MALDIVES
ML	MALI
MT	MALTA
MH	MARSHALL ISLANDS
MQ	MARTINIQUE
MR	MAURITANIA
MU	MAURITIUS
YT	MAYOTTE
MX	MEXICO
FM	MICRONESIA, FEDERATED STATES OF
MD	MOLDOVA, REPUBLIC OF
MC	MONACO
MN	MONGOLIA

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

MS	MONTSERRAT
MA	MOROCCO
MZ	MOZAMBIQUE
MM	MYANMAR
NA	NAMIBIA
NR	NAURU
NP	NEPAL
NL	NETHERLANDS
AN	NETHERLANDS ANTILLES
NC	NEW CALEDONIA
NZ	NEW ZEALAND
NI	NICARAGUA
NE	NIGER
NG	NIGERIA
NU	NIUE
NF	NORFOLK ISLAND
MP	NORTHERN MARIANA ISLANDS
NO	NORWAY
OM	OMAN
PK	PAKISTAN
PW	PALAU
PA	PANAMA
PG	PAPUA NEW GUINEA
PY	PARAGUAY
PE	PERU
PH	PHILIPPINES
PN	PITCAIRN
PL	POLAND
PT	PORTUGAL
PR	PUC
QA	QATAR
RE	REUNION
RO	ROMANIA
RU	RUSSIAN FEDERATION
RW	RWANDA
KN	SAINT KITTS AND NEVIS
LC	SAINT LUCIA
VC	SAINT VINCENT AND THE GRENADINES
WS	SAMOA
SM	SAN MARINO
ST	SAO TOME AND PRINCIPE
SA	SAUDI ARABIA
SN	SENEGAL
SC	SEYCHELLES
SL	SIONE
SG	SINGAPORE
SK	SLOVAKIA
SI	SLOVENIA
SB	SOLOMON ISLANDS
SO	SOMALIA

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

A	AFRICA
B	SOUTH GEORGIA AND THE SOUTH SANDWICH ISLANDS
C	SPAIN
D	SRI LANKA
E	SAINT HELENA
F	SAINT PIERRE AND MIQUELON
G	SUDAN
H	SURINAME
I	SVALBARD AND JAN MAYEN
J	SWAZILAND
K	SWEDEN
L	SWITZERLAND
M	SYRIAN ARAB REPUBLIC
N	TAIWAN, PROVINCE OF CHINA
O	TAJIKISTAN
P	TANZANIA, UNITED REPUBLIC OF
Q	THAILAND
R	TOGO
S	TOKELAU
T	TONGA
U	TRINIDAD AND TOBAGO
V	TUNISIA
W	TURKEY
X	TURKMENISTAN
Y	TURKS AND CAICOS ISLANDS
Z	TUVALU
AA	UGANDA
AB	UKRAINE
AC	UNITED ARAB EMIRATES
AD	UNITED KINGDOM
AE	UNITED STATES
AF	UNITED STATES MINOR OUTLYING ISLANDS
AG	URUGUAY
AH	UZBEKISTAN
AI	VANUATU
AJ	VENEZUELA
AK	VIETNAM
AL	VIRGIN ISLANDS, BRITISH
AM	VIRGIN ISLANDS, U.S.
AN	WALLIS AND FUTUNA
AO	SAMOA
AP	YEMEN
AQ	YUGOSLAVIA
AR	ZAMBIA
AS	ZIMBABWE

Keywords: country code @country

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

Last update: 2007-04-17 22:12

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

Language code

@**language** - one of the following language codes

Languagecode	Language
AFR	Afrikaans
ALB	Albanian
ARA	Arabic
ARM	Armenian
AZE	Azerbaijani
BAQ	Basque
BUL	Bulgarian
BUR	Burmese
CAT	Catalan
CHI	Chinese
CZE	Czech
DAN	Danish
DUT	Dutch
ENG	English
EST	Estonian
FAO	Faroese
FIN	Finnish
FRE	French
GEO	Georgian
GER	German
HEB	Hebrew
HIN	Hindi
HUN	Hungarian
ICE	Icelandic
ITA	Italian
JPN	Japanese
KOR	Korean
KUR	Kurdish
LAO	Lao
LAV	Latvian
LIT	Lithuanian
MAC	Macedonian
MAL	Malayalm
NEP	Nepali
NOR	Norwegian
PER	Persian
POL	Polish
POR	Portuguese
RUM	Romanian
RUS	Russian
SAN	Sanskirt
SCC	Serbian
SCR	Croatian

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

SLO	Slovak
SLV	Slovenian
SPA	Spanish
SWA	Swahili
SWE	Swedish
SYR	Syriac
TAM	Tamil
THA	Thai
TIB	Tibetan
TUR	Turkish
UKR	Ukrainian
URD	Urdu
UZB	Uzbek
VIE	Vietnamese
ZHO	Chinese

Keywords: @language language code

Last update: 2015-11-09 17:46

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COME-<number>, e.g. COME-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
.."-individual	[YN]	yes
.."-lname	[\x20-\x7e]{0,80}	no, if name is given
.."-fname	[\x20-\x7e]{0,80}	no, if name is given
.."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
.."-title	[\x20-\x7e]{0,80}	no
.."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
.."-address-1	[\x20-\x7e]{1,80}	yes
.."-address-2	[\x20-\x7e]{0,80}	no
.."-address-3	[\x20-\x7e]{0,80}	no
.."-postal-code	[\x20-\x7e]{1,50}	yes
.."-city	[\x20-\x7e]{1,80}	yes
.."-state	[\x20-\x7e]{0,80}	no
.."-country	@country	yes
.."-email	@email	yes

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

.."-phone	[\x20-\x7e]{1,50}	yes
.."-fax	[\x20-\x7e]{0,50}	no

An existing contact (**@mecont** or **@same-as**) (.me only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:COME-176269
admin-contact-handle:COME-176229
tech-contact-handle:COME-176269
billing-contact-handle:COME-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .me-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @mecont @same-as admin tech billing owner

Last update: 2008-08-14 11:46

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Macros

Create a dns-configuration

Introduction

With this request you can create or modify a zonefile at the joker-nameserver.

You can add A-Records, CNAME-Records, MX-Records, a nameservice-based Url-forwarding and a frame-based Url-forwarding. Modifing the TTL is not possible.

The format of this request is a little bit different from the other requests. Please check the given examples for how to specify the different zonefile-records.

ATTENTION:

You have to change the nameservers for a domain to the nameservers of joker.com first!

- a.ns.joker.com
- b.ns.joker.com
- c.ns.joker.com

If you would like to use the joker-nameservice, you will have to use **all** joker-nameservers.

It is **not** possible to use the joker-nameservice

- for primary nameservice only
- for secondarynameservice only

All joker-nameservers

- are configured to deny all zone-fetching requests!
- do not query foreign nameservers!

Request Fields

Definition of this request

request-field	valid values	required
domainID	[illegible]	yes
A	[illegible]	no
CNAME	[illegible]	no
MX	[illegible]	no
URL	[illegible]	no
FRAME	[illegible]	no

Example 1: **create dns-config** (without url-forwarding and without wildcard-matching)

subject: create dns-config [your reference id]

domainID:harenose.net

A:www:194.33.110.19

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

A:mail:194.33.110.19

A:mail2:194.33.110.20

A:@:194.33.110.10

MX:www.hansnose.net:70:mail.nrw.net

MX:www.hansnose.net:80:mail2.nrw.net

MX:@:70:mail.hansnose.net

MX:@:80:mail2.hansnose.net

CNAME:www2:some.other.domain.com

Example 2: **create dns-config** (with wildcard-matching)

subject: create dns-config [your reference id]

domainid:hansnose.net

A:www:194.33.110.19

A:@:194.33.110.19

A:*:194.33.110.20

Example 3: **create dns-config** (with dns-based url-forwarding)

subject: create dns-config [your reference id]

domainid:hansnose.net

A:www:194.33.110.19

A:@:194.33.110.19

URL:www2:http://www.sone.other.domain.com/index.html

(that means, the url within the browserbar is changing to the target address)

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

DNS/URL-Forwarding

Example 4: **create dns-config** (with frame-based url-forwarding)

subject: create dns-config [your reference id]

domains0:hansnose.net

A:www:194.33.110.19

A:@:194.33.110.19

FRAME:www2:http://www.sone.other.domain.com/index.html

*(that means, the url within the browserbar is **not** changing to the target address)*

Keywords: nameserver, records, zone, forwarding

Last update: 2011-08-11 15:37

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

DNS/URL-Forwarding

Delete a dns-configuration

Introduction

With this request you can delete a zonefile at the joker-nameserver.

Request fields

mailsubject: delete dns-config [your reference id]

Definition of this request

Request field	Field values	Required
domain0	domain	ok

Example 1: **delete dns-config**

subject: delete dns-config [your reference id]
domain0 hansnose.net

Keywords: nameserver,dns-config,records, forwarding

Last update: 2011-08-11 15:37

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

List a dns-configuration

Introduction

With this request you can get a listing of a current zonefile.

Request fields

mailsubject: list dns-config [your reference id] definition of this request

request-field	valid values	required
domains0	@fqdn	yes

Example 1: **list dns-config**

subject: list dns-config [your reference id]

domains0:hansnose.net

Keywords: nameserver,dns-config,records, forwarding

Last update: 2011-08-11 15:38

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

DNS/URL-Forwarding

Create an order

Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
- xxx
- asia
- me

With this request you can register one or more domains.

You have to provide the following information within the request:

- domain name(s),
- owner-contact-handle,
- admin-contact-handle,
- tech-contact-handle,
- billing-contact-handle,
- nameserver information,
- additional services, if required.

You can register up to 501 domains with one request.

If you register more than one domain with a request, all domains registerd with this request will have the same contact and nameserver structure.

There are two new requestfields within this request:

- name

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

- address-3

ATTENTION

Please, refer to the table for the corresponding contact handles.

TLD	Contact handle
com	CCOM-<number>
net	CNET-<number>
org	CORG-<number>
info	C<number>-LRMS
biz	CNEU-<number>
mobi	COMO-<number>
name	CNAM-<number>
us	COUS-<number>
de	CODE-<number>
cn	COCN-<number>
eu	C<number>
me	COME-<number>
asia	COAS-<number>
xxx	CONX-<number>

Request fields

mailsubject: create <tld>-order [your reference id]

Definition of this request

tld	request field		
	domains[0..500]	period	language[0..500]
com	[a-z0-9-]{1,63}\.com	^([1..9]{1})$	@language
net	[a-z0-9-]{1,63}\.net	^([1..9]{1})$	
org	[a-z0-9-]{1,63}\.org	^([1..9]{1})$	
info	[a-z0-9-]{1,63}\.info	^([1..9]{1})$	
biz	[a-z0-9][a-z0-9-]{1,6	^([1..9]{1})$	

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

	1}[a-z0-9]\.biz		
mobi	[a-z0-9-]{1,63}\.mobi	^([1..9]{1})$	
name	[a-z0-9-]{1,63}\.name	^([2..9]{1})$	
us	[a-z0-9-]{1,63}\.us	^([2..9]{1})$	
de	[a-z0-9-]{1,63}\.de	^([1..9]{1})$	
cn	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.cn	^([1..9]{1})$	
eu	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.eu	^([1..9]{1})$	
me	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.me	^([1..9]{1})$	
asia	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.asia	^([1..9]{1})$	
xxx	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.xxx	^([1..9]{1})$	
required	yes	yes	no (IDN domains only)

tld	owner-contact-handle	admin-contact-handle	tech-contact-handle	billing-contact-handle
com	@comcont			
net	@netcont			
org	@orgcont			
info	@infocont			
biz	@decont			
mobi	@mobicont			
name	@namecont			
us	@uscont			
de	@bizcont			
cn	@cncont			
eu	@eucont			
me	@mecont			
asia	@asiacon			
required	yes			

tld	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle
<tld>	@ns					
required	yes	yes	no			

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

.COM order

Example 1: create com-order with implicit contact-handle-creation of the owner-contact

subject: create com-order [your reference id]

domains0:xn--hans-mller-feb.com
language0:AFR
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create com-order with implicit nameserver-creation

subject: create com-order [your reference id]

domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create com-order with implicit contact-handle-creation of all contacts

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

subject: create com-order [your reference id]

domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.NET order

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Example 1: create net-order with implicit contact-handle-creation of the owner-contact

subject: create net-order [your reference id]

domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create net-order with implicit nameserver-creation

subject: create net-order [your reference id]

domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create net-order with implicit contact-handle-creation of all contacts

subject: create net-order [your reference id]

domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.ORG order

Example 1: create org-order with implicit contact-handle-creation of the owner-contact

subject: create org-order [your reference id]

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

domains0:xn--hans-mller-feb.org
language0:AFR
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create org-order with implicit nameserver-creation

subject: create org-order [your reference id]

domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-handle:CORG-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create org-order with implicit contact-handle-creation of all contacts

subject: create org-order [your reference id]

domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.INFO order

Example 1: create info-order with implicit contact-handle-creation of the owner-contact

subject: create info-order [your reference id]

domains0:xn--hans-mller-feb.info
language0:AFR
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C282828-LRMS
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create info-order with implicit nameserver-creation

subject: create info-order [your reference id]

domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-handle:C176269-LRMS
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C176219-LRMS
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create info-order with implicit contact-handle-creation of all contacts

subject: create info-order [your reference id]

domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.BIZ order

Example 1: create biz-order with implicit contact-handle-creation of the owner-contact

domains0:xn--hans-mller-feb.biz
language0:AFR
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create biz-order with implicit nameserver-creation

subject: create biz-order [your reference id]

domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-handle:CNEU-123
admin-contact-handle:CNEU-124
tech-contact-handle:CNEU-125
billing-contact-handle:CNEU-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create biz-order with implicit contact-handle-creation of all contacts

subject: create biz-order [your reference id]

domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.MOBI ORDER

Example 1: create mobi-order with implicit contact-handle-creation of the owner-contact

subject: create mobi-order [your reference id]

domains0:xn--hans-mller-feb.mobi
language0:AFR
domains1:minus-10a.mobi

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create mobi-order with implicit nameserver-creation

subject: create mobi-order [your reference id]

domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-handle:COMO-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create mobi-order with implicit contact-handle-creation of all contacts

subject: create mobi-order [your reference id]

domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.NAME ORDER

Example 1: create name-order with implicit contact-handle-creation of the owner-contact

subject: create name-order [your reference id]

domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-email:gonzo@nose.net

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create name-order with implicit nameserver-creation

subject: create name-order [your reference id]

domains0:minus-109.name
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-handle:CNAM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create name-order with implicit contact-handle-creation of all contacts

subject: create name-order [your reference id]

domains0:minus-109.name
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.US ORDER

Example 1: create us-order with implicit contact-handle-creation of the owner-contact

subject: create us-order [your reference id]

domains0:xn--hans-mller-feb.us
language0:AFR
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

tech-contact-handle:same-as-admin-contact
billing-contact-handle:COUS-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create us-order with implicit nameserver-creation

subject: create us-order [your reference id]

domains0:minus-109.us
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-handle:COUS-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COUS-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create us-order with implicit contact-handle-creation of all contacts

subject: create us-order [your reference id]

domains0:minus-109.us
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.DE ORDER

Example 1: create de-order with implicit contact-handle-creation of the owner-contact

subject: create de-order [your reference id]

domains0:minus-10x.de
language0:GER
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nase
owner-contact-address-1:Musterstrasse 11
owner-contact-postal-code:4711
owner-contact-city:Musterhausen
owner-contact-country:DE
owner-contact-phone:49 13383794 504040
owner-contact-fax:49 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CODE-1007
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create net-order with implicit nameserver-creation

subject: create de-order [your reference id]

domains0:minus-109.de
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-handle:CODE-1007
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CODE-1007
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create net-order with implicit contact-handle-creation of all contacts

subject: create de-order [your reference id]

domains0:minus-109.de
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nase
owner-contact-address-1:Musterstrasse 11
owner-contact-postal-code:4711
owner-contact-city:Musterhausen
owner-contact-country:DE
owner-contact-phone:49 13383794 504040
owner-contact-fax:49 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nase
admin-contact-address-1:Musterstrasse 11
admin-contact-postal-code:4711
admin-contact-city:Musterhausen
admin-contact-country:DE
admin-contact-phone:49 13383794 504040
admin-contact-fax:49 13383794 504040
tech-contact-email:gonzo@nose.net
tech-contact-individual:Y
tech-contact-fname:gonzo
tech-contact-lname:nase
tech-contact-address-1:Musterstrasse 11
tech-contact-postal-code:4711
tech-contact-city:Musterhausen
tech-contact-country:DE
tech-contact-phone:49 13383794 504040
tech-contact-fax:49 13383794 504040
billing-contact-email:gonzo@nose.net

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nase
billing-contact-address-1:Musterstrasse 11
billing-contact-postal-code:4711
billing-contact-city:Musterhausen
billing-contact-country:DE
billing-contact-phone:49 13383794 504040
billing-contact-fax:49 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.CN ORDER

Example 1: create cn-order with implicit contact-handle-creation of the owner-contact

subject: create cn-order [your reference id]

domains0:xn--hans-mller-feb.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create cn-order using existing cn-handles

subject: create cn-order [your reference id]

domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-handle:COCN-123
admin-contact-handle:COCN-124
tech-contact-handle:COCN-125
billing-contact-handle:COCN-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create cn-order with backreferences using @same-as

subject: create cn-order [your reference id]

domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
ns1-domain-name:nsxx1.gonzo.net

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.EU ORDER

Example 1: create eu-order with implicit contact-handle-creation of all contacts

subject: create eu-order [your reference id]

domains0:xn--hans-mller-feb.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create eu-order using existing .eu-handles

subject: create eu-order [your reference id]

domains0:minus-109.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-handle:C123123
admin-contact-handle:C123124
tech-contact-handle:C123125
billing-contact-handle:C123126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create eu-order with backreferences using @same-as

subject: create eu-order [your reference id]

domains0:minus-109.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Keywords: create, order, registration

Last update: 2015-07-29 12:02

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains
Modify a domain

Introduction

modify <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
- xxx
- asia
- me

With this request you can modify existing domains. You have to provide the following information within the

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

request:

- the domainname,
- handle(s) you want to change. (handles from the info-system are not valid)

The system will ignore not specified handles, so you have to provide only the handles, you would like to change.

Changes within the owner-contact

In case of changing the owner-contact-handle, the system checks, if lname and/or fname and/or organization differ from the original owner-contact-handle. If there are differences these changes will be ignored.

Request fields

mailsubject: modify <tld>-domain [your reference id]

Definition of this request

request-field	valid values		required
tld	com|net|org|info|mobi|name|us|de	biz|eu	yes
sld	[a-z0-9-]{1,63}	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]	yes
owner-contact-handle	Please, refer to the table below for the valid values.		no
admin-contact-handle			no
tech-contact-handle			no

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

billing-contact-handle		no
ns1-handle	@ns	no
ns2-handle		no
ns3-handle		no
ns4-handle		no
ns5-handle		no
ns6-handle		no

tld	contact handle
com	@comcont
net	@netcont
org	@orgcont
info	@infocont
biz	@bizcont
mobi	@mobicont
name	@namecont
us	@uscont
de	@decont
cn	@cncont
eu	@eucont

Example 1: modify com-domain

subject: modify domain [your reference id]

sld:gonzo
tld:com
admin-contact-handle:gonzo@nose.com#0
tech-contact-handle:hans@nose.com
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: modify net-domain

subject: modify net-domain [your reference id]

sld:gonzo
tld:net
admin-contact-handle:CNET-1234
tech-contact-handle:CNET-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Example 3: modify org-domain

subject: modify net-domain [your reference id]

sld:gonzo
tld:org
admin-contact-handle:CORG-1234
tech-contact-handle:CORG-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 4: modify info-domain

subject: modify info-domain [your reference id]

sld:gonzo
tld:info
admin-contact-handle:C112234-LRMS
tech-contact-handle:C112244-LRMS
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

OR

modify info-domain (new naming convention for info-handles)

subject: modify info-domain [your reference id]

sld:gonzo
tld:info
admin-contact-handle:C112244-LRMS
tech-contact-handle:CAFI-007
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 5: modify biz-domain

subject: modify biz-domain [your reference id]

sld:gonzo
tld:biz
admin-contact-handle:CNEU-11224
tech-contact-handle:CNEU-112244
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 6: modify mobi-domain

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

subject: modify mobi-domain [your reference id]

sld:gonzo
tld:mobi
admin-contact-handle:COMO-1234
tech-contact-handle:COMO-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 7: modify name-domain

subject: modify name-domain [your reference id]

sld:gonzo
tld:name
admin-contact-handle:CNAM-1234
tech-contact-handle:CNAM-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 8: modify us-domain

subject: modify us-domain [your reference id]

sld:gonzo
tld:us
admin-contact-handle:COUS-1234
tech-contact-handle:COUS-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 9: modify de-domain

subject: modify de-domain [your reference id]

sld:gonzo
tld:de
admin-contact-handle:CODE-1234
tech-contact-handle:CODE-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 10: modify cn-contact

subject: modify cn-contact [your reference id]

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

handle:COCN-1235
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 11: modify eu-domain

subject: modify eu-domain [your reference id]

sld:gonzo
tld:eu
admin-contact-handle:C112244
tech-contact-handle:C112244
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Keywords: modify-domain, nameserver, contacts

Last update: 2015-07-29 12:02

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

Renew a domain

Introduction

renew <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s),
- the renewalperiod or the desired expirationyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.
If the sum of the expire time and the renewal time is more then 10 years, we will reject your request.
This request is not working for domains, which are located on the old system. For these domains you have to check the documentation of the old system.

If you provide the expire year, this request will rejected, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew-request is sent twice by mistake.

Request fields

mailsubject: renew <tld>-domain [your reference id]

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

Definition of this request

You have to provide the domain name and the renewal period or the desired expire year using the format "YYYY" on one line. You have to seperate each field with a ":" (ASCII 058). The maximum for the renewal period is 9 years.

request-field	field values	required
domain[0..500]	[a-z0-9.]{1,63}[-.][a-z0-9]{2,63}	yes

.COM renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew com-domain [your reference id]

domains0:minus-106:com:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew com-domain [your reference id]

domains0:minus-106:com:4
domains1:minus-118:com:4
domains2:minus-129:com:4
domains3:minus-136:com:4
domains4:minus-148:com:4

Example 3: renew 5 domains for different years using the field period

subject: renew com-domain [your reference id]

domains0:minus-106:com:1
domains1:minus-118:com:2
domains2:minus-126:com:3
domains3:minus-136:com:4
domains4:minus-148:com:5

Example 4: renew 1 domain using the field expirationyear

subject: renew com-domain [your reference id]

domains0:minus-106:com:2005

.NET Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew net-domain [your reference id]

domains0:minus-106:net:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew net-domain [your reference id]

domains0:minus-106:net:4
domains1:minus-118:net:4
domains2:minus-126:net:4
domains3:minus-136:net:4
domains4:minus-148:net:4

Example 3: renew 5 domains for different years using the field period

subject: renew net-domain [your reference id]

domains0:minus-106:net:1
domains1:minus-118:net:2
domains2:minus-126:net:3
domains3:minus-136:net:4
domains4:minus-148:net:5

Example 4: renew 1 domain using the field expirationyear

subject: renew net-domain [your reference id]

domains0:minus-106:net:2005

.ORG Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew org-domain [your reference id]

domains0:minus-106:org:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew org-domain [your reference id]

domains0:minus-106:org:4
domains1:minus-118:org:4
domains2:minus-126:org:4
domains3:minus-136:org:4
domains4:minus-148:org:4

Example 3: renew 5 domains for different years using the field period

subject: renew org-domain [your reference id]

domains0:minus-106:org:1
domains1:minus-118:org:2
domains2:minus-126:org:3
domains3:minus-136:org:4
domains4:minus-148:org:5

Example 4: renew 1 domain using the field expirationyear

subject: renew org-domain [your reference id]

domains0:minus-106:org:2005

.INFO Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew info-domain [your reference id]

domains0:minus-106:info:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew info-domain [your reference id]

domains0:minus-106:info:4
domains1:minus-118:info:4
domains2:minus-126:info:4
domains3:minus-136:info:4
domains4:minus-148:info:4

Example 3: renew 5 domains for different years using the field period

subject: renew info-domain [your reference id]

domains0:minus-106:info:1
domains1:minus-118:info:2
domains2:minus-126:info:3
domains3:minus-136:info:4
domains4:minus-148:info:5

Example 4: renew 1 domain using the field expirationyear

subject: renew info-domain [your reference id]

domains0:minus-106:info:2005

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

.BIZ Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:4
domains1:minus-119.biz:4
domains2:minus-129.biz:4
domains3:minus-139.biz:4
domains4:minus-149.biz:4

Example 3: renew 5 domains for different years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1
domains1:minus-119.biz:2
domains2:minus-129.biz:3
domains3:minus-139.biz:4
domains4:minus-149.biz:5

Example 4: renew 1 domain using the field expirationyear

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:2005

.NAME Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:4
domains1:minus-119.name:4
domains2:minus-129.name:4
domains3:minus-139.name:4
domains4:minus-149.name:4

Example 3: renew 5 domains for different years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1
domains1:minus-119.name:2
domains2:minus-129.name:3
domains3:minus-139.name:4
domains4:minus-149.name:5

Example 4: renew 1 domain using the field expirationyear

subject: renew name-domain [your reference id]

domains0:minus-109.name:2005

.US Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:4
domains1:minus-119.us:4
domains2:minus-129.us:4
domains3:minus-139.us:4
domains4:minus-149.us:4

Example 3: renew 5 domains for different years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1
domains1:minus-119.us:2
domains2:minus-129.us:3
domains3:minus-139.us:4
domains4:minus-149.us:5

Example 4: renew 1 domain using the field expire year

subject: renew us-domain [your reference id]

domains0:minus-109.net:2005

.DE Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:4
domains1:minus-119.de:4
domains2:minus-129.de:4
domains3:minus-139.de:4
domains4:minus-149.de:4

Example 3: renew 5 domains for different years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1
domains1:minus-119.de:2
domains2:minus-129.de:3
domains3:minus-139.de:4
domains4:minus-149.de:5

Example 4: renew 1 domain using the field expirationyear

subject: renew de-domain [your reference id]

domains0:minus-109.de:2005

.CN Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:4
domains1:minus-119.cn:4
domains2:minus-129.cn:4
domains3:minus-139.cn:4
domains4:minus-149.cn:4

Example 3: renew 5 domains for different years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1
domains1:minus-119.cn:2
domains2:minus-129.cn:3
domains3:minus-139.cn:4
domains4:minus-149.cn:5

Example 4: renew 1 domain using the field expire year

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:2005

Keywords: renew, renewal

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

Last update: 2011-08-11 14:18

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

Transfer a domain

Introduction

transfer <tld>domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can transfer a domain from 1 registrar to Joker.com.
You have to provide the following information within the request:

- the domain name,
- the auth-id,
- the billing-contact-handle,

You can transfer 1 com domain with one request.

If you transfer a domain to Joker.com the domain will be renewed for one year.

As you can see, we dont need information about the owner-contact. We will detect this information from the whois of the current registrar and we will create the contact-handle for the owner-contact automatically.

You need to provide us with a so called auth-id. You have to ask the current registrar for this auth-id. If you provide an invalid auth-id, the transfer will be declined by the current registrar.

As you can see, we need the billing-contact-handle. We recommend using a billing-handle with the email-address of your "robot-email". If you use a contact-handle with a different e-mail than your robot e-mail, you can't administer the transfered domain using the webinterface and the person with access to the email, which is shown in the provided billing-handle will have access using the web-interface.

If you don't have a com-contact-handle with your "robot-email", you have to create a com-handle using the "create com-contact" request.

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

We do not need information about the nameservers. This information will be detected from the whois of the current registrar and we will create the nameservers if necessary.

This procedure implies, that an owner change or change of nameservers during the transfer-process is not possible.

Request fields

mailsubject: transfer <tld>-domain [your reference id]

ATTENTION:

You can transfer 1 domain with one request.

Definition of this request

request-field	field values	required
domainid	a-zA-Z [1,63]-<tld>	yes
auth-id	-	yes
billing-contact-handle	Please, refer to the table below.	yes

	billing-contact-handle
com	[illegible]
net	[illegible]
org	[illegible]
eu	[illegible]
ch	[illegible]
com	[illegible]
name	[illegible]
ch	[illegible]
ch	[illegible]
ch	[illegible]
ch	[illegible]

TRANSFER COM DOMAIN

Example 1: transfer com-domain

subject: transfer com-domain [your reference id]
domaine0 minus-109.com
auth-id:0293XaAdA
billing-contact-handle:CCOM-1234

TRANSFER NET DOMAIN

Example 1: transfer net-domain

subject: transfer net-domain [your reference id]

domaine0 minus-109.net
auth-id:0293XaAdA
billing-contact-handle:CNET-1234

TRANSFER ORG DOMAIN

Example 1: transfer org-domain

subject: transfer org-domain [your reference id]

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

domain0 minus-109.org
auth-id:02932AAdA

billing-contact-handle:CORG-1234

TRANSFER INFO DOMAIN

Example 1: transfer info-domain

subject: transfer info-domain [your reference id]

domain0 minus-109.info
auth-id:02932AAdA
billing-contact-handle:C176269-LRMS

TRANSFER BIZ DOMAIN

Example 1: transfer biz-domain

subject: transfer biz-domain [your reference id]

domain0 minus-109.biz
auth-id:02932AAdA
billing-contact-handle:CNEU-123

TRANSFER NAME DOMAIN

Example 1: transfer name-domain

subject: transfer name-domain [your reference id]

domain0 minus-109.name
auth-id:02932AAdA

billing-contact-handle:CNAM-1234

TRANSFER US DOMAIN

Example 1: transfer us-domain

subject: transfer us-domain [your reference id]

domain0 minus-109.us
auth-id:02932AAdA

billing-contact-handle:COUS-1234

TRANSFER DE DOMAIN

Example 1: transfer de-domain

subject: transfer de-domain [your reference id]

domain0 minus-109.de
auth-id:02932AAdA
billing-contact-handle:CODE-1234

TRANSFER CN DOMAIN

Example 1: transfer cn-domain

subject: transfer cn-domain [your reference id]

domain0 minus-109.cn
auth-id:02932AAdA
billing-contact-handle:COCN-1234

Keywords: transfer, auth-id

Last update: 2011-08-11 14:14

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

Delete a domain

Introduction

With this request you can delete a domain at Joker.com.

You have to provide the following information within the request:

- domain name(s),
- the special flag force

ATTENTION:

If you delete a domain within the first 72 hours after the registration, the registration-fee will be refunded to your account.

If Joker.com receives the delete-request more than 72 hours after the registration, you have to provide the flag "force:1", in order to accept that the registration-fee will not be refunded to your account. If you do not send the "force:1" in such a case, the request will be rejected.

Request fields

mailsubject: delete domain [your reference id]

Definition of this request

Please, do not forget to provide the domain name and the force-flag set to 1 if the domain is older 72h.

equest-field	alid values	equired
ld	(com|net|org|info|biz|mobi|name|de|cn|eu|us)	yes
sld	a-z0-9-]{1,63}	yes
orce	1|0	no

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

DELETE COM DOMAIN

Example 1: delete a domain during the first 72 hours after registration
subject: delete domain [your reference id]

tld:com
sld:frezel

Example 2: delete a domain after the first 72 hours after registration
subject: delete domain [your reference id]

tld:com
sld:frezel
force:1

Example 3: delete a domain only for the case that a refund is possible!
subject: delete domain [your reference id]

tld:com
sld:frezel
force:0

Keywords: delete-domain

Last update: 2011-08-11 15:45

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

List domains

Introduction

list domains

With this request you can get a list (lexicographically sorted) of all the domains, you have currently registered at joker.com.
You have to provide the target-registry within the request:

cno = .com/.net

com = .net

net = .net

org = .org

info = .info

biz = .biz

mobi = .mobi

name = .mobi

de = .de

cn = .cn

eu = .eu

us = .us

LIMITATIONS:

- Only 20.000 domains are listed. If you have more than 20.000 domains under 1 registry at joker.com, you have to track the domain names yourself.
- In case you have more than 20.000 domains at joker.com under 1 registry, this request will not work for you. The listing would be incomplete and it will be missing random domains.
- This request works only with the new joker.com system.

Request fields

mailsubject: list domains [your reference id]

Definition of this request:

Request field	Field values	Required
target	cno/com/net/org/info/biz/mobi/name/de/cn/eu/us	yes

LIST DOMAINS

Example 1: list domains for .com-domains
subject: list domains [your reference id]
target:com

Example 2: list domains for .net-domains
subject: list domains [your reference id]
target:net

Example 3: list domains for .org-domains
subject: list domains [your reference id]
target:org

Example 4: list domains for .info-domains
subject: list domains [your reference id]
target:info

Example 5: list domains for .biz-domains
subject: list domains [your reference id]
target:biz

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

Example 6: list domains for .de-domains
subject: list domains [your reference id]
target:de

Example 7: list domains for .cn-domains
subject: list domains [your reference id]
target:cn

Keywords: list-domains

Last update: 2011-08-11 15:44

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains
Lock a domain

Introduction

lock domain

With this request you can lock a domain in order to prevent fraudulent transfer attempts. If a domain is locked, each transfer-request from a foreign registrar will be declined.

You have to provide the following information within the request:

- domain name

You can lock 1 domain with one request.

Request fields

mailsubject: lock domain [your reference id]

Definition of this request

request-field	valid values	required
domain	domain	yes

Example 1: lock a domain
subject: lock domain [your reference id]

fqdn:minus-109.com

Keywords: lock-domain, protection

Last update: 2011-08-11 15:46

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains
Unlock a domain

Introduction

unlock domain

With this request you can unlock a domain. If you want to transfer a domain to a foreign registrar, the domain has to be unlocked.

You have to provide the following informations within the request:

- domain name

You can unlock 1 domain with one request.

Request fields

mailsubject: unlock domain [your reference id]

Definitions of this request

Parameter name	Valid values	Required
auth	password	yes

Example 1: unlock a domain

subject: unlock domain [your reference id]

fqdn minus-109.com

Keywords: unlock-domain, protection

Last update: 2011-08-11 15:46

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains
Get Auth-id

Introduction

With this request you can retrieve the auth-id for a particular domain. That request is needed only for the TLD's .org/.info/.biz.

You have to provide the following information within the request:

- domain name

You can retrieve the auth-id for 1 domain with one request.

Request fields

mail/subject: get auth-id [your reference id]

Definition of this request:

Request field	Valid values						Required
type							yes

Example 1: retrieve the auth-id for a .org-domain
subject: get auth-id [your reference id]
fqdn:minus-109.org

Example 2: retrieve the auth-id for a .biz-domain
subject: get auth-id [your reference id]
fqdn:minus-109.biz

Example 3: retrieve the auth-id for a .eu-domain
subject: get auth-id [your reference id]
fqdn:minus-109.eu

Keywords: transfer, auth-id

Last update: 2011-08-11 15:46

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

Grant Roles/Domain Permissions, Internal Transfer

Introduction

With this request you can assign 'Roles' (permissions) of domains to other Joker.com users. The special role "creator" is an equivalent to an internal transfer of that domain to another Joker.com user.In this case, the domain is assigned to the receiving account, including all rights and permissions on this domain.

There are two variants to use this functionality: If the user id (Joker.com user account-id) is given, and the account id matches the associated email address, the role is applied immediately - there will be no request for confirmation on the receiver's side. In case the user id is not given, but only the email address, the transaction has to be acknowledged by the receiver. For this, he will get an email, containing a link and a key. Either the link has to be clicked, or the key has to be applied using Joker.com (=> Transfer). This can also be used for users which do not yet have a Joker.com account.

You have to provide the following parameters:

- domain name (the domain you want to grant somebody else permissions on)
- destination client email (the email address of the user you want to receive permissions)

The following parameters are optional:

- destination client id (ID of Joker.com account - always shown in the upper right on Joker.com, also conforms to "reseller id" - must match the 'destination client email')
- desired role (type of permission you want to assign to "client email" resp. "client id" - one of "admin|tech|billing|creator"; "creator" means "all permissions" and is equivalent to an **internal transfer** or 'assignment' - also see 'roles')

Request fields

mailsubject: joker-internal-transfer [your reference id]

Definition of this request

Valid values for <tld> **all** Joker.com tlds

request-field	valid values	required
domain	[a-z0-9-]{1,63}\.<tld>	yes
destination-client-email	@email	yes
destination-client-id	[0-9]+	no
desired-role	admin|tech|billing|creator (if omitted, default is 'creator')	no

Example 1: assign 'billing'-role to user 123456 (direct)

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

subject: joker-internal-transfer [your reference id]

```
body:
fqdn:exampledomain.com
destination-client-email:example-user@gmail.com
destination-client-id:123456
desired-role:billing
```

Example 2: assign 'creator'-role to user 'example-user@gmail.com' (internal transfer with invitation)

subject: joker-internal-transfer [your reference id]

body:

```
fqdn:exampledomain.com
destination-client-email:example-user@gmail.com
desired-role:creator
```

Keywords: grants, roles, contacts, permissions, invitations

Last update: 2011-08-17 09:35

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Domains

Create a contact

Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

With this request you can create person contacts. You can create 1 contact with one request.

ATTENTION:

You will find the request-field "individual" within the request-definition. If you set it to "Y", you have to provide the request-fields "fname" and "lname" or "name". If you set it to "N", you have to provide information in the request-field "organization".

As the whois for .com shows a field called person, the rules for generating this field are the following:
If you provide the field "name", the whois is showing always the values of this field, regardless of "fname" and "lname".

If you only provide the field "fname" and the field "lname", we will generate the field "name" as the result of the concatenation of "fname" + " " + "lname".

The result of "create com-contact" is a reference which is following the format:

- CCOM-<number> e.g. CCOM-176269 for a .com domain.
- CNET-<number> e.g. CNET-176269 for a .net domain.
- CORG-<number> e.g. CORG-176269 for a .org domain.
- C<number>-LRMS e.g. C176269-LRMS for a .info domain.
- CNEU-<number> e.g. CNEU-176269 for a .biz domain.
- COMO-<number> e.g. COMO-176269 for a .mobi domain.
- CNAM-<number> e.g. CNAM-176269 for a .name domain.
- CDUS-<number> e.g. CDUS-176269 for a .us domain.
- CDDE-<number> e.g. CDDE-176269 for a .de domain.
- CDCN-<number> e.g. CDCN-176269 for a .cn domain.
- C<number> e.g. C176269 for a .eu domain.

Request fields

mailsubject: create <tld>-contact [your reference id]
Definition of this request

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

ATTENTION

According to the rules of DENIC, you have to provide a faxnumber for the admin-c and the tech-c of a **.de** domain.

request-field	valid values		required
	com|net|org|info|mobi|name|us|de	biz|cn|eu	
individual	[YN]		yes
fname	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	yes, if individual = Y
lname	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	yes, if individual = Y
name	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	yes, if fname **and/or** lname are not given
title	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
organization	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	yes, if individual = N
address-1	[\x20-\x7e]{1,80}	[\x20-\x7e]{1,30}	yes
address-2	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
address-3	Only for biz/cn/eu	[\x20-\x7e]{0,30}	no
postal-code	[\x20-\x7e]{1,50}	[\x20-\x7e]{1,10}	yes
city	[\x20-\x7e]{1,80}	[\x20-\x7e]{1,30}	yes
state	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
country	@country		yes
email	@email		yes
phone	[\x20-\x7e]{1,50}	[\x20-\x7e]{1,17}	yes
fax	[\x20-\x7e]{0,50}	[\x20-\x7e]{0,17}	yes (for admin-c and tech-c of .de only)

CREATE COM CONTACT

Example 1: create com-contact (name will be generated from fname and lname)

subject: create com-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 2: create com-contact (fname and lname will be ignored)

subject: create com-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CREATE NET CONTACT

Example 1: create net-contact (name will be generated from fname and lname)

subject: create net-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 2: create net-contact (fname and lname will be ignored)

subject: create net-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CREATE ORG CONTACT

Example 1: create org-contact (name will be generated from fname and lname)

subject: create org-contact [your reference id]

email:gonzo@nose.org
individual:Y
fname:gonzo
lname:nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

city:romsey
country:DE
phone:44 13383794 504040

Example 2: create org-contact (fname and lname will be ignored)

subject: create org-contact [your reference id]

email:gonzo@nose.org
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CREATE INFO CONTACT

Example 1: create info-contact (name will be generated from fname and lname)

subject: create info-contact [your reference id]

email:gonzo@nose.info
individual:Y
fname:gonzo
lname:nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 2: create info-contact (fname and lname will be ignored)

subject: create info-contact [your reference id]

email:gonzo@nose.info
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CREATE BIZ CONTACT

Example 1: create biz-contact (name will be generated from fname and lname)

subject: create biz-contact [your reference id]

email:gonzo@nose.biz
individual:Y
fname:gonzo
lname:nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 2: create biz-contact (fname and lname will be ignored)

subject: create biz-contact [your reference id]

email:gonzo@nose.biz
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE

phone:44 13383794 504040

CREATE NAME CONTACT

Example 1: create name-contact (name will be generated from fname and lname)

subject: create name-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 2: create name-contact (fname and lname will be ignored)

subject: create name-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CREATE US CONTACT

Example 1: create us-contact (name will be generated from fname and lname)

subject: create us-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 2: create us-contact (fname and lname will be ignored)

subject: create us-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE

phone:44 13383794 504040

CREATE DE CONTACT

Example 1: create de-contact (name will be generated from fname and lname)

subject: create de-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
address-1:Musterstrasse 19
address-2:App. 1
postal-code:4711
city:Musterstadt
country:DE
phone:49 13383794 504040

Example 2: create net-contact (fname and lname will be ignored)

subject: create net-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:Musterstrasse 19
address-2:App. 1
postal-code:4711
city:Musterstadt
country:DE
phone:49 13383794 504040

CREATE CN CONTACT

Example 1: create cn-contact (name will be generated from fname and lname)

subject: create cn-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 2: create cn-contact (fname and lname will be ignored)

subject: create cn-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE

phone:44 13383794 504040

CREATE EU CONTACT

Example 1: create eu-contact (name will be generated from fname and lname)

subject: create eu-contact [your reference id]

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 2: create eu-contact (fname and lname will be ignored)

subject: create eu-contact [your reference id]

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

email:gonzo@nose.net
individual:Y
fname:gonzo
lname:nose
name:Mr. Gonzo Nose
address-1:horsefair mews
address-2:App. 1
postal-code:4711
city:romsey
country:GE
phone:44 13383794 504040

Keywords: whois, contacts

Last update: 2011-08-11 15:38

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

Modify a contact

Introduction

With this request you can modify person contacts. You can modify 1 contact with one request. Unspecified request-fields will be ignored.

ATTENTION:

After changing the content of the specified contact, the whois information is automatically updated.

Keep in mind that you have to provide the numerical suffix of a handle.

- If you want to make an address change within the owner-record of a domain, you have to send a "modify com-domain"-request after changing the content of the specified handle.
- Only contact-handles, which are created by the reseller or where the e-mail within the contact is matching the reseller's robot-email can be changed.

Definition of this request

request-field	valid values		required
	[redacted]	[redacted]	
action	Please, refer to the table below.		yes
individual	Y/N		yes
name	[redacted]	[redacted]	no, if name is given
fname	[redacted]	[redacted]	no, if name is given
lname	[redacted]	[redacted]	yes, if fname **and/or** lname are not given
title	[redacted]	[redacted]	no
organization	[redacted]	[redacted]	no, if individual = N
address-1	[redacted]	[redacted]	yes
address-2	[redacted]	[redacted]	no
address-3	[redacted]	[redacted]	no
postal-code	[redacted]	[redacted]	yes
city	[redacted]	[redacted]	yes
state	[redacted]	[redacted]	no
country	[redacted]		yes
email	[redacted]		yes
phone	[redacted]	[redacted]	no
fax	[redacted]	[redacted]	no

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

			ies (for admin-c and tech-c of .de only)

TLD	handle
com	[COM#-<number>]
net	[NET-<number>]
org	[ORG-<number>]
info	[<number>-LRMS]
biz	[NEU-<number>]
name	[<NAME-<number>]
pro	[<PRO-<number>]
us	[<US-<number>]
eu	[<EU-<number>]
ch	[<CH-<number>]
de	[<number>]

MODIFY COM CONTACT

Example 1: modify com-contact

subject: modify com-contact [your reference id]

handle:CCOM-1235
address-1:hornefair mews
postal-code:4711
city:romney
country:DE
phone:44 13383794 504040

MODIFY NET CONTACT

Example 1: modify net-contact

subject: modify net-contact [your reference id]

handle:CNET-1235
address-1:hornefair mews
postal-code:4711
city:romney
country:DE
phone:44 13383794 504040

MODIFY ORG CONTACT

Example 1: modify org-contact

subject: modify org-contact [your reference id]

handle:CORG-1235
address-1:hornefair mews
postal-code:4711
city:romney
country:DE

phone:44 13383794 504040

MODIFY INFO CONTACT

Example 1: modify info-contact

subject: modify info-contact [your reference id]

handle:C293829-LRMS
address-1:hornefair mews
postal-code:4711
city:romney
country:DE
phone:44 13383794 504040

Example 2: modify info-contact (new naming convention for info-handles)

subject: modify info-contact [your reference id]

handle:CAR-607
address-1:hornefair mews
postal-code:4711
city:romney
country:DE
phone:44 13383794 504040

MODIFY BIZ CONTACT

Example 1: modify biz-contact

subject: modify biz-contact [your reference id]

handle:CNEU-12345
address-1:hornefair mews
postal-code:4711
city:romney
country:DE
phone:44 13383794 504040

MODIFY NAME CONTACT

Example 1: modify name-contact

subject: modify name-contact [your reference id]

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

handle:CNAM-1235
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE

phone:44 13383794 504040

MODIFY US CONTACT

Example 1: modify us-contact

subject: modify us-contact [your reference id]

handle:COUS-1235
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE

phone:44 13383794 504040

MODIFY DE CONTACT

Example 1: modify de-contact

subject: modify de-contact [your reference id]

handle:CODE-1235
address-1:Musterstrasse 1
postal-code:47011
city:Musterstadt
country:DE

phone:44 13383794 504040

MODIFY EU CONTACT

Example 1: modify eu-contact

subject: modify eu-contact [your reference id]

handle:C12345
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Keywords: whois, contacts

Last update: 2011-08-11 15:39

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

Change an address

Introduction

change <tld>-address

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can change the address of the domain owner.

ATTENTION:

It is not possible to change the following fields of the owner-record:

- individual
- lname
- fname
- title
- organization
- email

Request fields

mailsubject: change com-address [your reference id]

Definition of this request

request-field	valid values		required
	com/net/org/info/mobi/name/us/de	us/cn	
domain0	[a-z0-9-]{1,62}\.<tld>		yes
address-1	a20-\x7e{1,80}	\x20-\x7e{1,30}	no
address-2	a20-\x7e{0,80}	\x20-\x7e{0,30}	no
address-3	a20-\x7e{0,80}	\x20-\x7e{0,30}	no

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

postal-code	(x20-\x7e){1,50}	(x20-\x7e){0,30}	fax
fax	(x20-\x7e){1,50}	(x20-\x7e){0,30}	fax
state	(x20-\x7e){0,60}	(x20-\x7e){0,30}	fax
country	Germany		fax
phone	(x20-\x7e){1,50}	(\x20-\x7e){1,17}	fax
fax	(x20-\x7e){0,50}	(\x20-\x7e){0,17}	fax

CHANGE .COM ADDRESS

Example 1: change com-address

subject: change com-address [your reference id]

domains0.gonzo.com
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .NET ADDRESS

Example 1: change net-address

subject: change net-address [your reference id]

domains0.gonzo.net
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .ORG ADDRESS

Example 1: change org-address

subject: change org-address [your reference id]

domains0.gonzo.org
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .INFO ADDRESS

Example 1: change info-address

subject: change info-address [your reference id]

domains0.gonzo.info
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .BIZ ADDRESS

Example 1: change biz-address

subject: change biz-address [your reference id]

domains0.gonzo.biz
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .NAME ADDRESS

Example 1: change name-address

subject: change name-address [your reference id]

domains0.gonzo.name
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .US ADDRESS

Example 1: change us-address

subject: change us-address [your reference id]

domains0.gonzo.us
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .DE ADDRESS

Example 1: change de-address

subject: change de-address [your reference id]

domains0.gonzo.de
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE

phone:44 13383794 504040

CHANGE .CN ADDRESS

Example 1: change cn-address

subject: change cn-address [your reference id]

domains0.gonzo.cn
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Keywords: whois, contacts

Last update: 2011-08-11 15:39

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts
Change an owner

Introduction

With this request you can change the owner of a .com/.net/.org/.info./.mobi/.name/.biz/.de/.cn/.eu./us-domain.

Request fields

mailsubject: change owner [your reference id]

Definition of this request

request-field	valid values	required
domains0	[a-z0-9-]{1,63}\.(com|net|org|info|mobi|biz|de|cn|eu|us)	yes
email	an email **without** the numerical suffix	no
individual	[YN]	no
name ***(.com,.net,.org,.info,.biz,.mobi,.de,.cn,.eu,.us only)***	[\x20-\x7e]{0,80}	no
lname	[\x20-\x7e]{0,80}	no
fname	[\x20-\x7e]{0,80}	no
title	[\x20-\x7e]{0,80}	no
organization	[\x20-\x7e]{0,80}	no
address-1	[\x20-\x7e]{0,80}	no
address-2	[\x20-\x7e]{0,80}	no
postal-code	[\x20-\x7e]{0,50}	no
state	[\x20-\x7e]{0,80}	no
city	[\x20-\x7e]{0,80}	no
country	@country	no
phone	[\x20-\x7e]{0,50}	no
fax lock-opt-out	[\x20-\x7e]{0,50} [YN]	no no no

CHANGE .COM OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.com
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

phone:44 13383794 504040

CHANGE .NET OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.net
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .ORG OWNER

Example 1: change owner

subject: change owner [your reference id]
domains0:gonzo.org
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .INFO OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.info
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .BIZ OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.biz
fname:hans
lname:nose
address-1:horsefair mews

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .NAME OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.name
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .US OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.us
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .DE OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.de
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .CN OWNER

Example 1: change owner

subject: change owner [your reference id]

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

domains0:gonzo.cn
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Keywords: whois, contacts, transfer

Last update: 2016-11-21 15:06

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

.asia Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COAS-<number>, e.g. COAS-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname **and/or** lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[\x20-\x7e]{1,50}	yes
".."-fax	[\x20-\x7e]{0,50}	no

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Contacts

An existing contact (**@asiacont** or **@same-as**) (.asia only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:COAS-176269
admin-contact-handle:COAA-176229
tech-contact-handle:COAS-176269
billing-contact-handle:COAS-176269

ASIA-domains require an additional type of contact, the CED contact. This contact has to have its residence in the Asian/Australian area.

The Joker.com Registry Gateways automatically will use your provided tech-contact for the CED contact.

This means that the request for you remains consistent with the usual requests, you only have to make sure that the country code is correct, otherwise the .asia registry will reject the order.

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .asia-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: whois, contacts, asia

Last update: 2011-08-11 15:41

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Create a nameserver

Introduction

create <tld>-ns

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

With this request you can create an entry for a nameserver in the Joker.com database. If a nameserver is created, you can reference this nameserver using the hostname during a "create order"-request.

ATTENTION:

Only nameservers, which Joker.com is respondsible for, will be shown with the ip-address in the whois-output.

If you submit a "create-ns"-request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code-domain, the values for the ip-addresses are ignored.

Request fields

mailsubject: create <tld>-ns [your reference id]

<table>
<tr><th>request-field</th><th>valid values</th><th>required</th></tr>
<tr><td>ns-domain-name</td><td>([a-z0-9-]{1,63}\.)+(@country|com|net|org|int|edu|mil|biz|info|mobi|name)</td><td>yes</td></tr>
<tr><td>ns-ip-address</td><td>@ip</td><td>yes</td></tr>
</table>

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Nameservers

CREATE COM NAMESERVER

Example 1: create com-ns

subject: create com-ns [your reference id]

ns-domain-name:ns1.dummy.com
ns-ip-address:194.111.43.1

CREATE NET NAMESERVER

Example 1: create net-ns

subject: create net-ns [your reference id]

ns-domain-name:ns1.dummy.net
ns-ip-address:194.111.43.1

CREATE ORG NAMESERVER

Example 1: create org-ns

subject: create org-ns [your reference id]

ns-domain-name:ns1.dummy.org

ns-ip-address:194.111.43.1

CREATE INFO NAMESERVER

Example 1: create info-ns

subject: create info-ns [your reference id]

ns-domain-name:ns1.dummy.info
ns-ip-address:194.111.43.1

CREATE BIZ NAMESERVER

Example 1: create biz-ns

subject: create biz-ns [your reference id]

ns-domain-name:ns1.dummy.biz

ns-ip-address:194.111.43.1

CREATE NAME NAMESERVER

Example 1: create name-ns

subject: create name-ns [your reference id]

ns-domain-name:ns1.dummy.name

ns-ip-address:194.111.43.1

CREATE US NAMESERVER

Example 1: create us-ns

subject: create us-ns [your reference id]

ns-domain-name:ns1.dummy.us
ns-ip-address:194.111.43.1

CREATE DE NAMESERVER

Example 1: create de-ns

subject: create de-ns [your reference id]

ns-domain-name:ns1.dummy.de
ns-ip-address:194.111.43.1

CREATE CN NAMESERVER

Example 1: create cn-ns

subject: create cn-ns [your reference id]

ns-domain-name:ns1.dummy.cn
ns-ip-address:194.111.43.1

CREATE EU NAMESERVER

Example 1: create eu-ns

subject: create eu-ns [your reference id]

ns-domain-name:ns1.dummy.net
ns-ip-address:194.111.43.1

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Nameservers

Keywords: nameserver, modify domain

Last update: 2011-08-11 15:42

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Nameservers

Modify a nameserver

Introduction

modify <tld>-ns

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

With this request you can change the ip-address of a nameserver in the Joker.com database.

ATTENTION:

Only nameservers, which Joker.comis respondsible for, will be shown with the ip-address in the whois-output, so only these nameservers could be changed.

If you submit a "modify-ns"-request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code-domain, this request will be ignored.

Request fields

mailsubject: modify <tld>-ns [your reference id]

Definition of this request

<table>
<tr><th>request-field</th><th>valid values</th><th>required</th></tr>
<tr><td>ns-handle</td><td>[a-z0-9-]{1,63}\.)+(@country|com|net|org|int|edu|mil|biz|info|mobi|name)</td><td>yes</td></tr>
<tr><td>ns-ip-address</td><td>@ip</td><td>yes</td></tr>
</table>

MODIFY COM NAMESERVER

Example 1: modify com-ns

subject: modify com-ns [your reference id]

ns-handle:ns1.dummy.com

ns-ip-address:194.111.43.1

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Nameservers

MODIFY NET NAMESERVER

Example 1: modify net-ns

subject: modify com-ns [your reference id]

ns-handle:ns1.dummy.com

ns-ip-address:194.111.43.1

MODIFY ORG NAMESERVER

Example 1: modify org-ns

subject: modify org-ns [your reference id]

ns-handle:ns1.dummy.org
ns-ip-address:194.111.43.1

MODIFY INFO NAMESERVER

Example 1: modify info-ns

subject: modify info-ns [your reference id]

ns-handle:ns1.dummy.info
ns-ip-address:194.111.43.1

MODIFY BIZ NAMESERVER

Example 1: modify biz-ns

subject: modify biz-ns [your reference id]

ns-handle:ns1.dummy.biz ns-ip-address:194.111.43.1

MODIFY NAME NAMESERVER

Example 1: modify name-ns

subject: modify name-ns [your reference id]

ns-handle:ns1.dummy.name
ns-ip-address:194.111.43.1

MODIFY US NAMESERVER

Example 1: modify us-ns

subject: modify us-ns [your reference id]

ns-handle:ns1.dummy.us
ns-ip-address:194.111.43.1

MODIFY DE NAMESERVER

Example 1: modify de-ns

subject: modify de-ns [your reference id]

ns-handle:ns1.dummy.de
ns-ip-address:194.111.43.1

MODIFY CN NAMESERVER

Example 1: modify cn-ns

subject: modify cn-ns [your reference id]

ns-handle:ns1.dummy.cn
ns-ip-address:194.111.43.1

MODIFY EU NAMESERVER

Example 1: modify eu-ns

subject: modify eu-ns [your reference id]

ns-handle:ns1.dummy.com
ns-ip-address:194.111.43.1

Keywords: nameserver, modify-domain

Last update: 2011-08-11 15:42

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Nameservers

Support

Introduction

With this request you can send a question to the support team at Joker.com. Only questions, which are sent to the e-mail gateway are accepted.

ATTENTION:

Please, make sure that you sign your message with the keyset sent by you to Joker.com during your reseller registration. Please, also make sure not to include any characters that are not part of the 7-bit ASCII standard and do not use trailing blanks (i.e. every non blank line has to end with a non-whitespace character).

Request fields

mailsubject: support [your reference id]

Example 1

subject: support [your reference id]

-----BEGIN PGP SIGNED MESSAGE-----
Hash: SHA1

Enter your question here.
Dont forget the tgth in question

-----BEGIN PGP SIGNATURE-----
Version: GnuPG v1.0.2 (GNU/Linux)
Comment: For info see http://www.gnupg.org

ID7DBQEE2MMWqsl=dhNYRURAuWHAJ4sRewOrNc=yLMmmCouVcMP3vSnWQCdHUlf
UlogOuFmDmb3JS=7eRpAn
=Fame
-----END PGP SIGNATURE-----

Keywords: support,PGP

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Other

Last update: 2011-08-11 15:43

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Other

CheckD

please see section '2.5 Tools': Domain-Check

Keywords: checkd registration, whois, domain check

Last update: 2009-04-02 12:14

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Tools

Complete set of examples for download

We offer all examples summarized in a textfile. The file is attached to this article. As it has a lot of examples, it is recommended to use the search function of your text editor to find information.

Keywords: mail-gw, examples

Last update: 2012-09-27 16:33

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49

Examples

(c) 2023 Joker.com <webmaster@joker.com> | 2023-08-04 02:49