

Joker.com FAQ

Table of Content

2.3 Email Gateway	3
Basics	3
How does the PGP/GPG-Mailinterface work?	3
Where are the replies of the mail-gateway sent?	5
How do I change my robot-email-address?	6
What is the Joker.com public key?	7
Should I use PGP or GPG?	8
Differences to DMAPi	9
Requests	9
General Instructions	9
List of currently working requests	11
Macros	20
What is a macro?	20
E-mail Address	21
.com/.net Contacts	22
.com Contacts	24
.net Contacts	26
.org Contacts	28
.info Contacts	30
.biz Contacts	32
.mobi Contacts	35
.name Contacts	38
.us Contacts	40
.de Contacts	43
.cn Contacts	46
.eu Contacts	49
Valid domain names	52
Nameserver	53
Zonefile entries	54
IP	56
Domain renewal	57
Country code	58
Language code	64
.me Contacts	66
DNS/URL-Forwarding	68
Create a dns-configuration	68
Delete a dns-configuration	71
List a dns-configuration	72
Domains	73
Create an order	73
Modify a domain	98
Renew a domain	104

Transfer a domain	108
Delete a domain	111
List domains	113
Lock a domain	115
Unlock a domain	116
Get Auth-id	117
Grant Roles/Domain Permissions, Internal Transfer	118
Contacts	120
Create a contact	120
Modify a contact	124
Change an address	127
Change an owner	129
.asia Contacts	133
Nameservers	135
Create a nameserver	135
Modify a nameserver	138
Other	140
Support	140
Tools	142
CheckD	142
Examples	143
Complete set of examples for download	143

2.3 Email Gateway

How does the PGP/GPG-Mailinterface work?

Using the Joker.com email interface, you may send 'commands' to a special address at Joker.com by email. Those commands may consist of registration orders, domain renewals or modifications.

The Joker.com mail interface address is disclosed once you signed up as a reseller.

The emails making up the commands follow a simple format, which is described here in section 'Requests'.

For security reasons, each request which is sent to the mail gateway has to be signed using PGP or GPG. This means, you need to have a pgp/gpg-installation on your machine. Some tools which can be used for this:

- [Gnu GPG](#)
- [Enigmail for Thunderbird](#)

Emails which are not signed correctly will not be processed. All requests to the gateway have to be sent as PGP/GPG signed mails to the Joker mail-robot (you will receive the exact address if you have registered yourself as a reseller).

Mails are expected to be sent in the "**traditional**" format (signature is part of the message body), **not** (for example) in MIME encapsulated format!

The actual request (the command to be performed) has to be put into the subject of the email. Further details (for example the full qualified domain name) have to be put in the message body.

Example:

Subject: modify domain

-----BEGIN PGP SIGNED MESSAGE-----

Hash: SHA1

tld:org

Basics

sld:dummy

ns1-handle:ns1.dummy.org

ns2-handle:ns2.dummy.org

-----BEGIN PGP SIGNATURE-----

Version: GnuPG v1.0.2 (GNU/Linux)

Comment: For info see <http://www.gnupg.org>

iD7DBQE6ZtMfzWqd+drNYRURAUW4AJ4nRewOrNc+yLMmmCouVcMP3v5nWQCdHUIf

tJk/gOuFmDnls3JS+7eRjnA=

=Fwmc

-----END PGP SIGNATURE-----

Keywords: PGP GPG PGP/GPG mail-interface

Last update: 2012-10-11 10:19

Basics

Where are the replies of the mail-gateway sent?

The replies of the gateway are generally sent to the "reply-to"-address. In order to specify that address, you will have to fill in the reply-to-field within the e-mails you send to the mail-gateway.

Keywords: replies mail-gateway reply-to

Last update: 2007-03-27 15:15

Basics

How do I change my robot-email-address?

The Joker.com system identifies you using your pgp-signature and your email-address, so you have to provide a new pgp-key, if you want to change your robot-email-address. Without changing the pgp-key, our system cannot grant you access to the domains, you have registered at joker.com.

Please, follow the 3 steps below to **change your robot-email-address**.

1. Create a new contact with your new email-address using the mail-gateway.
2. Change the billing-c of **all** your domains using this new contact, which contains the new robot-email-address. Use the ["list domains"-request](#) for a listing of your domains.
3. Go to <https://joker.com/index.joker?mode=resellerpages&stage=step13b> and provide your new email-address and your new pgp-key and wait for our response mail.

Keywords: change robot-email-address robot e-mail address

Last update: 2007-03-27 15:23

Basics

What is the Joker.com public key?

Please verify a mail from joker.com using the following public key:

```
-----BEGIN PGP PUBLIC KEY BLOCK-----  
Version: GnuPG v1.0.7 (GNU/Linux)  
mIsePOorJQEAAJauWOOvusxn9GFEPjZnQ3x/480faPwSN4cIF5ezpUT6FycZQa+q  
eUnNlS+bj80ULXnyyigmkUGwEtW/Qoyd55RM983pr4KtuHSMSU9gCNlsyuHlDOAm  
71u6irfv5RaHbJXauMCAgUKn+dBNZVZyUTm9aW2pudcwY45apF2tieTZAAYptClq  
b2tlci5jb20gc2lnbmVyIHNLcnZpY2UgPGluZm9Aam9rZXIuY29tPoiyBBMBAgAc  
BQI8/NifAhsDBAsHAWIDFQIDAxYCAQIeAQIXgAAKCRAm3eE0EUTiIx9RA/9HGDrD  
cVM6PjZHR5jpt4svpv7xrjVRn2OIR+s80RuBAnLyAWOf1qJ9342SYD8C7BMAqYm4  
wXvC3/yvbQEAqsmJ5Bbq2NV+KDepahTtL8SUQ6TkOSUd9ND0vLoQWVI6o1Dz/3MG  
HLJfNtx6067Sq8pP8PuYyscPyZ7/uiUilyOrqg==  
=O/7Q  
-----END PGP PUBLIC KEY BLOCK-----
```

Keywords: public pgp/gpg-key key

Last update: 2007-03-30 15:48

Basics

Should I use PGP or GPG?

It does not matter if you use PGP or GPG, the version is not important as well. Just make sure that your program is able to put PGP signatures into your mail in the format described above.

Please have a look at the following web sites to get the newest versions and lots of explanation on the programs.

<http://www.pgpi.org/>

<http://www.gnupg.org/>

ATTENTION:

Users of GPG have to use the following flag:

```
gpg --clearsign --force-v3-sigs ....
```

Otherwise our system will reject your signed mails.

Keywords: PGP GPG signature

Last update: 2007-03-30 15:53

Basics

General Instructions

All requests do follow the same scheme:

- each key:value pair is unique in application.
- each key:value pair is one line finished with carriage return
- each key is delimited by a colon ":" from the value

You have to send the request as [signed email](#) to the Joker.com mail gateway address. This address is disclosed once you signed up as a reseller of Joker.com.

Each email uses a simple, special format, which is described under the different request-types.

For security reasons you have to pgp-sign each mail you send to the mail-gateway, so you need a pgp-installation on your machine. Unsigned or invalid mails will be ignored.

Emails without a valid subject (request-type) will produce an error. In this case you will receive an error message as response.

Valid requests are normally processed in realtime. Under certain circumstances (Registry-Downtimes, System maintenance, etc.) it is possible, that requests have to wait for processing. It is highly recommended to ask our support before you repeat such requests.

The descriptions for the requests do all follow the same scheme:

Topic 'introduction' - a short introduction of the request, what is the request for.

Topic 'request fields'

- which fields are required or allowed for a request
- which character are allowed for a request field (the valid character sets are described with PERL-REGULAR-EXPRESSIONS)
- one or more examples for a valid request

Requests

Keywords: instructions introduction requests

Last update: 2012-10-11 10:29

Requests

List of currently working requests

Here you will find the list of the currently working requests. There are 2 types of status for each request.

- available
- not yet implemented

All requests marked with "not yet implemented" will be available during the next weeks.

target	request type	status
com/nl	support	available
	create order	available
	change server	available
	change address	available
	transfer domain	available
	renew domain	available
	delete domain	available
	modify domain	available
	create contact	available
	modify contact	available
	create nameserver	available
	modify nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	org	support
create org order		available

Requests

	change org owner	enable
	change org address	enable
	transfer org domain	enable
	renew org domain	enable
	delete org domain	enable
	modify org domain	enable
	create org contact	enable
	modify org contact	enable
	create org nameserver	enable
	modify org nameserver	enable
	list domains	enable
	lock domain	enable
	unlock domain	enable
	get sub-id	enable
info	support	enable
	create info order	enable
	change info owner	enable
	change info address	enable
	transfer info domain	enable
	renew info domain	enable
	delete info domain	enable
	modify info domain	enable
	create info contact	enable
	modify info contact	enable
	create info nameserver	enable

Requests

	modify dns nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get sub-id	available
de	support	available
	create dns order	available
	change dns course	available
	change dns address	available
	transfer dns domain	available
	renew dns domain	available
	delete dns domain	available
	modify dns domain	available
	create dns contract	available
	modify dns contract	available
	create dns nameserver	available
	modify dns nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get sub-id	available
de	support	available
	create dns order	available
	change dns course	available
	change dns address	available

Requests

transfer de-domain	available
renew de-domain	available
delete de-domain	available
modify de-domain	available
create de-contact	available
modify de-contact	available
create de-namserver	available
modify de-namserver	available
list domains	available
lock domain	available
unlock domain	available
support	available
create eu-order	available
change eu-contact	available
change eu-nsd-ips	available
transfer eu-domain	available
renew eu-domain	available
delete eu-domain	available
modify eu-domain	available
create eu-contact	available
modify eu-contact	available
create eu-namserver	available
modify eu-namserver	available
list domains	available
lock domain	available

Requests

.cn	unlock domain	enable
	get sub-id	enable
	support	enable
	create cn-order	enable
	change cn-owner	enable
	change cn-address	enable
	transfer cn-domain	enable
	renew cn-domain	enable
	delete cn-domain	enable
	modify cn-domain	enable
	create cn-contact	enable
	modify cn-contact	enable
	create cn-namserver	enable
	modify cn-namserver	enable
	list domains	enable
	lock domain	enable
	unlock domain	enable
get sub-id	enable	
.us	support	enable
	create us-order	enable
	change us-owner	enable
	change us-address	enable
	transfer us-domain	enable
	renew us-domain	enable
	delete us-domain	enable

Requests

	modify via domain	available
	create via contact	available
	modify via contact	available
	create via nameserver	available
	modify via nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get sub-id	available
me	support	available
	create via order	available
	change via name	available
	change via address	available
	transfer via domain	available
	renew via domain	available
	delete via domain	available
	modify via domain	available
	create via contact	available
	modify via contact	available
	create via nameserver	available
	modify via nameserver	available
	list domains	available
	lock domain	available
	unlock domain	available
	get sub-id	available

Requests

.asa	support	enable	
	create asa-order	enable	
	change asa-order	enable	
	change asa-address	enable	
	transfer asa-domain	enable	
	renew asa-domain	enable	
	delete asa-domain	enable	
	modify asa-domain	enable	
	create asa-contact	enable	
	modify asa-contact	enable	
	create asa-nameserver	enable	
	modify asa-nameserver	enable	
	list domains	enable	
	lock domain	enable	
	unlock domain	enable	
	get sub-id	enable	
	.mbi	support	enable
create mbi-order		enable	
change mbi-order		enable	
change mbi-address		enable	
transfer mbi-domain		enable	
renew mbi-domain		enable	
delete mbi-domain		enable	
modify mbi-domain		enable	
create mbi-contact		enable	

Requests

	modify nslc-contact	enable
	create nslc-connection	enable
	modify nslc-connection	enable
	list domains	enable
	lock domain	enable
	unlock domain	enable
	get sub-id	enable
name	support	enable
	create name-order	enable
	change name-contact	enable
	change name-address	enable
	transfer name-domain	enable
	renew name-domain	enable
	delete name-domain	enable
	modify name-domain	enable
	create name-contact	enable
	modify name-contact	enable
	create name-connection	enable
	modify name-connection	enable
	list domains	enable
	lock domain	enable
	unlock domain	enable
	get sub-id	enable
	nameservice/forwarding	create dns-config
delete dns-config		enable

Requests

	test-config	enable
--	-------------	--------

Keywords: request requests, summary, email-gw, email-gateway

Last update: 2008-08-14 11:31

Requests

What is a macro?

A macro is used within the definition of a request.

A macro starts with an @.

Example: @count or @total or @sum

Every time you find a macro, please check the definition of this macro for further information.

Keywords: macro definition

Last update: 2007-04-02 15:20

Macros

E-mail Address

@mail
This means an email address in the following format:
Valid values (containing only):
foo@bar.com
foo@bar.com!1
foo@bar.com@15

mailto:username
Here: username@foo.com
username@foo.com (Here: username)

Valid values (containing only):
foo@bar.com

mailto:username
Here: username@foo.com
username@foo.com (Here: username)

foo@bar.com@15

Keywords: email address

Last update: 2011-08-11 15:34

Macros .com/.net Contacts

new-handle (explicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created and we will add a numerical suffix to the email address that starts with "0" and increases by "1" for every existing contact with such a emailaddress in the JOKER-DATABASE.

ATTENTION

The name of the request field depends on the contact. If you want to create a contact for the owner-contact, you have to replace the "-" at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "-" at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "-" at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "-" at the beginning of the fieldname with "billing-contact".

request field	used values	required
*idnumber	1-74	yes
*name	{JOKER-NAME}.000	yes if idnumber > 1
*lastname	{JOKER-NAME}.000	yes if idnumber > 1
*sex	{JOKER-NAME}.000	no
*organization	{JOKER-NAME}.000	yes if idnumber > 0
*address 1	{JOKER-NAME}.000	yes
*address 2	{JOKER-NAME}.000	no
*postalcode	{JOKER-NAME}.000	yes
*city	{JOKER-NAME}.000	yes
*state	{JOKER-NAME}.000	no
*country		yes
*email	@joker.com	yes
*phone	{JOKER-NAME}.000	yes
*fax	{JOKER-NAME}.000	no

An existing contact (@cont or @same-as (.com/net only))

This means an existing contact-handle in the JOKER-DATABASE.

Examples

owner-contact-handle.000@our.com@0
 admin-contact-handle.000@our.com
 tech-contact-handle.000@our.com@10
 billing-contact-handle.000@our.com@15

In case you have entered a non-existing contact-handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle.000@same-as-existence-contact
 tech-contact-handle.000@same-as-admin-contact
 billing-contact-handle.000@same-as-tech-contact

The @same-as macro always replaces the value for the specified contact-handle with the email address of the macroarg. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for (.com/net)-requests, contact handles for (jmk)-contacts are not allowed. If you are referencing to a shortcut like CO0703-LRMS, you will get an error.

Keywords: new-handle @cont @same-as admin tech billing

Macros

Last update: 2007-04-17 22:05

Macros

.com Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CCOM-<number>.

e.g. CCOM-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no

Macros

".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact ([@comcont](#) or [@same-as](#)) (.com only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:CCOM-176269
admin-contact-handle:CCOM-176229
tech-contact-handle:CCOM-176269
billing-contact-handle:CCOM-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .com-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle [@comcont](#) [@same-as](#) admin tech billing

Last update: 2015-11-09 17:47

Macros

.net Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CNET-<number>, e.g. CNET-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes

Macros

".."-city	[[\x20-\x7e]{1,80}	yes
".."-state	[[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact ([@netcont](#) or [@same-as](#)) (.net only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:CNET-176269
admin-contact-handle:CNET-176229
tech-contact-handle:CNET-176269
billing-contact-handle:CNET-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .net-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @netcont @same-as admin tech billing

Last update: 2015-11-09 17:48

Macros

.org Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CORG-<number>, e.g. CORG-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes

Macros

".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (**@orgcont** or **@same-as**) (.org only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:CORG-176269
admin-contact-handle:CORG-176229
tech-contact-handle:CORG-176269
billing-contact-handle:CORG-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .org-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @orgcont @same-as admin tech billing

Last update: 2015-11-09 17:49

Macros

.info Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format C<number>-LRMS, e.g. C176269-LRMS.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no

Macros

".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@infocont or @same-as) (.info only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:C176269-LRMS
admin-contact-handle:CAFI-007
tech-contact-handle:C176269-LRMS
billing-contact-handle:CAFI-008
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .info-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @infocont @same-as admin tech billing

Last update: 2015-11-09 17:49

Macros

.biz Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created.

ATTENTION

According to the rules of NEULEVEL, the fieldlength for most of the requestfields are limited to 30 characters. Please check very carefully the definitions of the request fields.

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

Please, keep in mind, that if you are using the concatenation of **fname** and **lname**, you have to care that the sum of both fields should not be longer than 30 characters.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
---------------	--------------	----------

Macros

".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,30}	no, if name is given
".."-fname	[\x20-\x7e]{0,30}	no, if name is given
".."-name	[\x20-\x7e]{0,30}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,30}	no
".."-organization	[\x20-\x7e]{0,30}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,30}	yes
".."-address-2	[\x20-\x7e]{0,30}	no
".."-address-3	[\x20-\x7e]{0,30}	no
".."-postal-code	[\x20-\x7e]{1,10}	yes
".."-city	[\x20-\x7e]{1,30}	yes
".."-state	[\x20-\x7e]{0,30}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,17}	yes
".."-fax	[[\x20-\x7e]{0,17}	no

An existing contact (@bizcont or @same-as) (.biz only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle: CNEU-12345
admin-contact-handle: CNEU-12345
tech-contact-handle: CNEU-12345
billing-contact-handle: CNEU-12345

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

Macros

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .biz-requests the contact handles for (.com/.net/.org/.info)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Note that for .biz-requests the contacthandles for (.info)-contacts are not allowed. If you referencing to a shortcut like C176269-LRMS, you will get an error.

Keywords: new-handle @bizcont @same-as admin tech billing

Last update: 2015-11-09 17:51

Macros

.mobi Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COMO-<number>, e.g. COMO-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

Macros

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@mobicont or @same-as) (.mobi only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:COMO-176269
admin-contact-handle:COMO-176229
tech-contact-handle:COMO-176269
billing-contact-handle:COMO-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

Macros

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .mobi-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @mobicont @same-as admin tech billing owner

Last update: 2015-11-09 17:50

Macros

Country	Handle	Owner
USA	USA	USA
USA	USA	USA
USA	USA	USA

An existing contact (@namecont or @same-as) (name only)

This means an existing contact handle in the JOKER DATABASE.

Examples:

```
owner-contact-handle:CNAM:112233
admin-contact-handle:CNAM:112233
tech-contact-handle:CNAM:112233
billing-contact-handle:CNAM:112233
```

In case you have entered a non-existing contact handle, the system will send you an error.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The @same-as macro always replaces the value for the specified contact handle with the email address of the macroarg. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for @same-as the contact handles for (com/net)contacts are not allowed. If you are referencing to a shortcut like handle@joker.net, you will get an error.

Keywords: new-handle @namecont @same-as admin tech billing owner

Last update: 2007-06-21 11:11

Macros

.us Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COUS-<number>, e.g. COUS-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes

Macros

".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@uscont or @same-as) (.us only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:COUS-176269
admin-contact-handle:COUS-176229
tech-contact-handle:COUS-176269
billing-contact-handle:COUS-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

Macros

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .us-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @uscont @same-as admin tech billing owner

Last update: 2015-11-09 17:51

Macros

.de Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CODE-<number>, e.g. CODE-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given

Macros

".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	yes, but for admin-c and tech-c only

An existing contact (@decont or @same-as) (.de only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:CODE-176269
admin-contact-handle:CODE-176229
tech-contact-handle:CODE-176269
billing-contact-handle:CODE-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

Macros

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .de-requests the contact handles for (.com/.net/.org/.info/.biz/.cn)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @decont @same-as admin tech billing owner

Last update: 2015-11-09 17:50

Macros

.cn Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COCN-<number>, e.g. COCN-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes

Macros

".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@cncont or @same-as) (.cn only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:COCN-176269
admin-contact-handle:COCN-176229
tech-contact-handle:COCN-176269
billing-contact-handle:COCN-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

Macros

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .cn-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @cncont @same-as admin tech billing owner

Last update: 2015-11-09 17:51

Macros

.eu Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format C<number>, e.g. C176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
---------------	--------------	----------

Macros

".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact ([@uscont](#) or [@same-as](#)) (.us only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:C176269
admin-contact-handle:C176229
tech-contact-handle:C176269
billing-contact-handle:C176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

Macros

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .eu-requests the contact handles for (.com/.net/.org/.info/.biz/.de/.us)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @eucont @same-as admin tech billing owner

Last update: 2015-11-09 17:52

Macros

Valid domain names

@dom - a valid domain name under .com/.net

@orgdom - a valid domain name under .org

@infodom - a valid domain name under .info

@dedom - a valid domain name under .de

@cndom - a valid domain name under .cn

@eudom - a valid domain name under .eu

@usdom - a valid domain name under .us

@fqdn - a valid domain name under .com/.net/.org/.info/.mobi/.name/.biz/.de/.cn/.eu/.us

Keywords: @dom @orgdom @infodom @dedom @cndom @eudom @usdom @fqdn

Last update: 2007-03-28 15:45

Macros

Nameserver

@ns - the definition of an existing nameserver

You have to provide a valid nameserver handle. Implicit nameserver creation is not allowed.

Examples:

ns1.foo.bar.net
ns2.foo.bar.net

ns3.foo.bar.net

Keywords: @ns nameserver

Last update: 2015-11-09 17:53

Macros

Zonefile entries

@a_record

[a hostprefix without the domainname]:[IP-Address]

- trailing dots at the hostprefix are deleted
- an "@" will be expanded to the domainname

Example1:

a:www:194.233.101.99

Example2:

a:@:194.233.101.99

@mx_record

[a hostprefix without the domainname]:[priority]:[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" as the value of the hostprefix will be expanded to the domain name

Example 1:

mx:www:50:mail.hansnose.net

Example 2:

mx:www:90:mail.hansnose.net

Example 3:

mx:@:50:mail.hansnose.net

Example 4:

mx:@:90:mail.hansnose.net

@cname_record

[a hostprefix without the domainname]:[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" for the hostprefix is not supported within a CNAME-Record

Macros

Example 1:

cname:www:mail.hansnose.net

Example 2:

cname:www2:mail.hansnose.net

@url_record

[a hostprefix without the domainname]::[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" as the value of the hostprefix will be expanded to the domain name

Example 1:

url:www:http://some.redirector.com

Example 2:

url:www2:http://some.redirector.com:9002

Example 3:

url:www3:https://some.redirector.com

Example 4:

url:www4:https://some.redirector.com:9002

Keywords: @a_record @mx_record @cname_record @url_record

Last update: 2007-04-20 14:49

Macros IP

@ip - a valid IP address

IP addresses within the following range are NOT valid:

Ä,

Keywords: @ip

Last update: 2007-04-02 16:24

Macros

Domain renewal

@renew

Here you have to provide the domain name and the renewal period or the desired expiration year on one line. You have to separate the domain name and renewal period/expire year with an ":" (ASCII 058). The maximum for the renewal period is 9 years.

Examples:

```
domain1:blafasel.com:2  
domain2:hansnose.net:3  
domain2:hansnose.info:2005  
domain2:hansnose.biz:2
```

Attention:

If you are using the expire year and the current expire year of the domain is equal or greater than the provided value for that field, the request will not be processed.

Keywords: @renew

Last update: 2007-03-28 16:12

Macros

	ALABAMA
	ALASKA
	ARIZONA
	ARKANSAS
	CALIFORNIA
	CONNECTICUT
	DELAWARE
	FLORIDA
	GEORGIA
	HAWAII
	ILLINOIS
	INDIANA
	IOWA
	KANSAS
	KENTUCKY
	LOUISIANA
	MAINE
	MARYLAND
	MASSACHUSETTS
	MICHIGAN
	MINNESOTA
	MISSISSIPPI
	MISSOURI
	MONTANA
	NEBRASKA
	NEVADA
	NEW HAMPSHIRE
	NEW JERSEY
	NEW MEXICO
	NEW YORK
	NORTH CAROLINA
	NORTH DAKOTA
	OHIO
	OKLAHOMA
	OREGON
	PENNSYLVANIA
	RHODE ISLAND
	SOUTH CAROLINA
	SOUTH DAKOTA
	TENNESSEE
	TEXAS
	UTAH
	VIRGINIA
	WASHINGTON
	WEST VIRGINIA
	WISCONSIN
	WYOMING

Macros

	AD
	ADORN ISLANDS AND THE SOLOMON ISLANDS
	AE
	AF
	AG
	AI
	AK
	AL
	AM
	AN
	AO
	AR
	AS
	AT
	AU
	AW
	AX
	AY
	AZ
	BA
	BB
	BC
	BD
	BE
	BF
	BG
	BH
	BI
	BJ
	BK
	BL
	BM
	BN
	BO
	BQ
	BR
	BS
	BT
	BV
	BW
	BX
	BY
	BZ
	CA
	CC
	CD
	CE
	CF
	CG
	CH
	CI
	CK
	CL
	CM
	CN
	CO
	CR
	CU
	CV
	CW
	CX
	CY
	CZ
	DA
	DB
	DC
	DD
	DE
	DF
	DG
	DH
	DI
	DJ
	DK
	DL
	DM
	DN
	DO
	DP
	DQ
	DR
	DS
	DT
	DU
	DV
	DW
	DX
	DY
	DZ
	EA
	EB
	EC
	ED
	EE
	EG
	EH
	EI
	EJ
	EK
	EL
	EM
	EN
	EO
	EP
	EQ
	ER
	ES
	ET
	EU
	EV
	EW
	EX
	EY
	EZ
	FA
	FB
	FC
	FD
	FE
	FF
	FG
	FH
	FI
	FJ
	FK
	FL
	FM
	FN
	FO
	FP
	FQ
	FR
	FS
	FT
	FU
	FV
	FW
	FX
	FY
	FZ
	GA
	GB
	GC
	GD
	GE
	GF
	GG
	GH
	GI
	GJ
	GK
	GL
	GM
	GN
	GO
	GP
	GQ
	GR
	GS
	GT
	GU
	GV
	GW
	GX
	GY
	HA
	HB
	HC
	HD
	HE
	HF
	HG
	HH
	HI
	HJ
	HK
	HL
	HM
	HN
	HO
	HP
	HQ
	HR
	HS
	HT
	HU
	HV
	HW
	HX
	HY
	HZ
	IA
	IB
	IC
	ID
	IE
	IF
	IG
	IH
	II
	IJ
	IK
	IL
	IM
	IN
	IO
	IP
	IQ
	IR
	IS
	IT
	IU
	IV
	IW
	IX
	IY
	IZ
	JA
	JB
	JC
	JD
	JE
	JF
	JG
	JH
	JI
	JJ
	JK
	JL
	JM
	JN
	JO
	JP
	JK
	JQ
	JR
	JS
	JT
	JU
	JV
	JW
	JX
	JY
	JZ
	KA
	KB
	KC
	KD
	KE
	KF
	KG
	KH
	KI
	KJ
	KK
	KL
	KM
	KN
	KO
	KP
	KQ
	KR
	KS
	KT
	KU
	KV
	KW
	KX
	KY
	KZ
	LA
	LB
	LC
	LD
	LE
	LF
	LG
	LH
	LI
	LJ
	LK
	LL
	LM
	LN
	LO
	LP
	LQ
	LR
	LS
	LT
	LU
	LV
	LW
	LX
	LY
	LZ
	MA
	MB
	MC
	MD
	ME
	MF
	MG
	MH
	MI
	MJ
	MK
	ML
	MM
	MN
	MO
	MP
	MQ
	MR
	MS
	MT
	MU
	MV
	MW
	MX
	MY
	MZ
	NA
	NB
	NC
	ND
	NE
	NF
	NG
	NH
	NI
	NJ
	NK
	NL
	NM
	NO
	NP
	NQ
	NR
	NS
	NT
	NU
	NV
	NW
	NX
	NY
	NZ
	OA
	OB
	OC
	OD
	OE
	OF
	OG
	OH
	OI
	OJ
	OK
	OL
	OM
	ON
	OO
	OP
	OQ
	OR
	OS
	OT
	OU
	OV
	OW
	OX
	OY
	OZ
	PA
	PB
	PC
	PD
	PE
	PF
	PG
	PH
	PI
	PJ
	PK
	PL
	PM
	PN
	PO
	PP
	PQ
	PR
	PS
	PT
	PU
	PV
	PW
	PX
	PY
	PZ
	QA
	QB
	QC
	QD
	QE
	QF
	QG
	QH
	QI
	QJ
	QK
	QL
	QM
	QN
	QO
	QP
	QQ
	QR
	QS
	QT
	QU
	QV
	QW
	QX
	QY
	QZ
	RA
	RB
	RC
	RD
	RE
	RF
	RG
	RH
	RI
	RJ
	RK
	RL
	RM
	RN
	RO
	RP
	RQ
	RR
	RS
	RT
	RU
	RV
	RW
	RX
	RY
	RZ
	SA
	SB
	SC
	SD
	SE
	SF
	SG
	SH
	SI
	SJ
	SK
	SL
	SM
	SN
	SO
	SP
	SQ
	SR
	SS
	ST
	SU
	SV
	SW
	SX
	SY
	SZ
	TA
	TB
	TC
	TD
	TE
	TF
	TG
	TH
	TI
	TJ
	TK
	TL
	TM
	TN
	TO
	TP
	TQ
	TR
	TS
	TT
	TU
	TV
	TW
	TX
	TY
	TZ
	UA
	UB
	UC
	UD
	UE
	UF
	UG
	UH
	UI
	UJ
	UK
	UL
	UM
	UN
	UO
	UP
	UQ
	UR
	US
	UT
	UU
	UV
	UW
	UX
	UY
	UZ
	VA
	VB
	VC
	VD
	VE
	VF
	VG
	VH
	VI
	VJ
	VK
	VL
	VM
	VN
	VO
	VP
	VQ
	VR
	VS
	VT
	VU
	VV
	VW
	VX
	VY
	VZ
	WA
	WB
	WC
	WD
	WE
	WF
	WG
	WH
	WI
	WJ
	WK
	WL
	WM
	WN
	WO
	WP
	WQ
	WR
	WS
	WT
	WU
	WV
	WW
	WX
	WY
	WZ
	XA
	XB
	XC
	XD
	XE
	XF
	XG
	XH
	XI
	XJ
	XK
	XL
	XM
	XN
	XO
	XP
	XQ
	XR
	XS
	XT
	XU
	XV
	XW
	XX
	XY
	XZ
	YA
	YB
	YC
	YD
	YE
	YF
	YG
	YH
	YI
	YJ
	YK
	YL
	YM
	YN
	YO
	YP
	YQ
	YR
	YS
	YT
	YU
	YV
	YW
	YX
	YY
	YZ
	ZA
	ZB
	ZC
	ZD
	ZE
	ZF
	ZG
	ZH
	ZI
	ZJ
	ZK
	ZL
	ZM
	ZN
	ZO
	ZP
	ZQ
	ZR
	ZS
	ZT
	ZU
	ZV
	ZW
	ZX
	ZY
	ZZ

Keywords: country code @country

Macros

Last update: 2007-04-17 22:12

Macros

Language code

@language - one of the following language codes

Languagecode	Language
AFR	Afrikaans
ALB	Albanian
ARA	Arabic
ARM	Armenian
AZE	Azerbaijani
BAQ	Basque
BUL	Bulgarian
BUR	Burmese
CAT	Catalan
CHI	Chinese
CZE	Czech
DAN	Danish
DUT	Dutch
ENG	English
EST	Estonian
FAO	Faroese
FIN	Finnish
FRE	French
GEO	Georgian
GER	German
HEB	Hebrew
HIN	Hindi
HUN	Hungarian
ICE	Icelandic
ITA	Italian
JPN	Japanese
KOR	Korean
KUR	Kurdish
LAO	Lao
LAV	Latvian
LIT	Lithuanian
MAC	Macedonian
MAL	Malayalm
NEP	Nepali
NOR	Norwegian
PER	Persian
POL	Polish
POR	Portuguese
RUM	Romanian
RUS	Russian
SAN	Sanskirt
SCC	Serbian
SCR	Croatian

Macros

SLO	Slovak
SLV	Slovenian
SPA	Spanish
SWA	Swahili
SWE	Swedish
SYR	Syriac
TAM	Tamil
THA	Thai
TIB	Tibetan
TUR	Turkish
UKR	Ukrainian
URD	Urdu
UZB	Uzbek
VIE	Vietnamese
ZHO	Chinese

Keywords: @language language code

Last update: 2015-11-09 17:46

Macros .me Contacts

new-handle (explicit creation of a new contact)

This means the definition of a new contact: if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COME-**number**, e.g. COME-17638.

ATTENTION

The name of the request field depends on the contact. If you want to create a contact for the owner contact, you have to replace the "-" at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "-" at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "-" at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "-" at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **firstname**. You have to provide the request field **name**, if **fname** and **sname** are not found. This is very important for the whole output. Everywhere a field **person** is shown. If you are using the request field **name**, the whole is showing the value for **name**, regardless the content of the request fields **fname** and **sname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **sname**, the whole is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request field	request value	response
new-handle	17638	OK
name	COME-17638	OK, if name is given
fname	COME-17638	OK, if fname is given
sname	COME-17638	OK, if sname is given
name	COME-17638	OK, if fname and/or sname are not given
address-1	COME-17638	OK
address-2	COME-17638	OK
address-3	COME-17638	OK
address-4	COME-17638	OK
address-5	COME-17638	OK
city	COME-17638	OK
state	COME-17638	OK
country	COME-17638	OK
zipcode	COME-17638	OK

Macros

OWNER	CONTACTNAME	EMAIL
ADMIN	CONTACTNAME	EMAIL

An existing contact (@mecont@ @same-as) (me-216)

This means an existing contact handle in the JOKER DATABASE.

Example:

```
owner-contact-handle:COMB-173289
admin-contact-handle:COMB-173229
tech-contact-handle:COMB-173289
billing-contact-handle:COMB-173289
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

The @same-as makes always replace the value for the specified contact handle with the email address of the macrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for me-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like home@joker.net, you will get an error.

Keywords: new-handle @mecont @same-as admin tech billing owner

Last update: 2008-08-14 11:46

Macros

Create a dns-configuration

Introduction

With this request you can create or modify a record in the joker-namenserver.
 You can add A-Records, CNAME-Records, MX-Records, a nameserver-based URI-forwarding and a frame-based URI-forwarding. Modifying the TTL is not possible.
 The format of this request is a little bit different from the other requests. Please check the given examples for how to specify the different consoile-records.

ATTENTION:

You have to change the nameservers for a domain to the nameservers of joker.com first!

[A-Record](#)
[CNAME-Record](#)
[MX-Record](#)
[URI-Record](#)
[URI-Record](#)
[URI-Record](#)
 If you would like to use the joker-namenserver, you will have to use all joker-namenserver.
 It is not possible to use the joker-namenserver.

- for primary nameserver only

- for secondary nameserver only

All joker-namenserver

- we configured to deny all zone-fetching request!

- do not query foreign nameserver!

Request Fields

Definition of the request

Record-Name	Record-Value	Priority
A	192.168.1.1	100
A	192.168.1.2	100
A	192.168.1.3	100
A	192.168.1.4	100
A	192.168.1.5	100
A	192.168.1.6	100
A	192.168.1.7	100
A	192.168.1.8	100
A	192.168.1.9	100
A	192.168.1.10	100

Example 1: create dns-config (without uri-forwarding and without address-matching)

subject: create dns-config [your reference id]

domain: joker.com

Awww: 192.168.1.10

DNS/URL-Forwarding

Amail 194.23.110.19

Amail2 194.23.110.20

A@ 194.23.110.10

MX www.hanroosa.net 70 mail.hroa.net

MX www.hanroosa.net 80 mail2.hroa.net

MX @ 70 mail.hanroosa.net

MX @ 80 mail2.hanroosa.net

CNAME www2.some.other.domain.com

Example 2: create dns-confiq (with wildcard-matching)

subject: create dns-confiq [your reference id]

domain@hanroosa.net

Awww 194.23.110.19

A@ 194.23.110.10

A* 194.23.110.20

Example 3: create dns-confiq (with dns-based url-forwarding)

subject: create dns-confiq [your reference id]

domain@hanroosa.net

Awww 194.23.110.19

A@ 194.23.110.10

URL www2 http://www.some.other.domain.com/index.html

[Other records, the url within the bracket is changing to the target address]

DNS/URL-Forwarding

Example 4 create dns.conf with frame-based url-forwarding

```
subject create dns.conf [your reference id]
```

```
domain2 forwarder.net
```

```
A www 194.23.110.10
```

```
A @ 194.23.110.10
```

```
FRAMES www2 http://www.some.other.domain.com/index.html
```

(that means, the url within the browser is not changing to the target address)

Keywords: nameserver, records, zone, forwarding

Last update: 2011-08-11 15:37

DNS/URL-Forwarding

Delete a dns-configuration

Introduction

With this request you can delete a zonefile at the joker nameserver.

Request fields

mailto:subject: delete dns-config [your reference id]

Definition of the request

parameter	url format	example
subject	mailto:subject: delete dns-config [your reference id]	

Example 1: delete dns-config

subject: delete dns-config [your reference id]

domain@nameserver.net

Keywords: nameserver,dns-config,records, forwarding

Last update: 2011-08-11 15:37

DNS/URL-Forwarding

List a dns-configuration

Introduction

With this request you can get a listing of a current records.

Request fields

request: subject: list dns-config [your reference id] definition of this request

request	subject	request

Example 1: list dns-config

subject: list dns-config [your reference id]

domain: joker.com

Keywords: nameserver,dns-config,records, forwarding

Last update: 2011-08-11 15:38

DNS/URL-Forwarding

Create an order

Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

- xxx

- asia

- me

With this request you can register one or more domains.

You have to provide the following information within the request:

- domain name(s),
- owner-contact-handle,
- admin-contact-handle,
- tech-contact-handle,
- billing-contact-handle,
- nameserver information,
- additional services, if required.

You can register up to 501 domains with one request.

If you register more than one domain with a request, all domains registered with this request will have the same contact and nameserver structure.

There are two new requestfields within this request:

- name

Domains

- address-3

ATTENTION

Please, refer to the table for the corresponding contact handles.

TLD	Contact handle
com	CCOM-<number>
net	CNET-<number>
org	CORG-<number>
info	C<number>-LRMS
biz	CNEU-<number>
mobi	COMO-<number>
name	CNAM-<number>
us	COUS-<number>
de	CODE-<number>
cn	COCN-<number>
eu	C<number>
me	COME-<number>
asia	COAS-<number>
xxx	CONX-<number>

Request fields

mailsubject: create <tld>-order [your reference id]

Definition of this request

tld	request field		
	domains[0..500]	period	language[0..500]
com	[a-z0-9]{1,63}\.com	^([1..9]{1})\$	@language
net	[a-z0-9]{1,63}\.net	^([1..9]{1})\$	
org	[a-z0-9]{1,63}\.org	^([1..9]{1})\$	
info	[a-z0-9]{1,63}\.info	^([1..9]{1})\$	
biz		^([1..9]{1})\$	

Domains

mobi	[a-z0-9-]{1,63}\.mobi	^([1..9]{1})\$	
name		^[2..9]{1}\$	
us	[a-z0-9-]{1,63}\.us	^[2..9]{1}\$	
de	[a-z0-9-]{1,63}\.de	^[1..9]{1}\$	
cn		^[1..9]{1}\$	
eu		^[1..9]{1}\$	
me		^[1..9]{1}\$	
asia		^[1..9]{1}\$	
xxx		^[1..9]{1}\$	
required	yes	yes	no (IDN domains only)

tld				
com				@comcont
net				@netcont
org				@orgcont
info				@infocont
biz				@decont
mobi				@mobicont
name				@namecont
us				@uscont
de				@bizcont
cn				@cncont
eu				@eucont
me				@mecont

Domains

asia	@asiacon
required	yes

tld	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle
<tld>	@ns					
required	yes	yes	no			

.COM order

Example 1: create com-order with implicit contact-handle-creation of the owner-contact

subject: create com-order [your reference id]

```
domains0:xn--hans-mller-feb.com
language0:AFR
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

Example 2: create com-order with implicit nameserver-creation

subject: create com-order [your reference id]

```
domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
```

Domains

period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create com-order with implicit contact-handle-creation of all contacts

subject: create com-order [your reference id]

domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net

Domains

ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.NET order

Example 1: create net-order with implicit contact-handle-creation of the owner-contact

subject: create net-order [your reference id]

domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create net-order with implicit nameserver-creation

subject: create net-order [your reference id]

domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1

Domains

ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create net-order with implicit contact-handle-creation of all contacts

subject: create net-order [your reference id]

domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Domains

.ORG order

Example 1: create org-order with implicit contact-handle-creation of the owner-contact

subject: create org-order [your reference id]

```
domains0:xn--hans-mller-feb.org
language0:AFR
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

Example 2: create org-order with implicit nameserver-creation

subject: create org-order [your reference id]

```
domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-handle:CORG-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

Example 3: create org-order with implicit contact-handle-creation of all contacts

subject: create org-order [your reference id]

Domains

domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.INFO order

Example 1: create info-order with implicit contact-handle-creation of the owner-contact

Domains

subject: create info-order [your reference id]

```
domains0:xn--hans-mller-feb.info
language0:AFR
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C282828-LRMS
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

Example 2: create info-order with implicit nameserver-creation

subject: create info-order [your reference id]

```
domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-handle:C176269-LRMS
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C176219-LRMS
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

Example 3: create info-order with implicit contact-handle-creation of all contacts

subject: create info-order [your reference id]

```
domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
```

Domains

owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.BIZ order

Example 1: create biz-order with implicit contact-handle-creation of the owner-contact

domains0:xn--hans-mller-feb.biz
language0:AFR
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-email:hans@nose.net

Domains

owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create biz-order with implicit nameserver-creation

subject: create biz-order [your reference id]

domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-handle:CNEU-123
admin-contact-handle:CNEU-124
tech-contact-handle:CNEU-125
billing-contact-handle:CNEU-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net

Domains

ns2-ip-address:194.201.101.2

Example 3: create biz-order with implicit contact-handle-creation of all contacts

subject: create biz-order [your reference id]

domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Domains

.MOBI ORDER

Example 1: create mobi-order with implicit contact-handle-creation of the owner-contact

subject: create mobi-order [your reference id]

```
domains0:xn--hans-mller-feb.mobi
language0:AFR
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

Example 2: create mobi-order with implicit nameserver-creation

subject: create mobi-order [your reference id]

```
domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-handle:COMO-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

Example 3: create mobi-order with implicit contact-handle-creation of all contacts

subject: create mobi-order [your reference id]

```
domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
```

Domains

domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.NAME ORDER

Example 1: create name-order with implicit contact-handle-creation of the owner-contact

subject: create name-order [your reference id]

Domains

```
domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

Example 2: create name-order with implicit nameserver-creation

```
subject: create name-order [your reference id]
```

```
domains0:minus-109.name
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-handle:CNAM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

Example 3: create name-order with implicit contact-handle-creation of all contacts

```
subject: create name-order [your reference id]
```

```
domains0:minus-109.name
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
```


Domains

owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.US ORDER

Example 1: create us-order with implicit contact-handle-creation of the owner-contact

subject: create us-order [your reference id]

domains0:xn--hans-mlller-feb.us
language0:AFR
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-email:gonzo@nose.net

Domains

owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COUS-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create us-order with implicit nameserver-creation

subject: create us-order [your reference id]

domains0:minus-109.us
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-handle:COUS-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COUS-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create us-order with implicit contact-handle-creation of all contacts

subject: create us-order [your reference id]

domains0:minus-109.us
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo

Domains

admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.DE ORDER

Example 1: create de-order with implicit contact-handle-creation of the owner-contact

subject: create de-order [your reference id]

domains0:minus-10x.de
language0:GER
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nase
owner-contact-address-1:Musterstrasse 11
owner-contact-postal-code:4711
owner-contact-city:Musterhausen
owner-contact-country:DE
owner-contact-phone:49 13383794 504040
owner-contact-fax:49 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact

Domains

billing-contact-handle:CODE-1007

ns1-handle:ns.gonzo.net

ns2-handle:ns2.gonzo.net

Example 2: create net-order with implicit nameserver-creation

subject: create de-order [your reference id]

domains0:minus-109.de

domains1:minus-10a.de

domains2:minus-10b.de

domains3:minus-10c.de

domains4:minus-10d.de

domains5:minus-10e.de

period:2

owner-contact-handle:CODE-1007

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:CODE-1007

ns1-domain-name:nsxx1.gonzo.net

ns1-ip-address:194.201.101.1

ns2-domain-name:nsxx1.gonzo.net

ns2-ip-address:194.201.101.2

Example 3: create net-order with implicit contact-handle-creation of all contacts

subject: create de-order [your reference id]

domains0:minus-109.de

domains1:minus-10a.de

domains2:minus-10b.de

domains3:minus-10c.de

domains4:minus-10d.de

domains5:minus-10e.de

period:2

owner-contact-email:gonzo@nose.net

owner-contact-individual:Y

owner-contact-fname:gonzo

owner-contact-lname:nase

owner-contact-address-1:Musterstrasse 11

owner-contact-postal-code:4711

owner-contact-city:Musterhausen

owner-contact-country:DE

owner-contact-phone:49 13383794 504040

owner-contact-fax:49 13383794 504040

admin-contact-email:gonzo@nose.net

admin-contact-individual:Y

admin-contact-fname:gonzo

admin-contact-lname:nase

admin-contact-address-1:Musterstrasse 11

admin-contact-postal-code:4711

admin-contact-city:Musterhausen

admin-contact-country:DE

admin-contact-phone:49 13383794 504040

admin-contact-fax:49 13383794 504040

tech-contact-email:gonzo@nose.net

tech-contact-individual:Y

Domains

tech-contact-fname:gonzo
tech-contact-lname:nase
tech-contact-address-1:Musterstrasse 11
tech-contact-postal-code:4711
tech-contact-city:Musterhausen
tech-contact-country:DE
tech-contact-phone:49 13383794 504040
tech-contact-fax:49 13383794 504040
billing-contact-email:gonzo@nose.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nase
billing-contact-address-1:Musterstrasse 11
billing-contact-postal-code:4711
billing-contact-city:Musterhausen
billing-contact-country:DE
billing-contact-phone:49 13383794 504040
billing-contact-fax:49 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.CN ORDER

Example 1: create cn-order with implicit contact-handle-creation of the owner-contact

subject: create cn-order [your reference id]

domains0:xn--hans-mller-feb.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net

Domains

```
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

Example 2: create cn-order using existing cn-handles

```
subject: create cn-order [your reference id]
```

```
domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-handle:COCN-123
admin-contact-handle:COCN-124
tech-contact-handle:COCN-125
billing-contact-handle:COCN-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

Example 3: create cn-order with backreferences using @same-as

```
subject: create cn-order [your reference id]
```

```
domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
```

Domains

owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.EU ORDER

Example 1: create eu-order with implicit contact-handle-creation of all contacts

subject: create eu-order [your reference id]

domains0:xn--hans-mller-feb.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y

Domains

billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create eu-order using existing .eu-handles

subject: create eu-order [your reference id]

domains0:minus-109.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-handle:C123123
admin-contact-handle:C123124
tech-contact-handle:C123125
billing-contact-handle:C123126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create eu-order with backreferences using @same-as

subject: create eu-order [your reference id]

domains0:minus-109.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1

Domains

ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Keywords: create, order, registration

Last update: 2015-07-29 12:02

Domains

Modify a domain

Introduction

modify <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

- xxx

- asia

- me

With this request you can modify existing domains. You have to provide the following information within the

Domains

request:

- the domainname,
- handle(s) you want to change. (handles from the info-system are not valid)

The system will ignore not specified handles, so you have to provide only the handles, you would like to change.

Changes within the owner-contact

In case of changing the owner-contact-handle, the system checks, if lname and/or fname and/or organization differ from the original owner-contact-handle. If there are differences these changes will be ignored.

Request fields

mailsubject: modify <tld>-domain [your reference id]

Definition of this request

request-field	valid values		required
tld		biz eu	yes
sld	[a-z0-9-]{1,63}		yes

Domains

owner-contact-handle	Please, refer to the table below for the valid values.	no
admin-contact-handle		no
tech-contact-handle		no
billing-contact-handle		no
ns1-handle	@ns	no
ns2-handle		no
ns3-handle		no
ns4-handle		no
ns5-handle		no
ns6-handle		no

tld	contact handle
com	@comcont
net	@netcont
org	@orgcont
info	@infocont
biz	@bizcont
mobi	@mobicont
name	@namecont
us	@uscont
de	@decont
cn	@cncont
eu	@eucont

Example 1: modify com-domain

subject: modify domain [your reference id]

sld:gonzo
 tld:com
 admin-contact-handle:gonzo@nose.com#0
 tech-contact-handle:hans@nose.com
 ns1-handle:ns1.gonzo.net
 ns2-handle:ns2.gonzo.net

Example 2: modify net-domain

subject: modify net-domain [your reference id]

sld:gonzo
 tld:net
 admin-contact-handle:CNET-1234
 tech-contact-handle:CNET-1234
 ns1-handle:ns1.gonzo.net

Domains

ns2-handle:ns2.gonzo.net

Example 3: modify org-domain

subject: modify net-domain [your reference id]

sld:gonzo
tld:org
admin-contact-handle:CORG-1234
tech-contact-handle:CORG-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 4: modify info-domain

subject: modify info-domain [your reference id]

sld:gonzo
tld:info
admin-contact-handle:C112234-LRMS
tech-contact-handle:C112244-LRMS
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

OR

modify info-domain (new naming convention for info-handles)

subject: modify info-domain [your reference id]

sld:gonzo
tld:info
admin-contact-handle:C112244-LRMS
tech-contact-handle:CAFI-007
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 5: modify biz-domain

subject: modify biz-domain [your reference id]

sld:gonzo
tld:biz
admin-contact-handle:CNEU-11224
tech-contact-handle:CNEU-112244
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Domains

Example 6: modify mobi-domain

subject: modify mobi-domain [your reference id]

sld:gonzo
tld:mobi
admin-contact-handle:COMO-1234
tech-contact-handle:COMO-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 7: modify name-domain

subject: modify name-domain [your reference id]

sld:gonzo
tld:name
admin-contact-handle:CNAM-1234
tech-contact-handle:CNAM-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 8: modify us-domain

subject: modify us-domain [your reference id]

sld:gonzo
tld:us
admin-contact-handle:COUS-1234
tech-contact-handle:COUS-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 9: modify de-domain

subject: modify de-domain [your reference id]

sld:gonzo
tld:de
admin-contact-handle:CODE-1234
tech-contact-handle:CODE-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 10: modify cn-contact

Domains

subject: modify cn-contact [your reference id]

handle:COCN-1235
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 11: modify eu-domain

subject: modify eu-domain [your reference id]

sld:gonzo
tld:eu
admin-contact-handle:C112244
tech-contact-handle:C112244
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Keywords: modify-domain, nameserver, contacts

Last update: 2015-07-29 12:02

Domains

Renew a domain

Introduction

renew <id>-domain

Valid values for <id>

- com
- net
- org
- info
- biz
- name
- me
- co
- cn

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s)
- the renewalperiod or the desired expirationyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.

If the sum of the expire time and the renewal time is more than 10 years, we will reject your request.

This request is not working for domains, which are located on the old system. For these domains you have to check the documentation of the old system.

If you provide the expire year, this request will be rejected, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew request is sent twice by mistake.

Request fields

mailto:renew <id>-domain [your reference ID]

Domains

Definition of the request

You have to provide the domain name and the renewal period or the desired expiry year using the format "YYYY" on one line. You have to separate each field with a "+" (ASCII 002B). The maximum for the renewal period is 9 years.

domain	renewal period	expiry year
example.com	5	2025

COM renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew com-domain {your reference id}
domain@minu-08.com.1

Example 2: renew 5 domains for 4 years using the field period

subject: renew com-domain {your reference id}

domain@minu-08.com.4
domain@minu-13.com.4
domain@minu-15.com.4
domain@minu-16.com.4
domain@minu-140.com.4

Example 3: renew 5 domains for different years using the field period

subject: renew com-domain {your reference id}

domain@minu-08.com.1
domain@minu-13.com.2
domain@minu-15.com.3
domain@minu-16.com.4
domain@minu-140.com.5

Example 4: renew 1 domain using the field expiry/year

subject: renew com-domain {your reference id}
domain@minu-08.com.2005

NET Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew net-domain {your reference id}
domain@minu-08.net.1

Example 2: renew 5 domains for 4 years using the field period

subject: renew net-domain {your reference id}

domain@minu-08.net.4
domain@minu-13.net.4
domain@minu-15.net.4
domain@minu-16.net.4
domain@minu-140.net.4

Example 3: renew 5 domains for different years using the field period

subject: renew net-domain {your reference id}

domain@minu-08.net.1
domain@minu-13.net.2
domain@minu-15.net.3
domain@minu-16.net.4
domain@minu-140.net.5

Example 4: renew 1 domain using the field expiry/year

subject: renew net-domain {your reference id}
domain@minu-08.net.2005

ORG Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew org-domain {your reference id}
domain@minu-08.org.1

Example 2: renew 5 domains for 4 years using the field period

subject: renew org-domain {your reference id}

domain@minu-08.org.4
domain@minu-13.org.4
domain@minu-15.org.4
domain@minu-16.org.4
domain@minu-140.org.4

Example 3: renew 5 domains for different years using the field period

subject: renew org-domain {your reference id}

domain@minu-08.org.1
domain@minu-13.org.2
domain@minu-15.org.3
domain@minu-16.org.4
domain@minu-140.org.5

Example 4: renew 1 domain using the field expiry/year

subject: renew org-domain {your reference id}
domain@minu-08.org.2005

INFO Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew info-domain {your reference id}
domain@minu-08.info.1

Example 2: renew 5 domains for 4 years using the field period

subject: renew info-domain {your reference id}

domain@minu-08.info.4
domain@minu-13.info.4
domain@minu-15.info.4
domain@minu-16.info.4
domain@minu-140.info.4

Example 3: renew 5 domains for different years using the field period

subject: renew info-domain {your reference id}

domain@minu-08.info.1
domain@minu-13.info.2
domain@minu-15.info.3
domain@minu-16.info.4
domain@minu-140.info.5

Domains

Example 4: renew 1 domain using the field expirationyear

subject: renew .nl-domain [your reference id]
domainid: minusp-100-nls2005

DEZ Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew .bz-domain [your reference id]
domainid: minusp-100-bz-1

Example 2: renew 5 domains for 4 years using the field period

subject: renew .bz-domain [your reference id]

domainid: minusp-100-bz-4
domainid: minusp-110-bz-4
domainid: minusp-120-bz-4
domainid: minusp-130-bz-4
domainid: minusp-140-bz-4

Example 3: renew 5 domains for different years using the field period

subject: renew .bz-domain [your reference id]

domainid: minusp-100-bz-1
domainid: minusp-110-bz-2
domainid: minusp-120-bz-3
domainid: minusp-130-bz-4
domainid: minusp-140-bz-5

Example 4: renew 1 domain using the field expirationyear

subject: renew .bz-domain [your reference id]
domainid: minusp-100-bz-2005

NAME Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew .name-domain [your reference id]
domainid: minusp-100-name-1

Example 2: renew 5 domains for 4 years using the field period

subject: renew .name-domain [your reference id]

domainid: minusp-100-name-4
domainid: minusp-110-name-4
domainid: minusp-120-name-4
domainid: minusp-130-name-4
domainid: minusp-140-name-4

Example 3: renew 5 domains for different years using the field period

subject: renew .name-domain [your reference id]

domainid: minusp-100-name-1
domainid: minusp-110-name-2
domainid: minusp-120-name-3
domainid: minusp-130-name-4
domainid: minusp-140-name-5

Example 4: renew 1 domain using the field expirationyear

subject: renew .name-domain [your reference id]
domainid: minusp-100-name-2005

US Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew .us-domain [your reference id]
domainid: minusp-100-us-1

Example 2: renew 5 domains for 4 years using the field period

subject: renew .us-domain [your reference id]

domainid: minusp-100-us-4
domainid: minusp-110-us-4
domainid: minusp-120-us-4
domainid: minusp-130-us-4
domainid: minusp-140-us-4

Example 3: renew 5 domains for different years using the field period

subject: renew .us-domain [your reference id]

domainid: minusp-100-us-1
domainid: minusp-110-us-2
domainid: minusp-120-us-3
domainid: minusp-130-us-4
domainid: minusp-140-us-5

Example 4: renew 1 domain using the field expiration year

subject: renew .us-domain [your reference id]
domainid: minusp-100-us-2005

DE Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew .de-domain [your reference id]
domainid: minusp-100-de-1

Example 2: renew 5 domains for 4 years using the field period

subject: renew .de-domain [your reference id]

domainid: minusp-100-de-4
domainid: minusp-110-de-4
domainid: minusp-120-de-4
domainid: minusp-130-de-4
domainid: minusp-140-de-4

Example 3: renew 5 domains for different years using the field period

subject: renew .de-domain [your reference id]

domainid: minusp-100-de-1
domainid: minusp-110-de-2
domainid: minusp-120-de-3
domainid: minusp-130-de-4
domainid: minusp-140-de-5

Example 4: renew 1 domain using the field expirationyear

subject: renew .de-domain [your reference id]
domainid: minusp-100-de-2005

CA Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew .ca-domain [your reference id]
domainid: minusp-100-ca-1

Example 2: renew 5 domains for 4 years using the field period

subject: renew .ca-domain [your reference id]

domainid: minusp-100-ca-4
domainid: minusp-110-ca-4
domainid: minusp-120-ca-4
domainid: minusp-130-ca-4
domainid: minusp-140-ca-4

Example 3: renew 5 domains for different years using the field period

subject: renew .ca-domain [your reference id]

domainid: minusp-100-ca-1
domainid: minusp-110-ca-2
domainid: minusp-120-ca-3
domainid: minusp-130-ca-4
domainid: minusp-140-ca-5

Example 4: renew 1 domain using the field expire year

subject: renew .ca-domain [your reference id]
domainid: minusp-100-ca-2005

Keywords: renew, renewal

Domains

Last update: 2011-08-11 14:18

Domains

Transfer a domain

Introduction

transfer-into-domain

Valid values for <code>

- .com
- .net
- .org
- .biz
- .info
- .mobi
- .name
- .us
- .co
- .ca

With this request you can transfer a domain from 1 registrar to Joker.com.
You have to provide the following information within the request:

- the domain name,
- the sub-id,
- the billing contact handle,

You can transfer 1 .com domain with one request.

If you transfer a domain to Joker.com the domain will be renewed for one year.

As you can see, we don't need information about the owner-contact. We will detect this information from the whois of the current registrar and we will create the contact handle for the owner-contact automatically.

You need to provide us with a so-called auth-id. You have to ask the current registrar for this auth-id. If you provide an invalid auth-id, the transfer will be declined by the current registrar.

As you can see, we need the billing contact handle. We recommend using a billing handle with the email address of your "joker-email". If you use a contact handle with a different email than your joker-email, you can't administer the transferred domain using the webinterface and the person with access to the email, which is shown in the provided billing handle will have access using the web-interface.

If you don't have a com contact handle with your "joker-email", you have to create a com-handle using the "create com-contact" request.

Domains

TRANSFER INFO DOMAIN
Example 1: transfer info-domain
subject: transfer info-domain [your reference id]
domain@mitup 100.00
auth-id:00000AAG
billig-combo-handle:C1HE200-L200

TRANSFER BIZ DOMAIN
Example 1: transfer biz-domain
subject: transfer biz-domain [your reference id]
domain@mitup 100.00
auth-id:00000AAG
billig-combo-handle:CNBU-123

TRANSFER NAME DOMAIN
Example 1: transfer name-domain
subject: transfer name-domain [your reference id]
domain@mitup 100.00
auth-id:00000AAG
billig-combo-handle:CNAM-1234

TRANSFER US DOMAIN
Example 1: transfer us-domain
subject: transfer us-domain [your reference id]
domain@mitup 100.00
auth-id:00000AAG
billig-combo-handle:COUS-1234

TRANSFER DE DOMAIN
Example 1: transfer de-domain
subject: transfer de-domain [your reference id]
domain@mitup 100.00
auth-id:00000AAG
billig-combo-handle:CODE-1234
TRANSFER CO DOMAIN
Example 1: transfer co-domain
subject: transfer co-domain [your reference id]
domain@mitup 100.00
auth-id:00000AAG
billig-combo-handle:COCN-1234

Keywords: transfer, auth-id

Last update: 2011-08-11 14:14

Domains

Delete a domain

Introduction

With this request you can delete a domain at Joker.com.

You have to provide the following information within the request:

- domain name(s).
- the special flag force.

ATTENTION

If you delete a domain within the first 72 hours after the registration, the registration-fee will be refunded to your account.

If Joker.com receives the delete-request more than 72 hours after the registration, you have to provide the flag "force": "1", in order to accept that the registration-fee will not be refunded to your account. If you do not send the "force": "1" in such a case, the request will be rejected.

Request fields

mailsubject: delete domain [your reference id]

Definition of the request

Please, do not forget to provide the domain name and the force-flag set to 1 if the domain is older 72h.

Request field	Request value	Response
mailsubject	delete domain [your reference id]	OK
force	1	OK

Domains

DELETE COM DOMAIN

Example 1: delete a domain during the first 72 hours after registration
subject: delete domain [your reference id]

tld:com
sld:frezel

Example 2: delete a domain after the first 72 hours after registration
subject: delete domain [your reference id]

tld:com
sld:frezel
force:1

Example 3: delete a domain only for the case that a refund is possible!
subject: delete domain [your reference id]

tld:com
sld:frezel
force:0

Keywords: delete-domain

Last update: 2011-08-11 15:45

Domains

List domains

Introduction

List domains

With this request you can get a list (lexicographically sorted) of all the domains, you have currently registered at joker.com. You have to provide the target registry within the request:

OTU = .otm-net

OPM = .net

OM = .net

OG = .org

OH = .edu

IO = .io

MOB = .mobi

NAME = .mobi

OR = .de

OT = .de

OU = .de

UL = .de

LISTDOMAINS

- Only 20.000 domains are listed. If you have more than 20.000 domains under 1 registry at joker.com, you have to track the domain names yourself.
- In case you have more than 20.000 domains at joker.com under 1 registry, the request will not work for you. The listing would be incomplete and it will be missing random domains.
- This request works only with the new joker.com system.

Request body

multiple: list domains [your reference id]

Definition of the request:

Request body	Get domains	Response
multiple: list domains [your reference id]	OTU,OPM,OM,OG,OH,IO,MOB,NAME,OR,OT,OU,UL	OTU,OPM,OM,OG,OH,IO,MOB,NAME,OR,OT,OU,UL

LISTDOMAINS

Example 1: list domains for .com-domains

subject: list domains [your reference id]

target:com

Example 2: list domains for .net-domains

subject: list domains [your reference id]

target:net

Example 3: list domains for .org-domains

subject: list domains [your reference id]

target:org

Example 4: list domains for .edu-domains

subject: list domains [your reference id]

target:edu

Example 5: list domains for .io-domains

subject: list domains [your reference id]

target:io

Example 6: list domains for .de-domains

subject: list domains [your reference id]

target:de

Domains

Example 7: list domains for .cn domains
subject: list domains [your reference ID]
begin

Keywords: list-domains

Last update: 2011-08-11 15:44

Domains

Lock a domain

Introduction

lock domain

With this request you can lock a domain in order to prevent fraudulent transfer attempts. If a domain is locked, each transfer request from a foreign registrar will be declined.

You have to provide the following information within the request:

● domain name

You can lock 1 domain with one request.

Request fields

subject: lock domain [your reference id]

Definition of this request

field name	field value	field type

Example 1: lock a domain

subject: lock domain [your reference id]

subject: lock domain [your reference id]

Keywords: lock-domain, protection

Last update: 2011-08-11 15:46

Domains

Unlock a domain

Introduction

unlock domain

With this request you can unlock a domain. If you want to transfer a domain to a foreign registrar, the domain has to be unlocked.

You have to provide the following information within the request:

● domain name

You can unlock 1 domain with one request.

Request fields

subject: unlock domain [your reference id]

Definitions of the request

field name	description	example
subject	subject: unlock domain [your reference id]	subject: unlock domain [your reference id]

Example 1: unlock a domain
subject: unlock domain [your reference id]
open-mnue-100.com

Keywords: unlock-domain, protection

Last update: 2011-08-11 15:46

Domains

Get Auth-id

Introduction

With this request you can retrieve the auth-id for a particular domain. That request is needed only for the TLDs: org/inu/az.

You have to provide the following information within the request:

- domain name

You can retrieve the auth-id for 1 domain with one request.

Request fields

mailsubject: get-auth-id [your-reference-id]

Definition of the request

Field Name	Field Value	Field Name	Field Value	Field Name	Field Value	Field Name	Field Value
mailsubject	get-auth-id [your-reference-id]	mailsubject	get-auth-id [your-reference-id]	mailsubject	get-auth-id [your-reference-id]	mailsubject	get-auth-id [your-reference-id]

Example 1: retrieve the auth-id for a .org-domain

mailsubject: get-auth-id [your-reference-id]
ipn:ipnuser-123.org

Example 2: retrieve the auth-id for a .biz-domain

mailsubject: get-auth-id [your-reference-id]
ipn:ipnuser-123.biz

Example 3: retrieve the auth-id for a .az-domain

mailsubject: get-auth-id [your-reference-id]
ipn:ipnuser-123.az

Keywords: transfer, auth-id

Last update: 2011-08-11 15:46

Domains

Grant Roles/Domain Permissions, Internal Transfer

Introduction

With this request you can assign [roles/permissions of domains](#) to other Joker.com users. The special role "creator" is an equivalent to an internal transfer of that domain to another Joker.com user. In this case, the domain is assigned to the receiving account, including all rights and permissions on the domain.

There are two variants to use this functionality: If the user id (Joker.com user account id) is given, and the account id matches the associated email address, the role is applied immediately - there will be no request for confirmation on the receiver's side. In case the user id is not given, but only the email address, the transaction has to be acknowledged by the receiver. For this, he will get an email, containing a link and a key. Either the link has to be clicked, or the key has to be applied using Joker.com (or Transfer). This can also be used for users which do not yet have a

Joker.com account.

You have to provide the following parameters:

- domain name (the domain you want to grant somebody else permissions on)
- destination client email (the email address of the user you want to receive permissions)

The following parameters are optional:

- destination client id (ID of Joker.com account - always shown in the upper right on Joker.com, also conforms to "header id" - must match the destination client email)
- desired role (type of permission you want to assign to "client email" resp. "client id" - one of "admin@jcb@joker.com", "creator" means "all permissions" and is equivalent to an internal transfer of "assignment" - also see [table 1](#))

Request fields

MultiSubject: joker-internal-transfer [your reference id]

Definition of the request

Valid values for client_id: all Joker.com IDs

Parameter	Default value	Required
client_id	[+40-9]31-632-+00-	no
destination-client-email	@email	yes
destination-client-id	[0-90]	no
desired-role	admin@jcb@joker.com (if omitted, default is "creator")	no

Example 1: assign billing-role to user 123456 (demo)

Domains

subject: joker-email-transfer [pour référence id]

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

destination-client-id:123456

desired-role:billing

Example 2:

assign 'creator'-role to user 'example-user@gmail.com' (internal transfer with invitation)

subject: joker-email-transfer [pour référence id]

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

desired-role:creator

Keywords: grants, roles, contacts, permissions, invitations

Last update: 2011-08-17 09:35

Domains

Create a contact

Introduction

create vld-order

Valid values for vld-order

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- au

With the request you can create person contacts. You can create 1 contact with one request.

ATTENTION

You will find the request field "individual" within the request definition. If you set it to "Y", you have to provide the request fields "trname" and "trname". If you set it to "N", you have to provide information in the request field "organization".

As the value for com shows a field called person, the rules for generating the field are the following:
If you provide the field "trname", the value is always always the values of this field, regardless of "trname" and "trname".

If you only provide the field "trname" and the field "trname", we will generate the field "trname" as the result of the concatenation of "trname" + "-" + "trname".

The result of "create vld-order" is a reference which is following the format:

- CCOM-number-e.g. CCOM-176269 for a com domain.
- CNET-number-e.g. CNET-176269 for a net domain.
- CORG-number-e.g. CORG-176269 for a org domain.
- Cinfo-number-e.g. C176269LRMS for a info domain.
- CBIZ-number-e.g. CBIZ-176269 for a biz domain.
- CMobi-number-e.g. CMobi-176269 for a mobi domain.
- CName-number-e.g. CName-176269 for a name domain.
- CUS-number-e.g. CUS-176269 for a us domain.
- CDE-number-e.g. CDE-176269 for a de domain.
- CCN-number-e.g. CCN-176269 for a cn domain.
- CAU-number-e.g. CAU-176269 for a au domain.

Request fields

multiSubject create vld-order [your reference ID]

Definition of this request

Contacts

ATTENTION

According to the rules of DENIC, you have to provide a first name for the admin-c and the tech-c of a .de domain.

CONTACT ID	CONTACT DATA		CONTACT TYPE
	CONTACT NAME	CONTACT PHONE	
CONTACT 1			CONTACT TYPE 1
CONTACT 2			CONTACT TYPE 1
CONTACT 3			CONTACT TYPE 1
CONTACT 4			CONTACT TYPE 1
CONTACT 5			CONTACT TYPE 1
CONTACT 6			CONTACT TYPE 1
CONTACT 7			CONTACT TYPE 1
CONTACT 8			CONTACT TYPE 1
CONTACT 9			CONTACT TYPE 1
CONTACT 10			CONTACT TYPE 1
CONTACT 11			CONTACT TYPE 1
CONTACT 12			CONTACT TYPE 1
CONTACT 13			CONTACT TYPE 1
CONTACT 14			CONTACT TYPE 1
CONTACT 15			CONTACT TYPE 1
CONTACT 16			CONTACT TYPE 1
CONTACT 17			CONTACT TYPE 1
CONTACT 18			CONTACT TYPE 1
CONTACT 19			CONTACT TYPE 1
CONTACT 20			CONTACT TYPE 1
CONTACT 21			CONTACT TYPE 1
CONTACT 22			CONTACT TYPE 1
CONTACT 23			CONTACT TYPE 1
CONTACT 24			CONTACT TYPE 1
CONTACT 25			CONTACT TYPE 1
CONTACT 26			CONTACT TYPE 1
CONTACT 27			CONTACT TYPE 1
CONTACT 28			CONTACT TYPE 1
CONTACT 29			CONTACT TYPE 1
CONTACT 30			CONTACT TYPE 1
CONTACT 31			CONTACT TYPE 1
CONTACT 32			CONTACT TYPE 1
CONTACT 33			CONTACT TYPE 1
CONTACT 34			CONTACT TYPE 1
CONTACT 35			CONTACT TYPE 1
CONTACT 36			CONTACT TYPE 1
CONTACT 37			CONTACT TYPE 1
CONTACT 38			CONTACT TYPE 1
CONTACT 39			CONTACT TYPE 1
CONTACT 40			CONTACT TYPE 1
CONTACT 41			CONTACT TYPE 1
CONTACT 42			CONTACT TYPE 1
CONTACT 43			CONTACT TYPE 1
CONTACT 44			CONTACT TYPE 1
CONTACT 45			CONTACT TYPE 1
CONTACT 46			CONTACT TYPE 1
CONTACT 47			CONTACT TYPE 1
CONTACT 48			CONTACT TYPE 1
CONTACT 49			CONTACT TYPE 1
CONTACT 50			CONTACT TYPE 1
CONTACT 51			CONTACT TYPE 1
CONTACT 52			CONTACT TYPE 1
CONTACT 53			CONTACT TYPE 1
CONTACT 54			CONTACT TYPE 1
CONTACT 55			CONTACT TYPE 1
CONTACT 56			CONTACT TYPE 1
CONTACT 57			CONTACT TYPE 1
CONTACT 58			CONTACT TYPE 1
CONTACT 59			CONTACT TYPE 1
CONTACT 60			CONTACT TYPE 1
CONTACT 61			CONTACT TYPE 1
CONTACT 62			CONTACT TYPE 1
CONTACT 63			CONTACT TYPE 1
CONTACT 64			CONTACT TYPE 1
CONTACT 65			CONTACT TYPE 1
CONTACT 66			CONTACT TYPE 1
CONTACT 67			CONTACT TYPE 1
CONTACT 68			CONTACT TYPE 1
CONTACT 69			CONTACT TYPE 1
CONTACT 70			CONTACT TYPE 1
CONTACT 71			CONTACT TYPE 1
CONTACT 72			CONTACT TYPE 1
CONTACT 73			CONTACT TYPE 1
CONTACT 74			CONTACT TYPE 1
CONTACT 75			CONTACT TYPE 1
CONTACT 76			CONTACT TYPE 1
CONTACT 77			CONTACT TYPE 1
CONTACT 78			CONTACT TYPE 1
CONTACT 79			CONTACT TYPE 1
CONTACT 80			CONTACT TYPE 1
CONTACT 81			CONTACT TYPE 1
CONTACT 82			CONTACT TYPE 1
CONTACT 83			CONTACT TYPE 1
CONTACT 84			CONTACT TYPE 1
CONTACT 85			CONTACT TYPE 1
CONTACT 86			CONTACT TYPE 1
CONTACT 87			CONTACT TYPE 1
CONTACT 88			CONTACT TYPE 1
CONTACT 89			CONTACT TYPE 1
CONTACT 90			CONTACT TYPE 1
CONTACT 91			CONTACT TYPE 1
CONTACT 92			CONTACT TYPE 1
CONTACT 93			CONTACT TYPE 1
CONTACT 94			CONTACT TYPE 1
CONTACT 95			CONTACT TYPE 1
CONTACT 96			CONTACT TYPE 1
CONTACT 97			CONTACT TYPE 1
CONTACT 98			CONTACT TYPE 1
CONTACT 99			CONTACT TYPE 1
CONTACT 100			CONTACT TYPE 1

```

CREATE COM CONTACT
Example 1: create com-contact (name will be generated from frame and frame)
subject: create com-contact [your reference ID]
email:gonzo@com.net
individual:Y
frame:gonzo
frame:gonzo
address-2:App. 1
address-3:Frankfurt, Hessen
address-2:App. 1
postal-code:60311
city:Frankfurt
country:DE
phone:44 12345678901234567890

Example 2: create com-contact (name and frame will be ignored)
subject: create com-contact [your reference ID]
email:gonzo@com.net
individual:Y
frame:gonzo
frame:gonzo
name:Mr. Gerdon Nisse
name-2:Gerdon Nisse
address-2:App. 1
address-3:Frankfurt, Hessen
address-2:App. 1
postal-code:60311
city:Frankfurt
country:DE
phone:44 12345678901234567890
    
```

```

CREATE NET CONTACT
Example 1: create net-contact (name will be generated from frame and frame)
subject: create net-contact [your reference ID]
email:gonzo@com.net
individual:Y
frame:gonzo
frame:gonzo
name:Mr. Gerdon Nisse
name-2:Gerdon Nisse
address-2:App. 1
address-3:Frankfurt, Hessen
address-2:App. 1
postal-code:60311
city:Frankfurt
country:DE
phone:44 12345678901234567890

Example 2: create net-contact (name and frame will be ignored)
subject: create net-contact [your reference ID]
email:gonzo@com.net
individual:Y
frame:gonzo
frame:gonzo
name:Mr. Gerdon Nisse
name-2:Gerdon Nisse
address-2:App. 1
address-3:Frankfurt, Hessen
address-2:App. 1
postal-code:60311
city:Frankfurt
country:DE
phone:44 12345678901234567890
    
```

```

CREATE ORG CONTACT
Example 1: create org-contact (name will be generated from frame and frame)
subject: create org-contact [your reference ID]
email:gonzo@com.org
    
```

Contacts

individualY
frame group
frame name
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

Example 2: create org-contact (frame and frame will be ignored)

subject: create org-contact [your reference id]

email: gregor@broad.org
individualY
frame group
frame name
name: Mr. Gernot Noss
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

CREATE INFO CONTACT

Example 1: create info-contact (frame will be generated from frame and frame)

subject: create info-contact [your reference id]

email: gregor@broad.info
individualY
frame group
frame name
name: Mr. Gernot Noss
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

Example 2: create info-contact (frame and frame will be ignored)

subject: create info-contact [your reference id]

email: gregor@broad.info
individualY
frame group
frame name
name: Mr. Gernot Noss
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

CREATE BIZ CONTACT

Example 1: create biz-contact (frame will be generated from frame and frame)

subject: create biz-contact [your reference id]

email: gregor@broad.biz
individualY
frame group
frame name
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

Example 2: create biz-contact (frame and frame will be ignored)

subject: create biz-contact [your reference id]

email: gregor@broad.biz
individualY
frame group
frame name
name: Mr. Gernot Noss
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

CREATE NAME CONTACT

Example 1: create name-contact (frame will be generated from frame and frame)

subject: create name-contact [your reference id]

email: gregor@broad.net
individualY
frame group
frame name
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

Example 2: create name-contact (frame and frame will be ignored)

subject: create name-contact [your reference id]

email: gregor@broad.net
individualY
frame group
frame name
name: Mr. Gernot Noss
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

CREATE US CONTACT

Example 1: create us-contact (frame will be generated from frame and frame)

subject: create us-contact [your reference id]

email: gregor@broad.us
individualY
frame group
frame name
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

Example 2: create us-contact (frame and frame will be ignored)

subject: create us-contact [your reference id]

email: gregor@broad.us
individualY
frame group
frame name
name: Mr. Gernot Noss
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

CREATE DE CONTACT

Example 1: create de-contact (frame will be generated from frame and frame)

subject: create de-contact [your reference id]

email: gregor@broad.de
individualY
frame group
frame name
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 49 1383794 50640

Example 2: create de-contact (frame and frame will be ignored)

subject: create de-contact [your reference id]

email: gregor@broad.de
individualY
frame group
frame name
name: Mr. Gernot Noss
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 49 1383794 50640

CREATE CN CONTACT

Example 1: create cn-contact (frame will be generated from frame and frame)

subject: create cn-contact [your reference id]

email: gregor@broad.cn
individualY
frame group
frame name
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

Example 2: create cn-contact (frame and frame will be ignored)

subject: create cn-contact [your reference id]

email: gregor@broad.cn
individualY
frame group
frame name
name: Mr. Gernot Noss
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

CREATE EU CONTACT

Example 1: create eu-contact (frame will be generated from frame and frame)

subject: create eu-contact [your reference id]

email: gregor@broad.eu
individualY
frame group
frame name
address-1 transfered mess
address-2 App, 1
postal-code 4711
city name
country DE
phone 44 1383794 50640

Contacts

phone 44 1283754 50640
Example 2: create an contact (Name and name will be ignored)
subject: create an contact (your reference id)
email: gregor@haha.net
password:
name: gregor
name: gregor
name: gregor
name: Gerdia Niss
address: 1234567890 street
address: 2 Ave. 1
city: 12345
country: DE
phone: 44 1283754 50640

Keywords: whois, contacts

Last update: 2011-08-11 15:38

Contacts

Example 1: modify name-contact
subject: modify name-contact [your reference id]
header: CN=CN=123
address: 1 boulevard France
postal-code=67111
city=Strasbourg
country=DE

phone: +44 1238754 50600

MODIFY US CONTACT
Example 1: modify us-contact
subject: modify us-contact [your reference id]
header: CN=CN=123
address: 1 boulevard France
postal-code=67111
city=Strasbourg
country=DE

phone: +44 1238754 50600

MODIFY DE CONTACT
Example 1: modify de-contact
subject: modify de-contact [your reference id]
header: CN=CN=123
address: 1 boulevard France
postal-code=67111
city=Strasbourg
country=DE

phone: +44 1238754 50600

MODIFY EU CONTACT
Example 1: modify eu-contact
subject: modify eu-contact [your reference id]
header: CN=CN=123
address: 1 boulevard France
postal-code=67111
city=Strasbourg
country=DE

phone: +44 1238754 50600

Keywords: whois, contacts

Last update: 2011-08-11 15:39

Contacts

Change an address

Introduction

Change v6to-address

Valid values for v6to:

- com
- net
- org
- info
- biz
- mil
- name
- us
- de
- ca

With this request you can change the address of the domain owner.

ATTENTION

It is not possible to change the following fields of the contact record:

- individual
- home
- frame
- site
- organization
- email

Request fields

method:post change-com-address {your-reference-id}

Definition of this request

Request ID	Request Name	Request
REQ000	change-com-address	
REQ001	change-com-address	
REQ002	change-com-address	
REQ003	change-com-address	

Contacts

CHANGE CNF ADDRESS

Example 1: change cnf address [your reference id]

subject: change cnf address [your reference id]
 domain@joker.com
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

CHANGE NET ADDRESS

Example 1: change net address

subject: change net address [your reference id]

domain@joker.de
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

CHANGE INFO ADDRESS

subject: change org address [your reference id]

domain@joker.org
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

CHANGE INFO ADDRESS

subject: change info address [your reference id]

domain@joker.info
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

CHANGE BIO ADDRESS

subject: change bio address [your reference id]

domain@joker.bio
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

CHANGE NAME ADDRESS

Example 1: change name address

subject: change name address [your reference id]

domain@joker.name
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

CHANGE US ADDRESS

subject: change us address [your reference id]

domain@joker.us
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

CHANGE DE ADDRESS

subject: change de address [your reference id]

domain@joker.de
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

CHANGE CN ADDRESS

subject: change cn address [your reference id]

domain@joker.cn
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

CHANGE CN ADDRESS

subject: change cn address [your reference id]

domain@joker.cn
 address: 1 Normal Street
 postal-code: 4711
 city: Mainz
 country: DE
 phone: +49 1383794 59040

Keywords: whois, contacts

Last update: 2011-08-11 15:39

Contacts

Change an owner

Introduction

With this request you can change the owner of a .com/.net/.org/.info/.mobi/.name/.biz/.de/.cn/.eu/.us-domain.

Request fields

mailsubject: change owner [your reference id]

Definition of this request

request-field	valid values	required
domains0		yes
email	an email without the numerical suffix	no
individual	[YN]	no
name	[\x20-\x7e]{0,80}	no
lname	[\x20-\x7e]{0,80}	no
fname	[\x20-\x7e]{0,80}	no
title	[\x20-\x7e]{0,80}	no
organization	[\x20-\x7e]{0,80}	no
address-1	[\x20-\x7e]{0,80}	no
address-2	[\x20-\x7e]{0,80}	no
postal-code	[\x20-\x7e]{0,50}	no
state	[\x20-\x7e]{0,80}	no
city	[\x20-\x7e]{0,80}	no
country	@country	no
phone	[\x20-\x7e]{0,50}	no
fax	[\x20-\x7e]{0,50}	no no
lock-opt-out	[YN]	

CHANGE .COM OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.com
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey

Contacts

country:DE
phone:44 13383794 504040

CHANGE .NET OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.net
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .ORG OWNER

Example 1: change owner

subject: change owner [your reference id]
domains0:gonzo.org
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .INFO OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.info
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .BIZ OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.biz
fname:hans
lname:nose

Contacts

address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .NAME OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.name
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .US OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.us
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .DE OWNER

Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.de
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

CHANGE .CN OWNER

Example 1: change owner

subject: change owner [your reference id]

Contacts

domains0:gonzo.cn
fname:hans
lname:nose
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Keywords: whois, contacts, transfer

Last update: 2016-11-21 15:06

Contacts

.asia Contacts

new-handle (explicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COAS-number-, e.g. COAS-176265.

ATTENTION

The name of the request field depends on the contact. If you want to create a contact for the owner-contact, you have to replace the "-" at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "-" at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "-" at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "-" at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory. If you do not provide the **firstname**, you have to provide the request field **name**. If **firstname** and **name** are not found, this is very important for the whole output. Everytime a field **person** is shown, if you are using the request field **name**, the whole is showing the value for **name**, regardless the content of the request fields **name** and **firstname**. If you do not provide the request field **name** but you are providing the request fields **name** and **firstname**, the whole is showing the concatenation of these fields.

There is also a new request field called **address2** within the contact definition. This field is not mandatory. It is simply the 3rd line of the address.

request field	request field	request field
name	name	name
firstname	name	name
lastname	name	name
email	name	name
phone	name	name
address	name	name
address2	name	name
address3	name	name
city	name	name
country	name	name
zip	name	name
company	name	name
website	name	name
phone2	name	name
fax	name	name

Contacts

An existing contact (`@handle.com` or `@name-ns`) (asia only)

This means an existing contact handle in the JOKER DATABASE.

Example:

```
owner-contact-handle:COAS-170209
admin-contact-handle:COAS-170209
tech-contact-handle:COAS-170209
billing-contact-handle:COAS-170209
```

ASIA domains require an additional type of contact, the CED contact. This contact has to have its residence in the Asia/Australasia area.

The Joker.com Registry Gateways automatically will use your provided tech-contact for the CED contact.

This means that the request for you remains consistent with the usual requests, you only have to make sure that the country code is correct, otherwise the Asia registry will reject the order.

In case you have entered a non-existing contact handle, the system will send you an errorcode.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The `@name-as` makes always replace the value for the specified contact handle with the email address of the macrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for asia requests the contact handles for (.com|.net|.org|.info|.biz|.de) contacts are not allowed. If you are referencing to a shortcut like `hans@hose.net`, you will get an error.

Keywords: whois, contacts, asia

Last update: 2011-08-11 15:41

Contacts

Create a nameserver

Introduction

create-05-04

Valid values for <id>

- com
- net
- org
- info
- biz
- mobi
- name
- us
- ca
- co
- tv

With this request you can create an entry for a nameserver in the Joker.com Database. If a nameserver is created, you can reference this nameserver using the hostname during a "create order" request.

ATTENTION:

Only nameservers, which Joker.com is responsible for, will be shown with the ip-address in the whole output.

If you submit a "create order" request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code-domain, the values for the ip-addresses are ignored.

Request fields

mailsubject: create-05-04 [your reference id]

Field Name	Field Values	Required
createOrderName	Example: http://www.joker.com/contacts/createOrderName	no
createOrderIP		no

Nameservers

```
CREATE COM NAMESERVER
Example 1: create com-ns
subject create com-ns [your reference id]
no-domain-name no.f.dummy.net
no-ip-address 194.111.43.1
```

```
CREATE NET NAMESERVER
Example 1: create net-ns
subject create net-ns [your reference id]
no-domain-name no.f.dummy.net
no-ip-address 194.111.43.1
```

```
CREATE ORG NAMESERVER
Example 1: create org-ns
subject create org-ns [your reference id]
no-domain-name no.f.dummy.org
no-ip-address 194.111.43.1
```

```
CREATE INFO NAMESERVER
Example 1: create info-ns
subject create info-ns [your reference id]
no-domain-name no.f.dummy.info
no-ip-address 194.111.43.1
```

```
CREATE BIZ NAMESERVER
Example 1: create biz-ns
subject create biz-ns [your reference id]
no-domain-name no.f.dummy.biz
no-ip-address 194.111.43.1
```

```
CREATE NAME NAMESERVER
Example 1: create name-ns
subject create name-ns [your reference id]
no-domain-name no.f.dummy.name
no-ip-address 194.111.43.1
```

```
CREATE US NAMESERVER
Example 1: create us-ns
subject create us-ns [your reference id]
no-domain-name no.f.dummy.us
no-ip-address 194.111.43.1
```

```
CREATE DE NAMESERVER
Example 1: create de-ns
subject create de-ns [your reference id]
no-domain-name no.f.dummy.de
no-ip-address 194.111.43.1
```

```
CREATE CN NAMESERVER
Example 1: create cn-ns
subject create cn-ns [your reference id]
no-domain-name no.f.dummy.cn
no-ip-address 194.111.43.1
```

```
CREATE EU NAMESERVER
Example 1: create eu-ns
subject create eu-ns [your reference id]
no-domain-name no.f.dummy.eu
no-ip-address 194.111.43.1
```


Nameservers

Last update: 2011-08-11 15:42

Nameservers

Modify a nameserver

Introduction

modify-ns-com

Valid values for <ns>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- co
- cn
- ru

With this request you can change the ip-address of a nameserver in the Joker.com database.

ATTENTION

Only nameservers, which Joker.com is responsible for, will be shown with the ip-address in the whole-output, so only these nameservers could be changed.

If you submit a "modify-ns"-request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code-domain, this request will be ignored.

Request Fields

multi-ns: modify-ns [your reference id]

Definition of this request

Request Field	Old Value	Example
multi-ns	modify-ns [your reference id]	ns
ip-address	[ip-address]	ns

MODIFY COM NAMESERVER

Example 1: modify-com-ns
subject: modify-com-ns [your reference id]
multi-ns: modify-ns [your reference id]

ip-address: 194.111.43.1

MODIFY NET NAMESERVER

Example 1: modify-net-ns
subject: modify-net-ns [your reference id]

Nameservers

no-handle.net_dumpty.com

no-p-address:194.111.43.1

MODIFY ORG NAMESERVER

Example 1: modify.org.no
subject: modify.org.no [your reference id]
no-handle.net_dumpty.org
no-p-address:194.111.43.1

MODIFY INFO NAMESERVER

Example 1: modify.info.no
subject: modify.info.no [your reference id]
no-handle.net_dumpty.info
no-p-address:194.111.43.1

MODIFY BIZ NAMESERVER

Example 1: modify.biz.no
subject: modify.biz.no [your reference id]
no-handle.net_dumpty.biz no-p-address:194.111.43.1

MODIFY NAME NAMESERVER

Example 1: modify.name.no
subject: modify.name.no [your reference id]
no-handle.net_dumpty.name
no-p-address:194.111.43.1

MODIFY US NAMESERVER

Example 1: modify.us.no
subject: modify.us.no [your reference id]
no-handle.net_dumpty.us
no-p-address:194.111.43.1

MODIFY DE NAMESERVER

Example 1: modify.de.no
subject: modify.de.no [your reference id]
no-handle.net_dumpty.de
no-p-address:194.111.43.1

MODIFY CN NAMESERVER

Example 1: modify.cn.no
subject: modify.cn.no [your reference id]
no-handle.net_dumpty.cn
no-p-address:194.111.43.1

MODIFY EU NAMESERVER

Example 1: modify.eu.no
subject: modify.eu.no [your reference id]
no-handle.net_dumpty.eu
no-p-address:194.111.43.1

Keywords: nameserver, modify-domain

Last update: 2011-08-11 15:42

Nameservers Support

Introduction

With this request you can send a question to the support team at Joker.com. Only questions, which are sent to the e-mail gateway are accepted.

ATTENTION

Please, make sure that you sign your message with the keypair sent by you to Joker.com during your webmaster registration. Please, also make sure not to include any characters that are not part of the 7-bit ASCII standard and do not use trailing blanks (i.e. every non-blank line has to end with a non-whitespace character).

Request fields

mailto:subject support [your reference id]

Example 1

```
subject support [your reference id]
-----BEGIN PGP SIGNED MESSAGE-----
Hash: SHA1

Enter your question here.
Don't forget the topic in question.
-----BEGIN PGP SIGNATURE-----
Version: GnuPG v1.3.2 (GNU/Linux)
Comment: For info see http://www.gnupg.org
iQIChwEABAAQAAABAAQAAJhRwOnOvLjMmMmCwllbF3d3wRQcRlU
dAgQdFmDhUdLmDmDmDm
=JfMm
-----END PGP SIGNATURE-----
```

Keywords: support,PGP

Other

Last update: 2011-08-11 15:43

Other CheckD

please see section '2.5 Tools': [Domain-Check](#)

Keywords: checkd registration, whois, domain check

Last update: 2009-04-02 12:14

Tools

Complete set of examples for download

We offer all examples summarized in a textfile. The file is attached to this article. As it has a lot of examples, it is recommended to use the search function of your text editor to find information.

Keywords: mail-gw, examples

Last update: 2012-09-27 16:33

Examples