

# Joker.com FAQ

## Table of Content

|   |     |
|---|-----|
| <b>Requests</b> .....                                   | 3   |
| General Instructions .....                              | 3   |
| List of currently working requests .....                | 5   |
| Macros .....  | 14  |
| What is a macro? .....                                  | 14  |
| E-mail Address .....                                    | 15  |
| .com/.net Contacts .....                                | 16  |
| .com Contacts .....                                     | 18  |
| .net Contacts .....                                     | 20  |
| .org Contacts .....                                     | 22  |
| .info Contacts .....                                    | 24  |
| .biz Contacts .....                                     | 26  |
| .mobi Contacts .....                                    | 29  |
| .name Contacts .....                                    | 32  |
| .us Contacts .....                                      | 34  |
| .de Contacts .....                                      | 37  |
| .cn Contacts .....                                      | 40  |
| .eu Contacts .....                                      | 43  |
| Valid domain names .....                                | 46  |
| Nameserver .....  | 47  |
| Zonefile entries .....                                  | 48  |
| IP .....  | 50  |
| Domain renewal .....                                    | 51  |
| Country code .....                                      | 52  |
| Language code .....                                     | 58  |
| .me Contacts .....                                      | 60  |
| DNS/URL-Forwarding .....                                | 62  |
| Create a dns-configuration .....                        | 62  |
| Delete a dns-configuration .....                        | 65  |
| List a dns-configuration .....                          | 66  |
| Domains .....   | 67  |
| Create an order .....                                   | 67  |
| Modify a domain .....                                   | 91  |
| Renew a domain .....                                    | 97  |
| Transfer a domain .....                                 | 101 |
| Delete a domain .....                                   | 104 |
| List domains .....                                      | 106 |
| Lock a domain .....                                     | 108 |
| Unlock a domain .....                                   | 109 |
| Get Auth-id .....                                       | 110 |
| Grant Roles/Domain Permissions, Internal Transfer ..... | 111 |
| Contacts .....  | 113 |

|                           |     |
|---------------------------|-----|
| Create a contact .....    | 113 |
| Modify a contact .....    | 117 |
| Change an address .....   | 120 |
| Change an owner .....     | 122 |
| .asia Contacts .....      | 126 |
| Nameservers .....         | 128 |
| Create a nameserver ..... | 128 |
| Modify a nameserver ..... | 131 |
| Other .....               | 133 |
| Support .....             | 133 |

# Requests

## General Instructions

All requests do follow the same scheme:

- each key:value pair is unique in application.
- each key:value pair is one line finished with carriage return
- each key is delimited by a colon ":" from the value

You have to send the request as [signed email](#) to the Joker.com mail gateway address. This address is disclosed once you signed up as a reseller of Joker.com.

Each email uses a simple, special format, which is described under the different request-types.

For security reasons you have to pgp-sign each mail you send to the mail-gateway, so you need a pgp-installation on your machine. Unsigned or invalid mails will be ignored.

Emails without a valid subject (request-type) will produce an error. In this case you will receive an error message as response.

**Valid requests are normally processed in realtime. Under certain circumstances (Registry-Downtimes, System maintenance, etc.) it is possible, that requests have to wait for processing. It is highly recommended to ask our support before you repeat such requests.**

The descriptions for the requests do all follow the same scheme:

Topic 'introduction' - a short introduction of the request, what is the request for.

Topic 'request fields'

- which fields are required or allowed for a request
- which character are allowed for a request field (the valid character sets are described with PERL-REGULAR-EXPRESSIONS)
- one or more examples for a valid request

# Requests

Keywords: instructions introduction requests

Last update: 2012-10-11 10:29

# Requests

## List of currently working requests

Here you will find the list of the currently working requests. There are 2 types of status for each request.

- available
- not yet implemented

All requests marked with "not yet implemented" will be available during the next weeks.

| target  | request type       | status    |
|---------|--------------------|-----------|
| com/net | support            | available |
|         | create order       | available |
|         | change server      | available |
|         | change address     | available |
|         | transfer domain    | available |
|         | renew domain       | available |
|         | delete domain      | available |
|         | modify domain      | available |
|         | create contact     | available |
|         | modify contact     | available |
|         | create name/server | available |
|         | modify name/server | available |
|         | list domains       | available |
|         | lock domain        | available |
|         | unlock domain      | available |
| org     | support            | available |
|         | create org/order   | available |

# Requests

|                        |        |
|------------------------|--------|
| change org owner       | enable |
| change org address     | enable |
| transfer org domain    | enable |
| renew org domain       | enable |
| delete org domain      | enable |
| modify org domain      | enable |
| create org contact     | enable |
| modify org contact     | enable |
| create org nameserver  | enable |
| modify org nameserver  | enable |
| list domains           | enable |
| lock domain            | enable |
| unlock domain          | enable |
| get sub-id             | enable |
| support                | enable |
| create info order      | enable |
| change info owner      | enable |
| change info address    | enable |
| transfer info domain   | enable |
| renew info domain      | enable |
| delete info domain     | enable |
| modify info domain     | enable |
| create info contact    | enable |
| modify info contact    | enable |
| create info nameserver | enable |

info

# Requests

|    |                       |        |
|----|-----------------------|--------|
|    | modify dns nameserver | enable |
|    | list domains          | enable |
|    | lock domain           | enable |
|    | unlock domain         | enable |
|    | get sub-id            | enable |
| de | support               | enable |
|    | create dns order      | enable |
|    | change dns owner      | enable |
|    | change dns address    | enable |
|    | transfer dns domain   | enable |
|    | renew dns domain      | enable |
|    | delete dns domain     | enable |
|    | modify dns domain     | enable |
|    | create dns contract   | enable |
|    | modify dns contract   | enable |
|    | create dns nameserver | enable |
|    | modify dns nameserver | enable |
|    | list domains          | enable |
|    | lock domain           | enable |
|    | unlock domain         | enable |
|    | get sub-id            | enable |
| de | support               | enable |
|    | create dns order      | enable |
|    | change dns owner      | enable |
|    | change dns address    | enable |

# Requests

|                       |           |
|-----------------------|-----------|
| transfer de-domain    | available |
| renew de-domain       | available |
| delete de-domain      | available |
| modify de-domain      | available |
| create de-contact     | available |
| modify de-contact     | available |
| create de-maintenance | available |
| modify de-maintenance | available |
| list domains          | available |
| lock domain           | available |
| unlock domain         | available |
| support               | available |
| create eu-order       | available |
| change eu-contact     | available |
| change eu-address     | available |
| transfer eu-domain    | available |
| renew eu-domain       | available |
| delete eu-domain      | available |
| modify eu-domain      | available |
| create eu-contact     | available |
| modify eu-contact     | available |
| create eu-maintenance | available |
| modify eu-maintenance | available |
| list domains          | available |
| lock domain           | available |



# Requests

|                  |                     |        |
|------------------|---------------------|--------|
| en               | unlock domain       | enable |
|                  | get sub-id          | enable |
|                  | support             | enable |
|                  | create cn-order     | enable |
|                  | change cn-owner     | enable |
|                  | change cn-address   | enable |
|                  | transfer cn-domain  | enable |
|                  | renew cn-domain     | enable |
|                  | delete cn-domain    | enable |
|                  | modify cn-domain    | enable |
|                  | create cn-contact   | enable |
|                  | modify cn-contact   | enable |
|                  | create cn-namserver | enable |
|                  | modify cn-namserver | enable |
|                  | list domains        | enable |
| us               | lock domain         | enable |
|                  | unlock domain       | enable |
|                  | get sub-id          | enable |
|                  | support             | enable |
|                  | create us-order     | enable |
|                  | change us-owner     | enable |
|                  | change us-address   | enable |
|                  | transfer us-domain  | enable |
| renew us-domain  | enable              |        |
| delete us-domain | enable              |        |

# Requests

|    |                       |        |
|----|-----------------------|--------|
|    | modify via domain     | enable |
|    | create via contact    | enable |
|    | modify via contact    | enable |
|    | create via nameserver | enable |
|    | modify via nameserver | enable |
|    | list domains          | enable |
|    | lock domain           | enable |
|    | unlock domain         | enable |
|    | get sub-id            | enable |
| me | support               | enable |
|    | create me order       | enable |
|    | change me name        | enable |
|    | change me address     | enable |
|    | transfer me domain    | enable |
|    | renew me domain       | enable |
|    | delete me domain      | enable |
|    | modify me domain      | enable |
|    | create me contact     | enable |
|    | modify me contact     | enable |
|    | create me nameserver  | enable |
|    | modify me nameserver  | enable |
|    | list domains          | enable |
|    | lock domain           | enable |
|    | unlock domain         | enable |
|    | get sub-id            | enable |

# Requests

|                     |                       |         |        |
|---------------------|-----------------------|---------|--------|
| .asa                | support               | enable  |        |
|                     | create asa-order      | enable  |        |
|                     | change asa-order      | enable  |        |
|                     | change asa-address    | enable  |        |
|                     | transfer asa-domain   | enable  |        |
|                     | renew asa-domain      | enable  |        |
|                     | delete asa-domain     | enable  |        |
|                     | modify asa-domain     | enable  |        |
|                     | create asa-contact    | enable  |        |
|                     | modify asa-contact    | enable  |        |
|                     | create asa-nameserver | enable  |        |
|                     | modify asa-nameserver | enable  |        |
|                     | list domains          | enable  |        |
|                     | lock domain           | enable  |        |
|                     | unlock domain         | enable  |        |
|                     | get sub-id            | enable  |        |
|                     | .mbi                  | support | enable |
| create mbi-order    |                       | enable  |        |
| change mbi-order    |                       | enable  |        |
| change mbi-address  |                       | enable  |        |
| transfer mbi-domain |                       | enable  |        |
| renew mbi-domain    |                       | enable  |        |
| delete mbi-domain   |                       | enable  |        |
| modify mbi-domain   |                       | enable  |        |
| create mbi-contact  |                       | enable  |        |
|                     |                       |         |        |
|                     |                       |         |        |

# Requests

|                   |                        |                   |
|-------------------|------------------------|-------------------|
|                   | modify nslc-contact    | enable            |
|                   | create nslc-connection | enable            |
|                   | modify nslc-connection | enable            |
|                   | list domains           | enable            |
|                   | lock domain            | enable            |
|                   | unlock domain          | enable            |
|                   | get sub-id             | enable            |
| name              | support                | enable            |
|                   | create name-order      | enable            |
|                   | change name-center     | enable            |
|                   | change name-address    | enable            |
|                   | transfer name-domain   | enable            |
|                   | renew name-domain      | enable            |
|                   | delete name-domain     | enable            |
|                   | modify name-domain     | enable            |
|                   | create name-contact    | enable            |
|                   | modify name-contact    | enable            |
|                   | create name-connection | enable            |
|                   | modify name-connection | enable            |
|                   | list domains           | enable            |
|                   | lock domain            | enable            |
|                   | unlock domain          | enable            |
|                   | get sub-id             | enable            |
|                   | nameservice/forwarding | create dns-config |
| delete dns-config |                        | enable            |

# Requests

|  |             |        |
|--|-------------|--------|
|  | test-config | enable |
|--|-------------|--------|

Keywords: request requests, summary, email-gw, email-gateway

Last update: 2008-08-14 11:31

# Requests

## What is a macro?

A macro is used within the definition of a request.

A macro starts with an @.

**Example:** @start or @end or @file

Every time you find a macro, please check the definition of this macro for further information.

Keywords: macro definition

Last update: 2007-04-02 15:20

# Macros

## E-mail Address

**@mail**  
This means an email address in the following format:  
Valid values (containing only):  
foo@bar.com  
foo@bar.com#1  
foo@bar.com#12

**Invalid values:**  
Here: Name: chow@foo.com,  
Name@foo.com (Name:Name)

**Valid values:** (only enter bar, bar on only):  
foo@bar.com

**Invalid values:**  
Here: Name: chow@foo.com,  
Name@foo.com (Name:Name)

foo@bar.com#12

Keywords: email address

Last update: 2011-08-11 15:34

# Macros

## .com/.net Contacts

**new-handle** (explicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created and we will add a numerical suffix to the email address that starts with "0" and increases by "1" for every existing contact with such an emailaddress in the JOKER-DATABASE.

**ATTENTION:**

The name of the request field depends on the contact. If you want to create a contact for the owner-contact, you have to replace the "-" at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "-" at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "-" at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "-" at the beginning of the fieldname with "billing-contact".

| request field | used values           | required               |
|---------------|-----------------------|------------------------|
| *idnumber     | [1-9]                 | yes                    |
| *name         | {JOKER+HQ}@{C}        | yes, if individual = Y |
| *firstname    | {JOKER+HQ}@{C}        | yes, if individual = Y |
| *title        | {JOKER+HQ}@{C}        | no                     |
| *organization | {JOKER+HQ}@{C}        | yes, if individual = N |
| *address-1    | {JOKER+HQ}@{C}        | yes                    |
| *address-2    | {JOKER+HQ}@{C}        | no                     |
| *postalcode   | {JOKER+HQ}@{C}        | yes                    |
| *city         | {JOKER+HQ}@{C}        | yes                    |
| *state        | {JOKER+HQ}@{C}        | no                     |
| *country      |                       | yes                    |
| *email        | <a href="#">@cont</a> | yes                    |
| *phone        | {JOKER+HQ}@{C}        | yes                    |
| *fax          | {JOKER+HQ}@{C}        | no                     |

**An existing contact** (@cont or @same-as) (cont.net only)

This means an existing contact handle in the JOKER-DATABASE.

**Example:**

```
owner-contact-handle-001@cont.com
admin-contact-handle-001@cont.com
tech-contact-handle-001@cont.com
billing-contact-handle-001@cont.com
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle-same-as-owner-contact
tech-contact-handle-same-as-admin-contact
billing-contact-handle-same-as-tech-contact
```

The @same-as macro always replaces the value for the specified contact handle with the email address of the makrotaget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for (cont.net) requests, contact handles for (jok) contacts are not allowed. If you are referencing to a shortcut the CONTACTNAME, you will get an error.



# Macros

Last update: 2007-04-17 22:05

# Macros

## .com Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CCOM-<number>.

e.g. CCOM-176269.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname** and **lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| request-field   | valid values      | required  |
|-----------------|-------------------|---|
| ".."-individual | [YN]              | yes   |
| ".."-lname      | [\x20-\x7e]{0,80} | no, if name is given                            |
| ".."-fname      | [\x20-\x7e]{0,80} | no, if name is given                            |
| ".."-name       | [\x20-\x7e]{0,80} | yes, if fname <b>and/or</b> lname are not given |
| ".."-title      | [\x20-\x7e]{0,80} | no  |

# Macros

|                   |                          |                        |
|-------------------|--------------------------|------------------------|
| ".."-organization | [\x20-\x7e]{0,80}        | yes, if individual = N |
| ".."-address-1    | [\x20-\x7e]{1,80}        | yes                    |
| ".."-address-2    | [\x20-\x7e]{0,80}        | no                     |
| ".."-address-3    | [\x20-\x7e]{0,80}        | no                     |
| ".."-postal-code  | [\x20-\x7e]{1,50}        | yes                    |
| ".."-city         | [\x20-\x7e]{1,80}        | yes                    |
| ".."-state        | [\x20-\x7e]{0,80}        | no                     |
| ".."-country      | <a href="#">@country</a> | yes                    |
| ".."-email        | <a href="#">@email</a>   | yes                    |
| ".."-phone        | [[\x20-\x7e]{1,50}       | yes                    |
| ".."-fax          | [[\x20-\x7e]{0,50}       | no                     |

**An existing contact** ([@comcont](#) or [@same-as](#)) (.com only)

This means an existing contact handle in the JOKER-DATABASE.

## Examples:

```
owner-contact-handle:CCOM-176269
admin-contact-handle:CCOM-176229
tech-contact-handle:CCOM-176269
billing-contact-handle:CCOM-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .com-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @comcont @same-as admin tech billing

Last update: 2015-11-09 17:47

# Macros

## .net Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CNET-<number>, e.g. CNET-176269.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| request-field     | valid values      | required  |
|-------------------|-------------------|---|
| ".."-individual   | [YN]              | yes   |
| ".."-lname        | [\x20-\x7e]{0,80} | no, if name is given                            |
| ".."-fname        | [\x20-\x7e]{0,80} | no, if name is given                            |
| ".."-name         | [\x20-\x7e]{0,80} | yes, if fname <b>and/or</b> lname are not given |
| ".."-title        | [\x20-\x7e]{0,80} | no  |
| ".."-organization | [\x20-\x7e]{0,80} | yes, if individual = N                          |
| ".."-address-1    | [\x20-\x7e]{1,80} | yes   |
| ".."-address-2    | [\x20-\x7e]{0,80} | no  |
| ".."-address-3    | [\x20-\x7e]{0,80} | no  |
| ".."-postal-code  | [\x20-\x7e]{1,50} | yes   |

# Macros

|              |                          |     |
|--------------|--------------------------|-----|
| ".."-city    | [\x20-\x7e]{1,80}        | yes |
| ".."-state   | [\x20-\x7e]{0,80}        | no  |
| ".."-country | <a href="#">@country</a> | yes |
| ".."-email   | <a href="#">@email</a>   | yes |
| ".."-phone   | [[\x20-\x7e]{1,50}       | yes |
| ".."-fax     | [[\x20-\x7e]{0,50}       | no  |

**An existing contact** ([@netcont](#) or [@same-as](#)) (.net only)

This means an existing contact handle in the JOKER-DATABASE.

## Examples:

```
owner-contact-handle:CNET-176269
admin-contact-handle:CNET-176229
tech-contact-handle:CNET-176269
billing-contact-handle:CNET-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .net-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle [@netcont](#) [@same-as](#) admin tech billing

Last update: 2015-11-09 17:48

# Macros

## .org Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CORG-<number>, e.g. CORG-176269.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname** and **lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| request-field     | valid values      | required  |
|-------------------|-------------------|---|
| ".."-individual   | [YN]              | yes   |
| ".."-lname        | [\x20-\x7e]{0,80} | no, if name is given                            |
| ".."-fname        | [\x20-\x7e]{0,80} | no, if name is given                            |
| ".."-name         | [\x20-\x7e]{0,80} | yes, if fname <b>and/or</b> lname are not given |
| ".."-title        | [\x20-\x7e]{0,80} | no  |
| ".."-organization | [\x20-\x7e]{0,80} | yes, if individual = N                          |
| ".."-address-1    | [\x20-\x7e]{1,80} | yes   |
| ".."-address-2    | [\x20-\x7e]{0,80} | no  |
| ".."-address-3    | [\x20-\x7e]{0,80} | no  |
| ".."-postal-code  | [\x20-\x7e]{1,50} | yes   |

# Macros

|              |                          |     |
|--------------|--------------------------|-----|
| ".."-city    | [\x20-\x7e]{1,80}        | yes |
| ".."-state   | [\x20-\x7e]{0,80}        | no  |
| ".."-country | <a href="#">@country</a> | yes |
| ".."-email   | <a href="#">@email</a>   | yes |
| ".."-phone   | [[\x20-\x7e]{1,50}       | yes |
| ".."-fax     | [[\x20-\x7e]{0,50}       | no  |

An existing contact (**@orgcont** or **@same-as**) (.org only)

This means an existing contact handle in the JOKER-DATABASE.

## Examples:

```
owner-contact-handle:CORG-176269
admin-contact-handle:CORG-176229
tech-contact-handle:CORG-176269
billing-contact-handle:CORG-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .org-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @orgcont @same-as admin tech billing

Last update: 2015-11-09 17:49

# Macros

## .info Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format C<number>-LRMS, e.g. C176269-LRMS.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| request-field     | valid values      | required  |
|-------------------|-------------------|---|
| ".."-individual   | [YN]              | yes   |
| ".."-lname        | [\x20-\x7e]{0,80} | no, if name is given                            |
| ".."-fname        | [\x20-\x7e]{0,80} | no, if name is given                            |
| ".."-name         | [\x20-\x7e]{0,80} | yes, if fname <b>and/or</b> lname are not given |
| ".."-title        | [\x20-\x7e]{0,80} | no  |
| ".."-organization | [\x20-\x7e]{0,80} | yes, if individual = N                          |
| ".."-address-1    | [\x20-\x7e]{1,80} | yes   |
| ".."-address-2    | [\x20-\x7e]{0,80} | no  |
| ".."-address-3    | [\x20-\x7e]{0,80} | no  |
| ".."-postal-code  | [\x20-\x7e]{1,50} | yes   |
| ".."-city         | [\x20-\x7e]{1,80} | yes   |
| ".."-state        | [\x20-\x7e]{0,80} | no  |



# Macros

|              |                          |     |
|--------------|--------------------------|-----|
| ".."-country | <a href="#">@country</a> | yes |
| ".."-email   | <a href="#">@email</a>   | yes |
| ".."-phone   | [[\x20-\x7e]{1,50}       | yes |
| ".."-fax     | [[\x20-\x7e]{0,50}       | no  |

## An existing contact (@infocont or @same-as) (.info only)

This means an existing contact handle in the JOKER-DATABASE.

### Examples:

```
owner-contact-handle:C176269-LRMS
admin-contact-handle:CAFI-007
tech-contact-handle:C176269-LRMS
billing-contact-handle:CAFI-008
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .info-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @infocont @same-as admin tech billing

Last update: 2015-11-09 17:49

# Macros

## .biz Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created.

### ATTENTION

According to the rules of NEULEVEL, the fieldlength for most of the requestfields are limited to 30 characters. Please check very carefully the definitions of the request fields.

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

Please, keep in mind, that if you are using the concatenation of **fname** and **lname**, you have to care that the sum of both fields should not be longer than 30 characters.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

|               |              |          |
|---------------|--------------|----------|
| request-field | valid values | required |
|---------------|--------------|----------|

# Macros

|                   |                          |   |
|-------------------|--------------------------|---|
| ".."-individual   | [YN]                     | yes   |
| ".."-lname        | [\x20-\x7e]{0,30}        | no, if name is given                            |
| ".."-fname        | [\x20-\x7e]{0,30}        | no, if name is given                            |
| ".."-name         | [\x20-\x7e]{0,30}        | yes, if fname <b>and/or</b> lname are not given |
| ".."-title        | [\x20-\x7e]{0,30}        | no  |
| ".."-organization | [\x20-\x7e]{0,30}        | yes, if individual = N                          |
| ".."-address-1    | [\x20-\x7e]{1,30}        | yes   |
| ".."-address-2    | [\x20-\x7e]{0,30}        | no  |
| ".."-address-3    | [\x20-\x7e]{0,30}        | no  |
| ".."-postal-code  | [\x20-\x7e]{1,10}        | yes   |
| ".."-city         | [\x20-\x7e]{1,30}        | yes   |
| ".."-state        | [\x20-\x7e]{0,30}        | no  |
| ".."-country      | <a href="#">@country</a> | yes   |
| ".."-email        | <a href="#">@email</a>   | yes   |
| ".."-phone        | [[\x20-\x7e]{1,17}       | yes   |
| ".."-fax          | [[\x20-\x7e]{0,17}       | no  |

## An existing contact (@bizcont or @same-as) (.biz only)

This means an existing contact handle in the JOKER-DATABASE.

### Examples:

owner-contact-handle: CNEU-12345

admin-contact-handle: CNEU-12345

tech-contact-handle: CNEU-12345

billing-contact-handle: CNEU-12345

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

# Macros

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .biz-requests the contact handles for (.com/.net/.org/.info)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Note that for .biz-requests the contacthandles for (.info)-contacts are not allowed. If you referencing to a shortcut like C176269-LRMS, you will get an error.

Keywords: new-handle @bizcont @same-as admin tech billing

Last update: 2015-11-09 17:51

# Macros

## .mobi Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COMO-<number>, e.g. COMO-176269.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

# Macros

| request-field     | valid values             | required  |
|-------------------|--------------------------|---|
| ".."-individual   | [YN]                     | yes   |
| ".."-lname        | [\x20-\x7e]{0,80}        | no, if name is given                            |
| ".."-fname        | [\x20-\x7e]{0,80}        | no, if name is given                            |
| ".."-name         | [\x20-\x7e]{0,80}        | yes, if fname <b>and/or</b> lname are not given |
| ".."-title        | [\x20-\x7e]{0,80}        | no  |
| ".."-organization | [\x20-\x7e]{0,80}        | yes, if individual = N                          |
| ".."-address-1    | [\x20-\x7e]{1,80}        | yes   |
| ".."-address-2    | [\x20-\x7e]{0,80}        | no  |
| ".."-address-3    | [\x20-\x7e]{0,80}        | no  |
| ".."-postal-code  | [\x20-\x7e]{1,50}        | yes   |
| ".."-city         | [\x20-\x7e]{1,80}        | yes   |
| ".."-state        | [\x20-\x7e]{0,80}        | no  |
| ".."-country      | <a href="#">@country</a> | yes   |
| ".."-email        | <a href="#">@email</a>   | yes   |
| ".."-phone        | [[\x20-\x7e]{1,50}       | yes   |
| ".."-fax          | [[\x20-\x7e]{0,50}       | no  |

**An existing contact** ([@mobicont](#) or [@same-as](#)) (.mobi only)

This means an existing contact handle in the JOKER-DATABASE.

## Examples:

```
owner-contact-handle:COMO-176269
admin-contact-handle:COMO-176229
tech-contact-handle:COMO-176269
billing-contact-handle:COMO-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

# Macros

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .mobi-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @mobicont @same-as admin tech billing owner

Last update: 2015-11-09 17:50

# Macros

## .name Contacts

**new-handle** (explicit creation of a new contact)

This means the addition of a new contact. If a contact with the provided email address exists in the JOKER\_CONTACTS table, a new contact will be created. The reference for the created handle is following the format CNM-*countdown*, e.g. CNM-17628.

### ATTENTION

The name of the request field depends on the contact. If you want to create a contact for the owner-contact, you have to replace the "." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory. If you do not provide the **frame** and **frames**. You have to provide the request field **name**. If **frame** and **frames** are not found. This is very important for the whole output. Everywhere a field **person** is shown. If you are using the request field **name**, the whole is showing the value for **name**, regardless the content of the request fields **frame** and **frames**. If you do not provide the request field **name** but you are providing the request fields **frame** and **frames**, the whole is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory. It is simply the 3rd line of the address.

| Request Field | Def. Format  | Output                                   |
|---------------|--------------|--|
| contactname   | %s           | no                                       |
| name          | 000-00000000 | no, if name is given                     |
| name          | 000-00000000 | no, if name is given                     |
| name          | 000-00000000 | no, if frame and/or frames are not given |
| name          | 000-00000000 | no                                       |
| organization  | 000-00000000 | no, if organization is                   |
| address-1     | 000-00000000 | no                                       |
| address-2     | 000-00000000 | no                                       |
| address-3     | 000-00000000 | no                                       |
| streetname    | 000-00000000 | no                                       |
| city          | 000-00000000 | no                                       |
| state         | 000-00000000 | no                                       |



# Macros

|         |         |         |
|---------|---------|---------|
| OWNER   | OWNER   | OWNER   |
| ADMIN   | ADMIN   | ADMIN   |
| TECH    | TECH    | TECH    |
| BILLING | BILLING | BILLING |

An existing contact (@namecont or @same-as) (comma only)

This means an existing contact handle in the JOKER DATABASE.

#### Example:

```
owner-contact-handle-CHAMA-171228  
admin-contact-handle-CHAMA-171228  
tech-contact-handle-CHAMA-171228  
billing-contact-handle-CHAMA-171228
```

In case you have entered a non-existing contact handle, the system will send you an email.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The @same-as markers always replace the value for the specified contact handle with the email address of the macrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for same requests the contact handles for (user:net) contacts are not allowed. If you are referencing to a shortcut like here@joker.net, you will get an error.

Keywords: new-handle @namecont @same-as admin tech billing owner

Last update: 2007-06-21 11:11

# Macros

## .us Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COUS-<number>, e.g. COUS-176269.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| request-field   | valid values | required |
|-----------------|--------------|----------|
| ".."-individual | [YN]         | yes      |

# Macros

|                   |                          |   |
|-------------------|--------------------------|---|
| ".."-lname        | [\x20-\x7e]{0,80}        | no, if name is given                            |
| ".."-fname        | [\x20-\x7e]{0,80}        | no, if name is given                            |
| ".."-name         | [\x20-\x7e]{0,80}        | yes, if fname <b>and/or</b> lname are not given |
| ".."-title        | [\x20-\x7e]{0,80}        | no  |
| ".."-organization | [\x20-\x7e]{0,80}        | yes, if individual = N                          |
| ".."-address-1    | [\x20-\x7e]{1,80}        | yes   |
| ".."-address-2    | [\x20-\x7e]{0,80}        | no  |
| ".."-address-3    | [\x20-\x7e]{0,80}        | no  |
| ".."-postal-code  | [\x20-\x7e]{1,50}        | yes   |
| ".."-city         | [\x20-\x7e]{1,80}        | yes   |
| ".."-state        | [\x20-\x7e]{0,80}        | no  |
| ".."-country      | <a href="#">@country</a> | yes   |
| ".."-email        | <a href="#">@email</a>   | yes   |
| ".."-phone        | [[\x20-\x7e]{1,50}       | yes   |
| ".."-fax          | [[\x20-\x7e]{0,50}       | no  |

**An existing contact (@uscont or @same-as) (.us only)**

This means an existing contact handle in the JOKER-DATABASE.

## Examples:

```
owner-contact-handle:COUS-176269
admin-contact-handle:COUS-176229
tech-contact-handle:COUS-176269
billing-contact-handle:COUS-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

# Macros

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .us-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @uscont @same-as admin tech billing owner

Last update: 2015-11-09 17:51

# Macros

## .de Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CODE-<number>, e.g. CODE-176269.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| request-field   | valid values      | required             |
|-----------------|-------------------|----------------------|
| ".."-individual | [YN]              | yes                  |
| ".."-lname      | [\x20-\x7e]{0,80} | no, if name is given |
| ".."-fname      | [\x20-\x7e]{0,80} | no, if name is given |

## Macros

|                   |                          |   |
|-------------------|--------------------------|---|
| ".."-name         | [\x20-\x7e]{0,80}        | yes, if fname <b>and/or</b> lname are not given |
| ".."-title        | [\x20-\x7e]{0,80}        | no  |
| ".."-organization | [\x20-\x7e]{0,80}        | yes, if individual = N                          |
| ".."-address-1    | [\x20-\x7e]{1,80}        | yes   |
| ".."-address-2    | [\x20-\x7e]{0,80}        | no  |
| ".."-address-3    | [\x20-\x7e]{0,80}        | no  |
| ".."-postal-code  | [\x20-\x7e]{1,50}        | yes   |
| ".."-city         | [\x20-\x7e]{1,80}        | yes   |
| ".."-state        | [\x20-\x7e]{0,80}        | no  |
| ".."-country      | <a href="#">@country</a> | yes   |
| ".."-email        | <a href="#">@email</a>   | yes   |
| ".."-phone        | [[\x20-\x7e]{1,50}       | yes   |
| ".."-fax          | [[\x20-\x7e]{0,50}       | yes, but for admin-c and tech-c only            |

### An existing contact (@decont or @same-as) (.de only)

This means an existing contact handle in the JOKER-DATABASE.

### Examples:

owner-contact-handle:CODE-176269

admin-contact-handle:CODE-176229

tech-contact-handle:CODE-176269

billing-contact-handle:CODE-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

# Macros

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .de-requests the contact handles for (.com/.net/.org/.info/.biz/.cn)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @decont @same-as admin tech billing owner

Last update: 2015-11-09 17:50

# Macros

## .cn Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COCN-<number>, e.g. COCN-176269.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| request-field   | valid values | required |
|-----------------|--------------|----------|
| ".."-individual | [YN]         | yes      |



# Macros

|                   |                          |   |
|-------------------|--------------------------|---|
| ".."-lname        | [\x20-\x7e]{0,80}        | no, if name is given                            |
| ".."-fname        | [\x20-\x7e]{0,80}        | no, if name is given                            |
| ".."-name         | [\x20-\x7e]{0,80}        | yes, if fname <b>and/or</b> lname are not given |
| ".."-title        | [\x20-\x7e]{0,80}        | no  |
| ".."-organization | [\x20-\x7e]{0,80}        | yes, if individual = N                          |
| ".."-address-1    | [\x20-\x7e]{1,80}        | yes   |
| ".."-address-2    | [\x20-\x7e]{0,80}        | no  |
| ".."-address-3    | [\x20-\x7e]{0,80}        | no  |
| ".."-postal-code  | [\x20-\x7e]{1,50}        | yes   |
| ".."-city         | [\x20-\x7e]{1,80}        | yes   |
| ".."-state        | [\x20-\x7e]{0,80}        | no  |
| ".."-country      | <a href="#">@country</a> | yes   |
| ".."-email        | <a href="#">@email</a>   | yes   |
| ".."-phone        | [[\x20-\x7e]{1,50}       | yes   |
| ".."-fax          | [[\x20-\x7e]{0,50}       | no  |

## An existing contact (@cncont or @same-as) (.cn only)

This means an existing contact handle in the JOKER-DATABASE.

### Examples:

owner-contact-handle:COCN-176269  
admin-contact-handle:COCN-176229  
tech-contact-handle:COCN-176269  
billing-contact-handle:COCN-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

# Macros

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .cn-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @cncont @same-as admin tech billing owner

Last update: 2015-11-09 17:51

# Macros

## .eu Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format C<number>, e.g. C176269.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| request-field | valid values | required |
|---------------|--------------|----------|
|---------------|--------------|----------|

# Macros

|                   |                          |   |
|-------------------|--------------------------|---|
| ".."-individual   | [YN]                     | yes   |
| ".."-lname        | [\x20-\x7e]{0,80}        | no, if name is given                            |
| ".."-fname        | [\x20-\x7e]{0,80}        | no, if name is given                            |
| ".."-name         | [\x20-\x7e]{0,80}        | yes, if fname <b>and/or</b> lname are not given |
| ".."-title        | [\x20-\x7e]{0,80}        | no  |
| ".."-organization | [\x20-\x7e]{0,80}        | yes, if individual = N                          |
| ".."-address-1    | [\x20-\x7e]{1,80}        | yes   |
| ".."-address-2    | [\x20-\x7e]{0,80}        | no  |
| ".."-address-3    | [\x20-\x7e]{0,80}        | no  |
| ".."-postal-code  | [\x20-\x7e]{1,50}        | yes   |
| ".."-city         | [\x20-\x7e]{1,80}        | yes   |
| ".."-state        | [\x20-\x7e]{0,80}        | no  |
| ".."-country      | <a href="#">@country</a> | yes   |
| ".."-email        | <a href="#">@email</a>   | yes   |
| ".."-phone        | [[\x20-\x7e]{1,50}       | yes   |
| ".."-fax          | [[\x20-\x7e]{0,50}       | no  |

## An existing contact (@uscont or @same-as) (.us only)

This means an existing contact handle in the JOKER-DATABASE.

### Examples:

```
owner-contact-handle:C176269
admin-contact-handle:C176229
tech-contact-handle:C176269
billing-contact-handle:C176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

# Macros

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .eu-requests the contact handles for (.com/.net/.org/.info/.biz/.de/.us)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @eucont @same-as admin tech billing owner

Last update: 2015-11-09 17:52

# Macros

## Valid domain names

**@dom** - a valid domain name under .com/.net

**@orgdom** - a valid domain name under .org

**@infodom** - a valid domain name under .info

**@dedom** - a valid domain name under .de

**@cndom** - a valid domain name under .cn

**@eudom** - a valid domain name under .eu

**@usdom** - a valid domain name under .us

**@fqdn** - a valid domain name under .com/.net/.org/.info/.mobi/.name/.biz/.de/.cn/.eu/.us

Keywords: @dom @orgdom @infodom @dedom @cndom @eudom @usdom @fqdn

Last update: 2007-03-28 15:45

# Macros

## Nameserver

**@ns** - the definition of an existing nameserver

You have to provide a valid nameserver handle. Implicit nameserver creation is not allowed.

### Examples:

ns1.foo.bar.net  
ns2.foo.bar.net

ns3.foo.bar.net

Keywords: @ns nameserver

Last update: 2015-11-09 17:53

# Macros

## Zonefile entries

### @a\_record

[a hostprefix without the domainname]:[IP-Address]

- trailing dots at the hostprefix are deleted
- an "@" will be expanded to the domainname

#### Example1:

a:www:194.233.101.99

#### Example2:

a:@:194.233.101.99

### @mx\_record

[a hostprefix without the domainname]:[priority]:[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" as the value of the hostprefix will be expanded to the domain name

#### Example 1:

mx:www:50:mail.hansnose.net

#### Example 2:

mx:www:90:mail.hansnose.net

#### Example 3:

mx:@:50:mail.hansnose.net

#### Example 4:

mx:@:90:mail.hansnose.net

### @cname\_record

[a hostprefix without the domainname]:[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" for the hostprefix is not supported within a CNAME-Record



# Macros

## Example 1:

cname:www:mail.hansnose.net

## Example 2:

cname:www2:mail.hansnose.net

## @url\_record

[a hostprefix without the domainname]::[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" as the value of the hostprefix will be expanded to the domain name

## Example 1:

url:www:http://some.redirector.com

## Example 2:

url:www2:http://some.redirector.com:9002

## Example 3:

url:www3:https://some.redirector.com

## Example 4:

url:www4:https://some.redirector.com:9002

Keywords: @a\_record @mx\_record @cname\_record @url\_record

Last update: 2007-04-20 14:49

# Macros

## IP

@ip - a valid ip address

IP addresses within the following ranges are NOT valid:

Ã,

| IP          | IP              |
|-------------|-----------------|
| 10.0.0.0    | 10.255.255.255  |
| 172.16.0.0  | 172.255.255.255 |
| 192.168.0.0 | 192.168.255.255 |
| 172.31.0.0  | 172.31.255.255  |

Keywords: @ip

Last update: 2007-04-02 16:24

# Macros

## Domain renewal

### @renew

Here you have to provide the domain name and the renewal period or the desired expiration year on one line. You have to separate the domain name and renewal period/expire year with an ":" (ASCII 058). The maximum for the renewal period is 9 years.

### Examples:

```
domain1:blafasel.com:2  
domain2:hansnose.net:3  
domain2:hansnose.info:2005  
domain2:hansnose.biz:2
```

### Attention:

If you are using the expire year and the current expire year of the domain is equal or greater than the provided value for that field, the request will not be processed.

Keywords: @renew

Last update: 2007-03-28 16:12













# Macros

Last update: 2007-04-17 22:12

# Macros

## Language code

@language - one of the following language codes

| Languagecode | Language    |
|--------------|-------------|
| AFR          | Afrikaans   |
| ALB          | Albanian    |
| ARA          | Arabic      |
| ARM          | Armenian    |
| AZE          | Azerbaijani |
| BAQ          | Basque      |
| BUL          | Bulgarian   |
| BUR          | Burmese     |
| CAT          | Catalan     |
| CHI          | Chinese     |
| CZE          | Czech       |
| DAN          | Danish      |
| DUT          | Dutch       |
| ENG          | English     |
| EST          | Estonian    |
| FAO          | Faroese     |
| FIN          | Finnish     |
| FRE          | French      |
| GEO          | Georgian    |
| GER          | German      |
| HEB          | Hebrew      |
| HIN          | Hindi       |
| HUN          | Hungarian   |
| ICE          | Icelandic   |
| ITA          | Italian     |
| JPN          | Japanese    |
| KOR          | Korean      |
| KUR          | Kurdish     |
| LAO          | Lao         |
| LAV          | Latvian     |
| LIT          | Lithuanian  |
| MAC          | Macedonian  |
| MAL          | Malayalm    |
| NEP          | Nepali      |
| NOR          | Norwegian   |
| PER          | Persian     |
| POL          | Polish      |
| POR          | Portuguese  |
| RUM          | Romanian    |
| RUS          | Russian     |
| SAN          | Sanskirt    |
| SCC          | Serbian     |
| SCR          | Croatian    |

## Macros

|     |            |
|-----|------------|
| SLO | Slovak     |
| SLV | Slovenian  |
| SPA | Spanish    |
| SWA | Swahili    |
| SWE | Swedish    |
| SYR | Syriac     |
| TAM | Tamil      |
| THA | Thai       |
| TIB | Tibetan    |
| TUR | Turkish    |
| UKR | Ukrainian  |
| URD | Urdu       |
| UZB | Uzbek      |
| VIE | Vietnamese |
| ZHO | Chinese    |

Keywords: @language language code

Last update: 2015-11-09 17:46

# Macros .me Contacts

**new-handle** (explicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COME-number, e.g. COME-174289.

**ATTENTION**

The name of the request field depends on the contact. If you want to create a contact for the owner-contact, you have to replace the "-" at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "-" at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "-" at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "-" at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **firstname**. You have to provide the request field **name**. If **firstname** and **lastname** are not found. This is very important for the whole output. Everytime a field **person** is shown. If you are using the request field **name**, the whole is showing the value for **name**, regardless the content of the request fields **firstname** and **lastname**. If you do not provide the request field **name** but you are providing the request fields **firstname** and **lastname**, the whole is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| request field | request value | response                                       |
|---------------|---------------|--|
| new-handle    | 174289        | OK   |
| name          | COME-174289   | OK, if name is given                           |
| firstname     | COME-174289   | OK, if name is given                           |
| lastname      | COME-174289   | OK, if lastname and/or firstname are not given |
| name          | COME-174289   | OK, if address-3 is given                      |
| address-1     | COME-174289   | OK   |
| address-2     | COME-174289   | OK   |
| address-3     | COME-174289   | OK   |
| city          | COME-174289   | OK   |
| country       | COME-174289   | OK   |
| zipcode       | COME-174289   | OK   |

# Macros

|       |             |       |
|-------|-------------|-------|
| OWNER | CONTACTNAME | EMAIL |
| ADMIN | CONTACTNAME | EMAIL |

An existing contact (@mecont or @same-as (me only))

This means an existing contact handle in the JOKER DATABASE.

**Examples:**

```
owner-contact-handle:COM-176289
admin-contact-handle:COM-176289
tech-contact-handle:COM-176289
billing-contact-handle:COM-176289
```

In case you have entered a non-existing contact handle, the system will send you an error.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The @same-as makes always replace the value for the specified contact handle with the email address of the macrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .me-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like here@joker.com, you will get an error.

Keywords: new-handle @mecont @same-as admin tech billing owner

Last update: 2008-08-14 11:46

# Macros

## Create a dns-configuration

### Introduction

With this request you can create or modify a record in the joker-namenserver.  
You can add A-Records, CNAME-Records, MX-Records, a nameservice-based URI-forwarding and a frame-based URI-forwarding. Modifying the TTL is not possible.  
The format of this request is a little bit different from the other requests. Please check the given examples for how to specify the different console records.

### ATTENTION:

You have to change the nameserver for a domain to the nameserver of joker.com first!

A-Record  
CNAME-Record  
MX-Record  
URI-Record  
Frame-Record

If you would like to use the joker-namenservice, you will have to use all joker-namenserver.  
It is not possible to use the joker-namenservice

● for primary nameservice only

● for secondnameservice only

### All joker-namenserver

● are configured to deny all zone-fetching requests!

● do not query foreign nameserver!

### Request Fields

#### Definition of the request

| Request-Field | Field-Value                          | Request |
|---------------|--------------------------------------|---------|
| DOMAIN        | <a href="#">joker.com</a>            | YES     |
| TYPE          | <a href="#">A</a>                    | NO      |
| VALUE         | <a href="#">192.168.1.1</a>          | NO      |
| MX            | <a href="#">10 mail.joker.com</a>    | NO      |
| TTL           | <a href="#">3600</a>                 | NO      |
| URI           | <a href="#">http://www.joker.com</a> | NO      |
| FRAME         | <a href="#">http://www.joker.com</a> | NO      |

Example 1: create dns-conf (without uri-forwarding and without selected matching)

subject: create dns-conf {your reference id}

domainid: nameserver

A: www-194.22.110.10

# DNS/URL-Forwarding

Amail 194.23.110.19

Amail2 194.23.110.20

A@ 194.23.110.10

MX www.hanroos.net 70 mail.ora.net

MX www.hanroos.net 80 mail2.ora.net

MX @ 70 mail.hanroos.net

MX @ 80 mail2.hanroos.net

CNAME www3.ora.net other.domain.com

**Example 2: create dns-confiq (with wildcard-matching)**

subject: create dns-confiq [your reference id]

domain#2 hanroos.net

Awww 194.23.110.19

A@ 194.23.110.10

A\* 194.23.110.20

**Example 3: create dns-confiq (with dns-based url-forwarding)**

subject: create dns-confiq [your reference id]

domain#2 hanroos.net

Awww 194.23.110.19

A@ 194.23.110.10

URLwww#2 http://www.ora.net/other.domain.com/index.html

(for internet, the url within the browser is changing to the target address)

# DNS/URL-Forwarding

Example 4 create dns.conf (with frame-based forwarding)

```
subject create dns.conf [your reference id]
```

```
domain2 forwarder.net
```

```
A www 194.23.110.10
```

```
A @ 194.23.110.10
```

```
FRAMES www2 http://www.some-other-domain.com/index.html
```

(that means, the url within the browserbar is not changing to the target address)

Keywords: nameserver, records, zone, forwarding

Last update: 2011-08-11 15:37



# DNS/URL-Forwarding

## Delete a dns-configuration

Introduction

With this request you can delete a zonefile at the given nameserver.

Request fields

mailto:subject: delete dns-config [your reference id]

Definition of the request

| parameter | url format  | example   |
|-----------|---|---|
| subject   | mailto:subject: delete dns-config [your reference id] | mailto:subject: delete dns-config [your reference id] |

Example 1: delete dns-config

subject: delete dns-config [your reference id]

domain@domain.net

Keywords: nameserver,dns-config,records, forwarding

Last update: 2011-08-11 15:37

# DNS/URL-Forwarding

## List a dns-configuration

Introduction

With this request you can get a listing of a current records.

Request fields

multiSubject: list dns-config (your reference id) definition of this request

| id | name | value |
|----|------|-------|
|    |      |       |

Example 1: list dns-config

subject: list dns-config (your reference id)

domain: example.com

Keywords: nameserver,dns-config,records, forwarding

Last update: 2011-08-11 15:38

# DNS/URL-Forwarding

## Create an order

### Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
  
- xxx
  
- asia
  
- me

With this request you can register one or more domains.

You have to provide the following information within the request:

- domain name(s),
- owner-contact-handle,
- admin-contact-handle,
- tech-contact-handle,
- billing-contact-handle,
- nameserver information,
- additional services, if required.

You can register up to 501 domains with one request.

If you register more than one domain with a request, all domains registered with this request will have the same contact and nameserver structure.

There are two new requestfields within this request:

- name

# Domains

- address-3

## ATTENTION

Please, refer to the table for the corresponding contact handles.

| TLD  | Contact handle |
|------|----------------|
| com  | CCOM-<number>  |
| net  | CNET-<number>  |
| org  | CORG-<number>  |
| info | C<number>-LRMS |
| biz  | CNEU-<number>  |
| mobi | COMO-<number>  |
| name | CNAM-<number>  |
| us   | COUS-<number>  |
| de   | CODE-<number>  |
| cn   | COCN-<number>  |
| eu   | C<number>      |
| me   | COME-<number>  |
| asia | COAS-<number>  |
| xxx  | CONX-<number>  |

## Request fields

mailsubject: create <tld>-order [your reference id]

Definition of this request

| tld  | request field        |                |                           |
|------|----------------------|----------------|---------------------------|
|      | domains[0..500]      | period         | language[0..500]          |
| com  | [a-z0-9]{1,63}\.com  | ^([1..9]{1})\$ | <a href="#">@language</a> |
| net  | [a-z0-9]{1,63}\.net  | ^([1..9]{1})\$ |                           |
| org  | [a-z0-9]{1,63}\.org  | ^([1..9]{1})\$ |                           |
| info | [a-z0-9]{1,63}\.info | ^([1..9]{1})\$ |                           |
| biz  | [a-z0-9][a-z0-9]{1,6 | ^([1..9]{1})\$ |                           |

# Domains

|          |                                      |                |                       |
|----------|--------------------------------------|----------------|-----------------------|
|          | 1}[a-z0-9]\.biz                      |                |                       |
| mobi     | [a-z0-9]{1,63}\.mobi                 | ^([1..9]{1})\$ |                       |
| name     | [a-z0-9]{1,63}\.name                 | ^([2..9]{1})\$ |                       |
| us       | [a-z0-9]{1,63}\.us                   | ^([2..9]{1})\$ |                       |
| de       | [a-z0-9]{1,63}\.de                   | ^([1..9]{1})\$ |                       |
| cn       | [a-z0-9][a-z0-9]{1,61}[a-z0-9]\.cn   | ^([1..9]{1})\$ |                       |
| eu       | [a-z0-9][a-z0-9]{1,61}[a-z0-9]\.eu   | ^([1..9]{1})\$ |                       |
| me       | [a-z0-9][a-z0-9]{1,61}[a-z0-9]\.me   | ^([1..9]{1})\$ |                       |
| asia     | [a-z0-9][a-z0-9]{1,61}[a-z0-9]\.asia | ^([1..9]{1})\$ |                       |
| xxx      | [a-z0-9][a-z0-9]{1,61}[a-z0-9]\.xxx  | ^([1..9]{1})\$ |                       |
| required | yes                                  | yes            | no (IDN domains only) |

| tld      | owner-contact-handle | admin-contact-handle | tech-contact-handle       | billing-contact-handle |
|----------|----------------------|----------------------|---------------------------|------------------------|
| com      |                      |                      | <a href="#">@comcont</a>  |                        |
| net      |                      |                      | <a href="#">@netcont</a>  |                        |
| org      |                      |                      | <a href="#">@orgcont</a>  |                        |
| info     |                      |                      | <a href="#">@infocont</a> |                        |
| biz      |                      |                      | <a href="#">@decont</a>   |                        |
| mobi     |                      |                      | <a href="#">@mobicont</a> |                        |
| name     |                      |                      | <a href="#">@namecont</a> |                        |
| us       |                      |                      | <a href="#">@uscont</a>   |                        |
| de       |                      |                      | <a href="#">@bizcont</a>  |                        |
| cn       |                      |                      | <a href="#">@cncont</a>   |                        |
| eu       |                      |                      | <a href="#">@eucont</a>   |                        |
| me       |                      |                      | @mecont                   |                        |
| asia     |                      |                      | @asiacon                  |                        |
| required |                      |                      | yes                       |                        |

| tld      | ns1-handle | ns1-handle | ns1-handle | ns1-handle          | ns1-handle | ns1-handle |
|----------|------------|------------|------------|---------------------|------------|------------|
| <tld>    |            |            |            | <a href="#">@ns</a> |            |            |
| required | yes        | yes        |            |                     | no         |            |

# Domains

## .COM order

**Example 1:** create com-order with implicit contact-handle-creation of the owner-contact

subject: create com-order [your reference id]

```
domains0:xn--hans-mller-feb.com
language0:AFR
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

**Example 2:** create com-order with implicit nameserver-creation

subject: create com-order [your reference id]

```
domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

**Example 3:** create com-order with implicit contact-handle-creation of all contacts

# Domains

subject: create com-order [your reference id]

domains0:minus-109.com  
domains1:minus-10a.com  
domains2:minus-10b.com  
domains3:minus-10c.com  
domains4:minus-10d.com  
domains5:minus-10e.com  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**.NET order**

# Domains

**Example 1:** create net-order with implicit contact-handle-creation of the owner-contact

subject: create net-order [your reference id]

```
domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

**Example 2:** create net-order with implicit nameserver-creation

subject: create net-order [your reference id]

```
domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

**Example 3:** create net-order with implicit contact-handle-creation of all contacts

subject: create net-order [your reference id]

```
domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
```



# Domains

domains4:minus-10d.net  
domains5:minus-10e.net  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .ORG order

**Example 1:** create org-order with implicit contact-handle-creation of the owner-contact

subject: create org-order [your reference id]

# Domains

domains0:xn--hans-mller-feb.org  
language0:AFR  
domains1:minus-10a.org  
domains2:minus-10b.org  
domains3:minus-10c.org  
domains4:minus-10d.org  
domains5:minus-10e.org  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CORG-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create org-order with implicit nameserver-creation

subject: create org-order [your reference id]

domains0:minus-109.org  
domains1:minus-10a.org  
domains2:minus-10b.org  
domains3:minus-10c.org  
domains4:minus-10d.org  
domains5:minus-10e.org  
period:2  
owner-contact-handle:CORG-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CORG-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create org-order with implicit contact-handle-creation of all contacts

subject: create org-order [your reference id]

domains0:minus-109.org  
domains1:minus-10a.org  
domains2:minus-10b.org  
domains3:minus-10c.org  
domains4:minus-10d.org  
domains5:minus-10e.org  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose

# Domains

owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .INFO order

**Example 1:** create info-order with implicit contact-handle-creation of the owner-contact

subject: create info-order [your reference id]

domains0:xn--hans-mlller-feb.info  
language0:AFR  
domains1:minus-10a.info  
domains2:minus-10b.info  
domains3:minus-10c.info  
domains4:minus-10d.info  
domains5:minus-10e.info  
period:2

# Domains

owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:C282828-LRMS  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 2:** create info-order with implicit nameserver-creation

subject: create info-order [your reference id]

domains0:minus-109.info  
domains1:minus-10a.info  
domains2:minus-10b.info  
domains3:minus-10c.info  
domains4:minus-10d.info  
domains5:minus-10e.info  
period:2  
owner-contact-handle:C176269-LRMS  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:C176219-LRMS  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## **Example 3:** create info-order with implicit contact-handle-creation of all contacts

subject: create info-order [your reference id]

domains0:minus-109.info  
domains1:minus-10a.info  
domains2:minus-10b.info  
domains3:minus-10c.info  
domains4:minus-10d.info  
domains5:minus-10e.info  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y

# Domains

admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## **.BIZ order**

**Example 1:** create biz-order with implicit contact-handle-creation of the owner-contact

domains0:xn--hans-mller-feb.biz  
language0:AFR  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz  
domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo

# Domains

```
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

## **Example 2:** create biz-order with implicit nameserver-creation

```
subject: create biz-order [your reference id]
```

```
domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-handle:CNEU-123
admin-contact-handle:CNEU-124
tech-contact-handle:CNEU-125
billing-contact-handle:CNEU-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

## **Example 3:** create biz-order with implicit contact-handle-creation of all contacts

```
subject: create biz-order [your reference id]
```

```
domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
```

# Domains

domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .MOBI ORDER

**Example 1:** create mobi-order with implicit contact-handle-creation of the owner-contact

subject: create mobi-order [your reference id]

domains0:xn--hans-mller-feb.mobi  
language0:AFR  
domains1:minus-10a.mobi

# Domains

domains2:minus-10b.mobi  
domains3:minus-10c.mobi  
domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COMO-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create mobi-order with implicit nameserver-creation

subject: create mobi-order [your reference id]

domains0:minus-109.mobi  
domains1:minus-10a.mobi  
domains2:minus-10b.mobi  
domains3:minus-10c.mobi  
domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-handle:COMO-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COMO-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create mobi-order with implicit contact-handle-creation of all contacts

subject: create mobi-order [your reference id]

domains0:minus-109.mobi  
domains1:minus-10a.mobi  
domains2:minus-10b.mobi  
domains3:minus-10c.mobi  
domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey



# Domains

owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .NAME ORDER

**Example 1:** create name-order with implicit contact-handle-creation of the owner-contact

subject: create name-order [your reference id]

domains0:xn--hans-mller-feb.net  
language0:AFR  
domains1:minus-10a.name  
domains2:minus-10b.name  
domains3:minus-10c.name  
domains4:minus-10d.name  
domains5:minus-10e.name  
period:2  
owner-contact-email:gonzo@nose.net

# Domains

owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CNAM-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create name-order with implicit nameserver-creation

subject: create name-order [your reference id]

domains0:minus-109.name  
domains1:minus-10a.name  
domains2:minus-10b.name  
domains3:minus-10c.name  
domains4:minus-10d.name  
domains5:minus-10e.name  
period:2  
owner-contact-handle:CNAM-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CNAM-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create name-order with implicit contact-handle-creation of all contacts

subject: create name-order [your reference id]

domains0:minus-109.name  
domains1:minus-10a.name  
domains2:minus-10b.name  
domains3:minus-10c.name  
domains4:minus-10d.name  
domains5:minus-10e.name  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo

# Domains

admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .US ORDER

**Example 1:** create us-order with implicit contact-handle-creation of the owner-contact

subject: create us-order [your reference id]

domains0:xn--hans-mller-feb.us  
language0:AFR  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact

# Domains

tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COUS-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 2:** create us-order with implicit nameserver-creation

subject: create us-order [your reference id]

domains0:minus-109.us  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-handle:COUS-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COUS-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## **Example 3:** create us-order with implicit contact-handle-creation of all contacts

subject: create us-order [your reference id]

domains0:minus-109.us  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi

# Domains

tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .DE ORDER

**Example 1:** create de-order with implicit contact-handle-creation of the owner-contact

subject: create de-order [your reference id]

domains0:minus-10x.de  
language0:GER  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nase  
owner-contact-address-1:Musterstrasse 11  
owner-contact-postal-code:4711  
owner-contact-city:Musterhausen  
owner-contact-country:DE  
owner-contact-phone:49 13383794 504040  
owner-contact-fax:49 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CODE-1007  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create net-order with implicit nameserver-creation

subject: create de-order [your reference id]

# Domains

domains0:minus-109.de  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-handle:CODE-1007  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CODE-1007  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create net-order with implicit contact-handle-creation of all contacts

subject: create de-order [your reference id]

domains0:minus-109.de  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nase  
owner-contact-address-1:Musterstrasse 11  
owner-contact-postal-code:4711  
owner-contact-city:Musterhausen  
owner-contact-country:DE  
owner-contact-phone:49 13383794 504040  
owner-contact-fax:49 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nase  
admin-contact-address-1:Musterstrasse 11  
admin-contact-postal-code:4711  
admin-contact-city:Musterhausen  
admin-contact-country:DE  
admin-contact-phone:49 13383794 504040  
admin-contact-fax:49 13383794 504040  
tech-contact-email:gonzo@nose.net  
tech-contact-individual:Y  
tech-contact-fname:gonzo  
tech-contact-lname:nase  
tech-contact-address-1:Musterstrasse 11  
tech-contact-postal-code:4711  
tech-contact-city:Musterhausen  
tech-contact-country:DE  
tech-contact-phone:49 13383794 504040  
tech-contact-fax:49 13383794 504040  
billing-contact-email:gonzo@nose.net

# Domains

billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nase  
billing-contact-address-1:Musterstrasse 11  
billing-contact-postal-code:4711  
billing-contact-city:Musterhausen  
billing-contact-country:DE  
billing-contact-phone:49 13383794 504040  
billing-contact-fax:49 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .CN ORDER

**Example 1:** create cn-order with implicit contact-handle-creation of the owner-contact

subject: create cn-order [your reference id]

domains0:xn--hans-mller-feb.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net

# Domains

billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## Example 2: create cn-order using existing cn-handles

subject: create cn-order [your reference id]

domains0:minus-109.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn  
period:2  
owner-contact-handle:COCN-123  
admin-contact-handle:COCN-124  
tech-contact-handle:COCN-125  
billing-contact-handle:COCN-126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## Example 3: create cn-order with backreferences using @same-as

subject: create cn-order [your reference id]

domains0:minus-109.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:same-as-tech-contact  
ns1-domain-name:nsxx1.gonzo.net



# Domains

ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .EU ORDER

**Example 1:** create eu-order with implicit contact-handle-creation of all contacts

subject: create eu-order [your reference id]

domains0:xn--hans-mller-feb.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1

# Domains

ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 2:** create eu-order using existing .eu-handles

subject: create eu-order [your reference id]

domains0:minus-109.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-handle:C123123  
admin-contact-handle:C123124  
tech-contact-handle:C123125  
billing-contact-handle:C123126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create eu-order with backreferences using @same-as

subject: create eu-order [your reference id]

domains0:minus-109.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:same-as-tech-contact  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

Keywords: create, order, registration

Last update: 2015-07-29 12:02

# Domains

## Modify a domain

### Introduction

modify <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
  
- xxx
  
- asia
  
- me

With this request you can modify existing domains. You have to provide the following information within the

# Domains

request:

- the domainname,
- handle(s) you want to change. (handles from the info-system are not valid)

The system will ignore not specified handles, so you have to provide only the handles, you would like to change.

## Changes within the owner-contact

In case of changing the owner-contact-handle, the system checks, if lname and/or fname and/or organization differ from the original owner-contact-handle. If there are differences these changes will be ignored.

## Request fields

mailsubject: modify <tld>-domain [your reference id]

Definition of this request

| request-field        | valid values   |                                     | required |
|----------------------|--|-------------------------------------|----------|
| tld                  | com net org info mobi<br> name us de                   | biz eu                              | yes      |
| sld                  | [a-z0-9-]{1,63}  | [a-z0-9][a-<br>z0-9-]{1,61}[a-z0-9] | yes      |
| owner-contact-handle | Please, refer to the table below for the valid values. |                                     | no       |
| admin-contact-handle |  |                                     | no       |
| tech-contact-handle  |  |                                     | no       |

# Domains

|                        |                     |    |
|------------------------|---------------------|----|
| billing-contact-handle |                     | no |
| ns1-handle             | <a href="#">@ns</a> | no |
| ns2-handle             |                     | no |
| ns3-handle             |                     | no |
| ns4-handle             |                     | no |
| ns5-handle             |                     | no |
| ns6-handle             |                     | no |

| tld  | contact handle            |
|------|---------------------------|
| com  | <a href="#">@comcont</a>  |
| net  | <a href="#">@netcont</a>  |
| org  | <a href="#">@orgcont</a>  |
| info | <a href="#">@infocont</a> |
| biz  | <a href="#">@bizcont</a>  |
| mobi | <a href="#">@mobicont</a> |
| name | <a href="#">@namecont</a> |
| us   | <a href="#">@uscont</a>   |
| de   | <a href="#">@decont</a>   |
| cn   | <a href="#">@cncont</a>   |
| eu   | <a href="#">@eucont</a>   |

## Example 1: modify com-domain

subject: modify domain [your reference id]

sld:gonzo  
tld:com  
admin-contact-handle:gonzo@nose.com#0  
tech-contact-handle:hans@nose.com  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## Example 2: modify net-domain

subject: modify net-domain [your reference id]

sld:gonzo  
tld:net  
admin-contact-handle:CNET-1234  
tech-contact-handle:CNET-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

# Domains

## Example 3: modify org-domain

subject: modify net-domain [your reference id]

sld:gonzo  
tld:org  
admin-contact-handle:CORG-1234  
tech-contact-handle:CORG-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## Example 4: modify info-domain

subject: modify info-domain [your reference id]

sld:gonzo  
tld:info  
admin-contact-handle:C112234-LRMS  
tech-contact-handle:C112244-LRMS  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

OR

modify info-domain (new naming convention for info-handles)

subject: modify info-domain [your reference id]

sld:gonzo  
tld:info  
admin-contact-handle:C112244-LRMS  
tech-contact-handle:CAFI-007  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## Example 5: modify biz-domain

subject: modify biz-domain [your reference id]

sld:gonzo  
tld:biz  
admin-contact-handle:CNEU-11224  
tech-contact-handle:CNEU-112244  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## Example 6: modify mobi-domain

# Domains

subject: modify mobi-domain [your reference id]

sld:gonzo  
tld:mobi  
admin-contact-handle:COMO-1234  
tech-contact-handle:COMO-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 7:** modify name-domain

subject: modify name-domain [your reference id]

sld:gonzo  
tld:name  
admin-contact-handle:CNAM-1234  
tech-contact-handle:CNAM-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 8:** modify us-domain

subject: modify us-domain [your reference id]

sld:gonzo  
tld:us  
admin-contact-handle:COUS-1234  
tech-contact-handle:COUS-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 9:** modify de-domain

subject: modify de-domain [your reference id]

sld:gonzo  
tld:de  
admin-contact-handle:CODE-1234  
tech-contact-handle:CODE-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 10:** modify cn-contact

subject: modify cn-contact [your reference id]

# Domains

handle:COCN-1235  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## **Example 11:** modify eu-domain

subject: modify eu-domain [your reference id]

sld:gonzo  
tld:eu  
admin-contact-handle:C112244  
tech-contact-handle:C112244  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

Keywords: modify-domain, nameserver, contacts

Last update: 2015-07-29 12:02



# Domains

## Renew a domain

Introduction

renew <id>-domain

Valid values for <id>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- ca
- cn

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s)
- the renewalperiod or the desired expirationyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.

If the sum of the expire time and the renewal time is more than 10 years, we will reject your request.

This request is not working for domains, which are located on the old system. For these domains you have to check the documentation of the old system.

If you provide the expire year, this request will be rejected, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew-request is sent twice by mistake.

Request fields

mailto:subject:renew <id>-domain [your reference id]

# Domains

Definition of this request

You have to provide the domain name and the renewal period or the desired expiry year using the format "YYYY" on one line. You have to separate each field with a " " (ASCII 32). The maximum for the renewal period is 9 years.

| Domain Name | Renewal Period | Expiry Year |
|-------------|----------------|-------------|
| example.com | 1              |             |

COM Renewal

**Example 1:** renew 1 domain for 1 year using the field period  
subject: renew com-domain {your reference ID}  
domain@minus-100.com.1

**Example 2:** renew 5 domains for 4 years using the field period  
subject: renew com-domain {your reference ID}  
domain@minus-100.com.4  
domain@minus-110.com.4  
domain@minus-120.com.4  
domain@minus-130.com.4  
domain@minus-140.com.4

**Example 3:** renew 5 domains for different years using the field period  
subject: renew com-domain {your reference ID}  
domain@minus-100.com.1  
domain@minus-110.com.2  
domain@minus-120.com.3  
domain@minus-130.com.4  
domain@minus-140.com.5

**Example 4:** renew 1 domain using the field expiryyear  
subject: renew com-domain {your reference ID}  
domain@minus-100.com.2005

NET Renewal

**Example 1:** renew 1 domain for 1 year using the field period  
subject: renew net-domain {your reference ID}  
domain@minus-100.net.1

**Example 2:** renew 5 domains for 4 years using the field period  
subject: renew net-domain {your reference ID}  
domain@minus-100.net.4  
domain@minus-110.net.4  
domain@minus-120.net.4  
domain@minus-130.net.4  
domain@minus-140.net.4

**Example 3:** renew 5 domains for different years using the field period  
subject: renew net-domain {your reference ID}  
domain@minus-100.net.1  
domain@minus-110.net.2  
domain@minus-120.net.3  
domain@minus-130.net.4  
domain@minus-140.net.5

**Example 4:** renew 1 domain using the field expiryyear  
subject: renew net-domain {your reference ID}  
domain@minus-100.net.2005

ORG Renewal

**Example 1:** renew 1 domain for 1 year using the field period  
subject: renew org-domain {your reference ID}  
domain@minus-100.org.1

**Example 2:** renew 5 domains for 4 years using the field period  
subject: renew org-domain {your reference ID}  
domain@minus-100.org.4  
domain@minus-110.org.4  
domain@minus-120.org.4  
domain@minus-130.org.4  
domain@minus-140.org.4

**Example 3:** renew 5 domains for different years using the field period  
subject: renew org-domain {your reference ID}  
domain@minus-100.org.1  
domain@minus-110.org.2  
domain@minus-120.org.3  
domain@minus-130.org.4  
domain@minus-140.org.5

**Example 4:** renew 1 domain using the field expiryyear  
subject: renew org-domain {your reference ID}  
domain@minus-100.org.2005

INFO Renewal

**Example 1:** renew 1 domain for 1 year using the field period  
subject: renew info-domain {your reference ID}  
domain@minus-100.info.1

**Example 2:** renew 5 domains for 4 years using the field period  
subject: renew info-domain {your reference ID}  
domain@minus-100.info.4  
domain@minus-110.info.4  
domain@minus-120.info.4  
domain@minus-130.info.4  
domain@minus-140.info.4

**Example 3:** renew 5 domains for different years using the field period  
subject: renew info-domain {your reference ID}  
domain@minus-100.info.1  
domain@minus-110.info.2  
domain@minus-120.info.3  
domain@minus-130.info.4  
domain@minus-140.info.5

**Example 4:** renew 1 domain using the field expiryyear  
subject: renew info-domain {your reference ID}  
domain@minus-100.info.2005

# Domains

## BIZ Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew biz-domain [your reference id]  
domainid: minuo-100.biz.1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew biz-domain [your reference id]  
domainid: minuo-100.biz.4  
domainid: minuo-110.biz.4  
domainid: minuo-120.biz.4  
domainid: minuo-130.biz.4  
domainid: minuo-140.biz.4

**Example 3:** renew 5 domains for different years using the field period

subject: renew biz-domain [your reference id]  
domainid: minuo-100.biz.1  
domainid: minuo-110.biz.2  
domainid: minuo-120.biz.3  
domainid: minuo-130.biz.4  
domainid: minuo-140.biz.5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew biz-domain [your reference id]  
domainid: minuo-100.biz.2005

## NAME Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew name-domain [your reference id]  
domainid: minuo-100.name.1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew name-domain [your reference id]  
domainid: minuo-100.name.4  
domainid: minuo-110.name.4  
domainid: minuo-120.name.4  
domainid: minuo-130.name.4  
domainid: minuo-140.name.4

**Example 3:** renew 5 domains for different years using the field period

subject: renew name-domain [your reference id]  
domainid: minuo-100.name.1  
domainid: minuo-110.name.2  
domainid: minuo-120.name.3  
domainid: minuo-130.name.4  
domainid: minuo-140.name.5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew name-domain [your reference id]  
domainid: minuo-100.name.2005

## US Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew us-domain [your reference id]  
domainid: minuo-100.us.1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew us-domain [your reference id]  
domainid: minuo-100.us.4  
domainid: minuo-110.us.4  
domainid: minuo-120.us.4  
domainid: minuo-130.us.4  
domainid: minuo-140.us.4

**Example 3:** renew 5 domains for different years using the field period

subject: renew us-domain [your reference id]  
domainid: minuo-100.us.1  
domainid: minuo-110.us.2  
domainid: minuo-120.us.3  
domainid: minuo-130.us.4  
domainid: minuo-140.us.5

**Example 4:** renew 1 domain using the field expiry year

subject: renew us-domain [your reference id]  
domainid: minuo-100.us.2005

## DE Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew de-domain [your reference id]  
domainid: minuo-100.de.1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew de-domain [your reference id]  
domainid: minuo-100.de.4  
domainid: minuo-110.de.4  
domainid: minuo-120.de.4  
domainid: minuo-130.de.4  
domainid: minuo-140.de.4

**Example 3:** renew 5 domains for different years using the field period

subject: renew de-domain [your reference id]  
domainid: minuo-100.de.1  
domainid: minuo-110.de.2  
domainid: minuo-120.de.3  
domainid: minuo-130.de.4  
domainid: minuo-140.de.5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew de-domain [your reference id]  
domainid: minuo-100.de.2005

## CA Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew ca-domain [your reference id]  
domainid: minuo-100.ca.1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew ca-domain [your reference id]  
domainid: minuo-100.ca.4  
domainid: minuo-110.ca.4  
domainid: minuo-120.ca.4  
domainid: minuo-130.ca.4  
domainid: minuo-140.ca.4

**Example 3:** renew 5 domains for different years using the field period

subject: renew ca-domain [your reference id]  
domainid: minuo-100.ca.1  
domainid: minuo-110.ca.2  
domainid: minuo-120.ca.3  
domainid: minuo-130.ca.4  
domainid: minuo-140.ca.5

**Example 4:** renew 1 domain using the field expiry year

subject: renew ca-domain [your reference id]  
domainid: minuo-100.ca.2005

Keywords: renew, renewal

# Domains

Last update: 2011-08-11 14:18

# Domains

## Transfer a domain

Introduction

Transfer .com domain

Valid values for .com:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- ca
- co

With this request you can transfer a domain from 1 registrar to Joker.com.  
You have to provide the following information within the request:

- the domain name,
- the auth-Id,
- the billing-contact-handle.

You can transfer 1 .com domain with one request.

If you transfer a domain to Joker.com the domain will be renewed for one year.

As you can see, we don't need information about the owner-contact. We will detect this information from the which of the current registrar and we will create the contact-handle for the owner-contact automatically.

You need to provide us with a so-called auth-Id. You have to ask the current registrar for this auth-Id. If you provide an invalid auth-Id, the transfer will be declined by the current registrar.

As you can see, we need the billing-contact-handle. We recommend using a billing-handle with the email-address of your "joker-email". If you use a contact-handle with a different e-mail than your joker e-mail, you can't administer the transferred domain using the webinterface and the person with access to the email, which is shown in the provided billing-handle will have access using the web-interface.

If you don't have a com contact-handle with your "joker-email", you have to create a com-handle using the "create-com-contact" request.



# Domains

domain@mouse-100.org  
auth-id=00000A00

billig-comcast-handels-COEG-1234

**TRANSFER INFO DOMAIN**  
**Example 1:** transfer info-domain  
subject: transfer info-domain [your reference id]  
domain@mouse-100.de  
auth-id=00000A00  
billig-comcast-handels-CFHDS-LRMS

**TRANSFER BIZ DOMAIN**  
**Example 1:** transfer biz-domain  
subject: transfer biz-domain [your reference id]  
domain@mouse-100.biz  
auth-id=00000A00  
billig-comcast-handels-CNEU-123

**TRANSFER NAME DOMAIN**  
**Example 1:** transfer name-domain  
subject: transfer name-domain [your reference id]  
domain@mouse-100.name  
auth-id=00000A00

billig-comcast-handels-CNAM-1234

**TRANSFER US DOMAIN**  
**Example 1:** transfer us-domain  
subject: transfer us-domain [your reference id]  
domain@mouse-100.us  
auth-id=00000A00

billig-comcast-handels-COUS-1234

**TRANSFER DE DOMAIN**  
**Example 1:** transfer de-domain  
subject: transfer de-domain [your reference id]  
domain@mouse-100.de  
auth-id=00000A00  
billig-comcast-handels-CODE-1234

**TRANSFER CN DOMAIN**  
**Example 1:** transfer cn-domain  
subject: transfer cn-domain [your reference id]  
domain@mouse-100.cn  
auth-id=00000A00  
billig-comcast-handels-COCN-1234

Keywords: transfer, auth-id

Last update: 2011-08-11 14:14

# Domains

## Delete a domain

### Introduction

With this request you can delete a domain at joker.com.

You have to provide the following information within the request:

- domain name(s).
- the special flag force.

### ATTENTION

If you delete a domain within the first 72 hours after the registration, the registration fee will be refunded to your account.

If Joker.com receives the delete request more than 72 hours after the registration, you have to provide the flag "force 1", in order to accept that the registration fee will not be refunded to your account. If you do not send the "force 1" in such a case, the request will be rejected.

### Request fields

mailsubject: delete domain [your reference id]

Definition of this request

Please, do not forget to provide the domain name and the force-flag set to 1 if the domain is older 72h.

| id | mailsubject                       | mailto              |
|----|-----------------------------------|---------------------|
| 1  | delete domain [your reference id] | webmaster@joker.com |
| 2  | delete domain [your reference id] | webmaster@joker.com |
| 3  | delete domain [your reference id] | webmaster@joker.com |



# Domains

## DELETE COM DOMAIN

**Example 1:** delete a domain during the first 72 hours after registration  
subject: delete domain [your reference id]

tld:com  
sld:frezel

**Example 2:** delete a domain after the first 72 hours after registration  
subject: delete domain [your reference id]

tld:com  
sld:frezel  
force:1

**Example 3:** delete a domain only for the case that a refund is possible!  
subject: delete domain [your reference id]

tld:com  
sld:frezel  
force:0

Keywords: delete-domain

Last update: 2011-08-11 15:45

# Domains

## List domains

### Introduction

list domains

With this request you can get a list (lexicographically sorted) of all the domains you have currently registered at joker.com. You have to provide the target registry within the request:

cto = cto.net

com = net

net = net

org = org

info = info

biz = biz

mod = mod

name = mod

co = co

co = co

co = co

co = co

### LIMITATIONS

- Only 20,000 domains are listed. If you have more than 20,000 domains under 1 registry at joker.com, you have to track the domain names yourself.
- In case you have more than 20,000 domains at joker.com under 1 registry, the request will not work for you. The listing would be incomplete and it will be missing random domains.
- This request works only with the new joker.com system.

### Request fields

url=subject list domains [your reference id]

Definition of the request:

| Request field | Request value                            | Response |
|---------------|--|----------|
| url           | subject list domains [your reference id] | list     |

### LIST DOMAINS

**Example 1:** list domains for .com-domains  
subject: list domains [your reference id]  
target: com

**Example 2:** list domains for .net-domains  
subject: list domains [your reference id]  
target: net

**Example 3:** list domains for .org-domains  
subject: list domains [your reference id]  
target: org

**Example 4:** list domains for .info-domains  
subject: list domains [your reference id]  
target: info

**Example 5:** list domains for .biz-domains  
subject: list domains [your reference id]  
target: biz

# Domains

Example 6: list domains for .de-domains  
subject: list domains [your reference id]  
target: de

Example 7: list domains for .cn-domains  
subject: list domains [your reference id]  
target: cn

Keywords: list-domains

Last update: 2011-08-11 15:44

# Domains

## Lock a domain

Introduction

Lock domain

With this request you can lock a domain in order to prevent fraudulent transfer attempts. If a domain is locked, each transfer request from a foreign registrar will be declined.

You have to provide the following information within the request:

● domain name

You can lock 1 domain with one request.

Request fields

mailto:subject: lock domain [your reference id]

Definition of this request

| Request field | Request value                   | Request type |
|---------------|---------------------------------|--------------|
| subject       | lock domain [your reference id] | text         |

Example 1: lock a domain

subject: lock domain [your reference id]

ipdn.milvus-100.com

Keywords: lock-domain, protection

Last update: 2011-08-11 15:46

# Domains

## Unlock a domain

Introduction

unlock domain

With this request you can unlock a domain. If you want to transfer a domain to a foreign registrar, the domain has to be unlocked.

You have to provide the following information within the request:

● domain name

You can unlock 1 domain with one request.

Request fields

mailsubject: unlock domain [your reference id]

Definitions of the request

| mailsubject | mailto | recipient |
|-------------|--------|-----------|
|             |        |           |

Example 1: unlock a domain  
subject: unlock domain [your reference id]  
typ:unlock-158.com

Keywords: unlock-domain, protection

Last update: 2011-08-11 15:46

# Domains

## Get Auth-id

### Introduction

With this request you can retrieve the auth-id for a particular domain. That request is needed only for the TLDs: org/info.biz.

You have to provide the following information within the request:

- domain name

You can retrieve the auth-id for 1 domain with one request.

### Request fields

mailto:subject: get-auth-id [your-reference-id]

### Definition of the request

| Field Name | Field Value                     | Field Name | Field Value                     | Field Name | Field Value                     | Field Name | Field Value                     |
|------------|---------------------------------|------------|---------------------------------|------------|---------------------------------|------------|---------------------------------|
| subject    | get-auth-id [your-reference-id] | subject    | get-auth-id [your-reference-id] | subject    | get-auth-id [your-reference-id] | subject    | get-auth-id [your-reference-id] |

Example 1: retrieve the auth-id for a .org-domain  
subject: get-auth-id [your-reference-id]  
http://minius-100.org

Example 2: retrieve the auth-id for a .biz-domain  
subject: get-auth-id [your-reference-id]  
http://minius-100.biz

Example 3: retrieve the auth-id for a .info-domain  
subject: get-auth-id [your-reference-id]  
http://minius-100.info

Keywords: transfer, auth-id

Last update: 2011-08-11 15:46

# Domains

## Grant Roles/Domain Permissions, Internal Transfer

Introduction

With this request you can assign [roles/permissions of domains](#) to other Joker.com users. The special role "creator" is an equivalent to an internal transfer of that domain to another Joker.com user. In this case, the domain is assigned to the receiving account, including all rights and permissions on this domain.

There are two variants to use this functionality. If the user id (Joker.com user account id) is given, and the account id matches the associated email address, the role is applied immediately - there will be no request for confirmation on the receiver's side. In case the user id is not given, but only the email address, the transaction has to be acknowledged by the receiver. For this, he will get an email, containing a link and a key. Either the link has to be clicked, or the key has to be applied using Joker.com (or Transfer). This can also be used for users which do not yet have a

Joker.com account

You have to provide the following parameters:

- domain name (the domain you want to grant somebody else permissions on)
- destination client email (the email address of the user you want to receive permissions)

The following parameters are optional:

- destination client id (ID of Joker.com account - always shown in the upper right on Joker.com, also conforms to "header id" - must match the destination client email)
- desired role (type of permission you want to assign to "client email" - help: "client id" - one of "admin@joker.com", "creator" means "all permissions" and is equivalent to an internal transfer or "assignment" - also see [links](#))

Request fields

mailto:joker@joker.com [your reference id]

Definition of this request

Valid values for client\_email: @joker.com ID

| Parameter Name           | Parameter Value                                    | Required |
|--------------------------|--|----------|
| client_email             | [+40-9]@joker.com                                  | yes      |
| destination-client-email | @email   | yes      |
| destination-client-id    | [0-9]  | no       |
| desired-role             | admin@joker.com (if omitted, default is "creator") | no       |

Example 1: assign "admin" role to user 12345 (demo)

# Domains

subject: plan-internal-transfer (pour référence id)

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

destination-client-id:123456

desired-role:billing

**Example 2:** assign 'creator'-role to user 'example-user@gmail.com' (internal transfer with invitation)

subject: plan-internal-transfer (pour référence id)

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

desired-role:creator

Keywords: grants, roles, contacts, permissions, invitations

Last update: 2011-08-17 09:35



# Domains

## Create a contact

Introduction

create vld-order

VLD values for vld:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- ru

With this request you can create person contacts. You can create 1 contact with one request.

**ATTENTION:**

You will find the request field "individual" within the request definition. If you set it to "Y", you have to provide the request fields "firstname" and "lastname". If you set it to "N", you have to provide information in the request field "organization".

As the value for com shows a field called person, the data for generating this field are the following:

If you provide the field "firstname", the value is always always the value of this field, regardless of "firstname" and "lastname".

If you only provide the field "firstname" and the field "lastname", we will generate the field "person" as the result of the concatenation of "firstname" + " " + "lastname".

The result of "create com-contact" is a reference which is following the format:

- CCOM-number e.g. CCOM-170289 for a com domain.
- CNET-number e.g. CNET-170289 for a net domain.
- CORG-number e.g. CORG-170289 for a org domain.
- Cinfo-number e.g. C170289LRIS for a info domain.
- CBIZ-number e.g. CBIZ-170289 for a biz domain.
- CMobi-number e.g. CMobi-170289 for a mobi domain.
- CNAME-number e.g. CNAME-170289 for a name domain.
- CUS-number e.g. CUS-170289 for a us domain.
- CDE-number e.g. CDE-170289 for a de domain.
- CCN-number e.g. CCN-170289 for a cn domain.
- CRU-number e.g. CRU-170289 for a ru domain.

Request fields

Multiject: create vld-contact [your reference ID]

Definition of this request

# Contacts

ATTENTION

According to the rules of DENIC, you have to provide a telephone number for the admin-c and the tech-c of a .de domain.

| CONTACT ID  | CONTACT INFORMATION |               | CONTACT TYPE   |
|-------------|---------------------|---------------|----------------|
|             | CONTACT NAME        | CONTACT PHONE |                |
| CONTACT 1   |                     |               | CONTACT TYPE 1 |
| CONTACT 2   |                     |               | CONTACT TYPE 1 |
| CONTACT 3   |                     |               | CONTACT TYPE 1 |
| CONTACT 4   |                     |               | CONTACT TYPE 1 |
| CONTACT 5   |                     |               | CONTACT TYPE 1 |
| CONTACT 6   |                     |               | CONTACT TYPE 1 |
| CONTACT 7   |                     |               | CONTACT TYPE 1 |
| CONTACT 8   |                     |               | CONTACT TYPE 1 |
| CONTACT 9   |                     |               | CONTACT TYPE 1 |
| CONTACT 10  |                     |               | CONTACT TYPE 1 |
| CONTACT 11  |                     |               | CONTACT TYPE 1 |
| CONTACT 12  |                     |               | CONTACT TYPE 1 |
| CONTACT 13  |                     |               | CONTACT TYPE 1 |
| CONTACT 14  |                     |               | CONTACT TYPE 1 |
| CONTACT 15  |                     |               | CONTACT TYPE 1 |
| CONTACT 16  |                     |               | CONTACT TYPE 1 |
| CONTACT 17  |                     |               | CONTACT TYPE 1 |
| CONTACT 18  |                     |               | CONTACT TYPE 1 |
| CONTACT 19  |                     |               | CONTACT TYPE 1 |
| CONTACT 20  |                     |               | CONTACT TYPE 1 |
| CONTACT 21  |                     |               | CONTACT TYPE 1 |
| CONTACT 22  |                     |               | CONTACT TYPE 1 |
| CONTACT 23  |                     |               | CONTACT TYPE 1 |
| CONTACT 24  |                     |               | CONTACT TYPE 1 |
| CONTACT 25  |                     |               | CONTACT TYPE 1 |
| CONTACT 26  |                     |               | CONTACT TYPE 1 |
| CONTACT 27  |                     |               | CONTACT TYPE 1 |
| CONTACT 28  |                     |               | CONTACT TYPE 1 |
| CONTACT 29  |                     |               | CONTACT TYPE 1 |
| CONTACT 30  |                     |               | CONTACT TYPE 1 |
| CONTACT 31  |                     |               | CONTACT TYPE 1 |
| CONTACT 32  |                     |               | CONTACT TYPE 1 |
| CONTACT 33  |                     |               | CONTACT TYPE 1 |
| CONTACT 34  |                     |               | CONTACT TYPE 1 |
| CONTACT 35  |                     |               | CONTACT TYPE 1 |
| CONTACT 36  |                     |               | CONTACT TYPE 1 |
| CONTACT 37  |                     |               | CONTACT TYPE 1 |
| CONTACT 38  |                     |               | CONTACT TYPE 1 |
| CONTACT 39  |                     |               | CONTACT TYPE 1 |
| CONTACT 40  |                     |               | CONTACT TYPE 1 |
| CONTACT 41  |                     |               | CONTACT TYPE 1 |
| CONTACT 42  |                     |               | CONTACT TYPE 1 |
| CONTACT 43  |                     |               | CONTACT TYPE 1 |
| CONTACT 44  |                     |               | CONTACT TYPE 1 |
| CONTACT 45  |                     |               | CONTACT TYPE 1 |
| CONTACT 46  |                     |               | CONTACT TYPE 1 |
| CONTACT 47  |                     |               | CONTACT TYPE 1 |
| CONTACT 48  |                     |               | CONTACT TYPE 1 |
| CONTACT 49  |                     |               | CONTACT TYPE 1 |
| CONTACT 50  |                     |               | CONTACT TYPE 1 |
| CONTACT 51  |                     |               | CONTACT TYPE 1 |
| CONTACT 52  |                     |               | CONTACT TYPE 1 |
| CONTACT 53  |                     |               | CONTACT TYPE 1 |
| CONTACT 54  |                     |               | CONTACT TYPE 1 |
| CONTACT 55  |                     |               | CONTACT TYPE 1 |
| CONTACT 56  |                     |               | CONTACT TYPE 1 |
| CONTACT 57  |                     |               | CONTACT TYPE 1 |
| CONTACT 58  |                     |               | CONTACT TYPE 1 |
| CONTACT 59  |                     |               | CONTACT TYPE 1 |
| CONTACT 60  |                     |               | CONTACT TYPE 1 |
| CONTACT 61  |                     |               | CONTACT TYPE 1 |
| CONTACT 62  |                     |               | CONTACT TYPE 1 |
| CONTACT 63  |                     |               | CONTACT TYPE 1 |
| CONTACT 64  |                     |               | CONTACT TYPE 1 |
| CONTACT 65  |                     |               | CONTACT TYPE 1 |
| CONTACT 66  |                     |               | CONTACT TYPE 1 |
| CONTACT 67  |                     |               | CONTACT TYPE 1 |
| CONTACT 68  |                     |               | CONTACT TYPE 1 |
| CONTACT 69  |                     |               | CONTACT TYPE 1 |
| CONTACT 70  |                     |               | CONTACT TYPE 1 |
| CONTACT 71  |                     |               | CONTACT TYPE 1 |
| CONTACT 72  |                     |               | CONTACT TYPE 1 |
| CONTACT 73  |                     |               | CONTACT TYPE 1 |
| CONTACT 74  |                     |               | CONTACT TYPE 1 |
| CONTACT 75  |                     |               | CONTACT TYPE 1 |
| CONTACT 76  |                     |               | CONTACT TYPE 1 |
| CONTACT 77  |                     |               | CONTACT TYPE 1 |
| CONTACT 78  |                     |               | CONTACT TYPE 1 |
| CONTACT 79  |                     |               | CONTACT TYPE 1 |
| CONTACT 80  |                     |               | CONTACT TYPE 1 |
| CONTACT 81  |                     |               | CONTACT TYPE 1 |
| CONTACT 82  |                     |               | CONTACT TYPE 1 |
| CONTACT 83  |                     |               | CONTACT TYPE 1 |
| CONTACT 84  |                     |               | CONTACT TYPE 1 |
| CONTACT 85  |                     |               | CONTACT TYPE 1 |
| CONTACT 86  |                     |               | CONTACT TYPE 1 |
| CONTACT 87  |                     |               | CONTACT TYPE 1 |
| CONTACT 88  |                     |               | CONTACT TYPE 1 |
| CONTACT 89  |                     |               | CONTACT TYPE 1 |
| CONTACT 90  |                     |               | CONTACT TYPE 1 |
| CONTACT 91  |                     |               | CONTACT TYPE 1 |
| CONTACT 92  |                     |               | CONTACT TYPE 1 |
| CONTACT 93  |                     |               | CONTACT TYPE 1 |
| CONTACT 94  |                     |               | CONTACT TYPE 1 |
| CONTACT 95  |                     |               | CONTACT TYPE 1 |
| CONTACT 96  |                     |               | CONTACT TYPE 1 |
| CONTACT 97  |                     |               | CONTACT TYPE 1 |
| CONTACT 98  |                     |               | CONTACT TYPE 1 |
| CONTACT 99  |                     |               | CONTACT TYPE 1 |
| CONTACT 100 |                     |               | CONTACT TYPE 1 |

CREATE COM CONTACT

Example 1: create com-contact (name will be generated from frame and frame)

subject: create com-contact [your reference id]

email: gregor@house.net  
 individual: Y  
 frame: gregor  
 frame: gregor  
 name: gregor  
 address: 7 Normalstr. Meiers  
 address: 2466, 1  
 postal-code: 4711  
 city: meiers  
 country: DE  
 phone: 44 13883794 50040

Example 2: create com-contact (name and frame will be ignored)

subject: create com-contact [your reference id]

email: gregor@house.net  
 individual: Y  
 frame: gregor  
 frame: gregor  
 name: 86 Gerdon Meiers  
 address: 7 Normalstr. Meiers  
 address: 2466, 1  
 postal-code: 4711  
 city: meiers  
 country: DE  
 phone: 44 13883794 50040

CREATE NET CONTACT

Example 1: create net-contact (name will be generated from frame and frame)

subject: create net-contact [your reference id]

email: gregor@house.net  
 individual: Y  
 frame: gregor  
 frame: gregor  
 name: gregor  
 name: 86 Gerdon Meiers  
 address: 7 Normalstr. Meiers  
 address: 2466, 1  
 postal-code: 4711  
 city: meiers  
 country: DE  
 phone: 44 13883794 50040

Example 2: create net-contact (name and frame will be ignored)

subject: create net-contact [your reference id]

email: gregor@house.net  
 individual: Y  
 frame: gregor  
 frame: gregor  
 name: 86 Gerdon Meiers  
 address: 7 Normalstr. Meiers  
 address: 2466, 1  
 postal-code: 4711  
 city: meiers  
 country: DE  
 phone: 44 13883794 50040

CREATE ORG CONTACT

Example 1: create org-contact (name will be generated from frame and frame)

subject: create org-contact [your reference id]

email: gregor@house.org  
 individual: Y  
 frame: gregor  
 frame: gregor  
 name: 86 Gerdon Meiers  
 address: 7 Normalstr. Meiers  
 address: 2466, 1  
 postal-code: 4711

# Contacts

cityname  
country DE  
phone 44 1383754 50600

**Example 2:** create info-contact (frame and frame will be ignored)  
subject: create info-contact [your reference id]

email:gonzo@noaa.org  
individual Y  
frame:gonzo  
frame:gonzo  
name:Mr. Gonzo Nisse  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

## CREATE INFO CONTACT

**Example 1:** create info-contact (frame will be generated from frame and frame)  
subject: create info-contact [your reference id]

email:gonzo@noaa.info  
individual Y  
frame:gonzo  
frame:gonzo  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

**Example 2:** create info-contact (frame and frame will be ignored)  
subject: create info-contact [your reference id]

email:gonzo@noaa.info  
individual Y  
frame:gonzo  
frame:gonzo  
name:Mr. Gonzo Nisse  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

## CREATE BIZ CONTACT

**Example 1:** create biz-contact (frame will be generated from frame and frame)  
subject: create biz-contact [your reference id]

email:gonzo@noaa.biz  
individual Y  
frame:gonzo  
frame:gonzo  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

**Example 2:** create biz-contact (frame and frame will be ignored)  
subject: create biz-contact [your reference id]

email:gonzo@noaa.biz  
individual Y  
frame:gonzo  
frame:gonzo  
name:Mr. Gonzo Nisse  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE

phone:44 1383754 50600

## CREATE NAME CONTACT

**Example 1:** create name-contact (frame will be generated from frame and frame)  
subject: create name-contact [your reference id]

email:gonzo@noaa.net  
individual Y  
frame:gonzo  
frame:gonzo  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

**Example 2:** create name-contact (frame and frame will be ignored)  
subject: create name-contact [your reference id]

email:gonzo@noaa.net  
individual Y  
frame:gonzo  
frame:gonzo  
name:Mr. Gonzo Nisse  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

## CREATE US CONTACT

**Example 1:** create us-contact (frame will be generated from frame and frame)  
subject: create us-contact [your reference id]

email:gonzo@noaa.net  
individual Y  
frame:gonzo  
frame:gonzo  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

**Example 2:** create us-contact (frame and frame will be ignored)  
subject: create us-contact [your reference id]

email:gonzo@noaa.net  
individual Y  
frame:gonzo  
frame:gonzo  
name:Mr. Gonzo Nisse  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE

phone:44 1383754 50600

## CREATE DE CONTACT

**Example 1:** create de-contact (frame will be generated from frame and frame)  
subject: create de-contact [your reference id]

email:gonzo@noaa.net  
individual Y  
frame:gonzo  
frame:gonzo  
address-1:Northstar News 13  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

**Example 2:** create de-contact (frame and frame will be ignored)  
subject: create de-contact [your reference id]

email:gonzo@noaa.net  
individual Y  
frame:gonzo  
frame:gonzo  
name:Mr. Gonzo Nisse  
address-1:Northstar News 13  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

## CREATE CN CONTACT

**Example 1:** create cn-contact (frame will be generated from frame and frame)  
subject: create cn-contact [your reference id]

email:gonzo@noaa.net  
individual Y  
frame:gonzo  
frame:gonzo  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

**Example 2:** create cn-contact (frame and frame will be ignored)  
subject: create cn-contact [your reference id]

email:gonzo@noaa.net  
individual Y  
frame:gonzo  
frame:gonzo  
name:Mr. Gonzo Nisse  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE

phone:44 1383754 50600

## CREATE EU CONTACT

**Example 1:** create eu-contact (frame will be generated from frame and frame)  
subject: create eu-contact [your reference id]

email:gonzo@noaa.net  
individual Y  
frame:gonzo  
frame:gonzo  
address-1:Northstar News  
address-2:App. 1  
postal-code:4711  
city:torrey  
country:DE  
phone:44 1383754 50600

**Example 2:** create eu-contact (frame and frame will be ignored)  
subject: create eu-contact [your reference id]







# Contacts

handle:CN46-125  
address:1 boulevard mess  
postal-code:4711  
city:miram  
country:DE

phone:44 1383754 50600

MODIFY US CONTACT

Example 1: modify us-contact  
subject:modify us-contact [your reference id]

handle:CN46-125  
address:1 boulevard mess  
postal-code:4711  
city:miram  
country:DE

phone:44 1383754 50600

MODIFY DE CONTACT

Example 1: modify de-contact  
subject:modify de-contact [your reference id]

handle:CN02-125  
address:1 Muehlenstrasse 1  
postal-code:4711  
city:Moersheim  
country:DE

phone:44 1383754 50600

MODIFY EU CONTACT

Example 1: modify eu-contact  
subject:modify eu-contact [your reference id]

handle:CN246  
address:1 boulevard mess  
postal-code:4711  
city:miram  
country:DE  
phone:44 1383754 50600

Keywords: whois, contacts

Last update: 2011-08-11 15:39

# Contacts

## Change an address

Introduction

change cldn-address

Valid values for cldn:

- com
- net
- org
- info
- biz
- public
- names
- us
- de
- ch

With this request you can change the address of the domain owner.

**ATTENTION**

It is not possible to change the following fields of the contact record:

- individual
- home
- frame
- site
- organization
- email

Request fields

method:post change-com-address {your-reference-id}

Definition of this request

| Request ID | Request Fields |  | Response |
|------------|----------------|--|----------|
|            | Request Body   | Request Headers                        |          |
| Request 0  | method:post    | change-com-address {your-reference-id} | 200 OK   |
| Request 1  | method:post    | change-com-address {your-reference-id} | 200 OK   |
| Request 2  | method:post    | change-com-address {your-reference-id} | 200 OK   |
| Request 3  | method:post    | change-com-address {your-reference-id} | 200 OK   |





# Contacts

## Change an owner

### Introduction

With this request you can change the owner of a .com/.net/.org/.info/.mobi/.name/.biz/.de/.cn/.eu/.us-domain.

### Request fields

mailsubject: change owner [your reference id]

Definition of this request

| request-field  | valid values   | required |
|--|--|----------|
| domains0   | [a-z0-9-]{1,63}\.(com net org info mobi biz de cn eu us) | yes      |
| email  | an email <b>without</b> the numerical suffix             | no       |
| individual   | [YN]   | no       |
| name<br>(.com,.net,.org,.info,.biz,.mobi,.de,.cn,.eu,.us only) | [\x20-\x7e]{0,80}  | no       |
| lname  | [\x20-\x7e]{0,80}  | no       |
| fname  | [\x20-\x7e]{0,80}  | no       |
| title  | [\x20-\x7e]{0,80}  | no       |
| organization   | [\x20-\x7e]{0,80}  | no       |
| address-1  | [\x20-\x7e]{0,80}  | no       |
| address-2  | [\x20-\x7e]{0,80}  | no       |
| postal-code  | [\x20-\x7e]{0,50}  | no       |
| state  | [\x20-\x7e]{0,80}  | no       |
| city   | [\x20-\x7e]{0,80}  | no       |
| country  | <a href="#">@country</a>                                 | no       |
| phone  | [\x20-\x7e]{0,50}  | no       |
| fax  | [\x20-\x7e]{0,50}  | no<br>no |
| lock-opt-out   | [YN]   |          |

CHANGE .COM OWNER

### Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.com  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE

# Contacts

phone:44 13383794 504040

CHANGE .NET OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.net  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .ORG OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.org  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .INFO OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.info  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .BIZ OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.biz  
fname:hans  
lname:nose  
address-1:horsefair mews

# Contacts

postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .NAME OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.name  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .US OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.us  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .DE OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.de  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .CN OWNER

**Example 1:** change owner

subject: change owner [your reference id]

# Contacts

domains0:gonzo.cn  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

Keywords: whois, contacts, transfer

Last update: 2016-11-21 15:06

# Contacts

## .asia Contacts

**new-handle** (explicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CDAAS-number, e.g. CDAAS-176265.

**ATTENTION**

The name of the request field depends on the contact. If you want to create a contact for the owner-contact, you have to replace the "-" at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "-" at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "-" at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "-" at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory. If you do not provide the **firstname** and **lastname**, you have to provide the request field **name**. If **name** and **name** are not found, this is very important for the whole output. Everyone a field **person** is shown. If you are using the request field **name**, the value for **name**, regardless the content of the request fields **firstname** and **lastname**. If you do not provide the request field **name** but you are providing the request fields **firstname** and **lastname**, the value is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

| Request Field | Request Name | Request Value |
|---------------|--------------|---------------|
| new-handle    | new-handle   | new-handle    |
| name          | new-handle   | new-handle    |
| firstname     | new-handle   | new-handle    |
| lastname      | new-handle   | new-handle    |
| email         | new-handle   | new-handle    |
| phone         | new-handle   | new-handle    |
| address-1     | new-handle   | new-handle    |
| address-2     | new-handle   | new-handle    |
| address-3     | new-handle   | new-handle    |
| city          | new-handle   | new-handle    |
| state         | new-handle   | new-handle    |
| country       | new-handle   | new-handle    |
| zipcode       | new-handle   | new-handle    |
| phone         | new-handle   | new-handle    |
| email         | new-handle   | new-handle    |
| name          | new-handle   | new-handle    |
| phone         | new-handle   | new-handle    |
| email         | new-handle   | new-handle    |

# Contacts

An existing contact (`@handle` or `@name-cc` (asia only))

This means an existing contact handle in the JOKER DATABASE.

Example:

```
owner-contact-handle:COAS-170209
admin-contact-handle:COAS-170209
tech-contact-handle:COAS-170209
billing-contact-handle:COAS-170209
```

Asia domains require an additional type of contact, the CED contact. This contact has to have its residence in the Asian/Oceania area.

The Joker.com Registry Gateways automatically will use your provided tech-contact for the CED contact.

This means that the request for you remains consistent with the usual requests, you only have to make sure that the country code is correct, otherwise the asia registry will reject the order.

In case you have entered a non-existing contact handle, the system will send you an error.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The `@same-as` makes always replace the value for the specified contact handle with the email address of the referenced contact. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for asia-requests the contact handles for (.com|.net|.org|.info|.biz|.de)-contacts are not allowed. If you are referencing to a shortcut like `handle@joker.com`, you will get an error.

Keywords: whois, contacts, asia

Last update: 2011-08-11 15:41

# Contacts

## Create a nameserver

Introduction

create -rdns -rd

Valid values for -rdns-

- com
- net
- org
- info
- biz
- mobi
- gov
- edu
- mil
- int
- ac
- uk

With this request you can create an entry for a nameserver in the Joker.com database. If a nameserver is created, you can reference the nameserver using the hostname during a "Create order" request.

**ATTENTION:**

Only nameservers, which Joker.com is responsible for, will be shown with the ip-address in the whole output.

If you submit a "create-ns" request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code domain, the values for the ip-addresses are ignored.

Request fields

mailsubject: create -rdns -rd [your reference id]

| Field Name       | Field Value | Field Type |
|------------------|-------------|------------|
| create-ns-domain | example.com | str        |
| create-ns-ip     | 192.168.1.1 | ip         |



# Nameservers

```
CREATE COM NAMESPACE
Example 1: create com-ns
subject: create com-ns [your reference id]
no-domain-name ns1.dummy.com
no-ip-address 194.111.43.1
```

```
CREATE NET NAMESPACE
Example 1: create net-ns
subject: create net-ns [your reference id]
no-domain-name ns1.dummy.net
no-ip-address 194.111.43.1
```

```
CREATE ORG NAMESPACE
Example 1: create org-ns
subject: create org-ns [your reference id]
no-domain-name ns1.dummy.org
no-ip-address 194.111.43.1
```

```
CREATE INFO NAMESPACE
Example 1: create info-ns
subject: create info-ns [your reference id]
no-domain-name ns1.dummy.info
no-ip-address 194.111.43.1
```

```
CREATE BIZ NAMESPACE
Example 1: create biz-ns
subject: create biz-ns [your reference id]
no-domain-name ns1.dummy.biz
no-ip-address 194.111.43.1
```

```
CREATE NAME NAMESPACE
Example 1: create name-ns
subject: create name-ns [your reference id]
no-domain-name ns1.dummy.name
no-ip-address 194.111.43.1
```

```
CREATE US NAMESPACE
Example 1: create us-ns
subject: create us-ns [your reference id]
no-domain-name ns1.dummy.us
no-ip-address 194.111.43.1
```

```
CREATE DE NAMESPACE
Example 1: create de-ns
subject: create de-ns [your reference id]
no-domain-name ns1.dummy.de
no-ip-address 194.111.43.1
```

```
CREATE CN NAMESPACE
Example 1: create cn-ns
subject: create cn-ns [your reference id]
no-domain-name ns1.dummy.cn
no-ip-address 194.111.43.1
```

```
CREATE EU NAMESPACE
Example 1: create eu-ns
subject: create eu-ns [your reference id]
no-domain-name ns1.dummy.eu
no-ip-address 194.111.43.1
```

# Nameservers

Keywords: nameserver, modify domain

Last update: 2011-08-11 15:42

# Nameservers

## Modify a nameserver

Introduction

modify-ns.com

Valid values for <id>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- ru

With this request you can change the ip-address of a nameserver in the Joker.com database.

**ATTENTION:**

Only nameservers, which Joker.com is responsible for, will be shown with the ip-address in the whole-output, so only these nameservers could be changed.

If you submit a "modify-ns" request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code-domain, this request will be ignored.

Request fields

mailto:modify-ns@joker.com [your reference id]

Definition of this request

| Request field | Old domain  | Request                           |
|---------------|-------------|-----------------------------------|
| Example       | example.com | modify-ns example.com 192.168.1.1 |
| Request field |             |                                   |

MODIFY COM NAMESERVER  
Example 1: modify-com-ns  
subject: modify-com-ns [your reference id]  
ns-address: 192.168.1.1

# Nameservers

**MODIFY NET NAMESERVER**  
**Example 1:** modify net-na  
subject: modify.com-na [your reference id]  
no-handle.net.dummy.com  
no-p-address:194.111.43.1

**MODIFY ORG NAMESERVER**  
**Example 1:** modify org-na  
subject: modify.org-na [your reference id]  
no-handle.net.dummy.org  
no-p-address:194.111.43.1

**MODIFY INFO NAMESERVER**  
**Example 1:** modify info-na  
subject: modify.info-na [your reference id]  
no-handle.net.dummy.info  
no-p-address:194.111.43.1

**MODIFY BIZ NAMESERVER**  
**Example 1:** modify biz-na  
subject: modify.biz-na [your reference id]  
no-handle.net.dummy.biz no-p-address:194.111.43.1

**MODIFY NAME NAMESERVER**  
**Example 1:** modify name-na  
subject: modify.name-na [your reference id]  
no-handle.net.dummy.name  
no-p-address:194.111.43.1

**MODIFY US NAMESERVER**  
**Example 1:** modify us-na  
subject: modify.us-na [your reference id]  
no-handle.net.dummy.us  
no-p-address:194.111.43.1

**MODIFY DE NAMESERVER**  
**Example 1:** modify de-na  
subject: modify.de-na [your reference id]  
no-handle.net.dummy.de  
no-p-address:194.111.43.1

**MODIFY CN NAMESERVER**  
**Example 1:** modify cn-na  
subject: modify.cn-na [your reference id]  
no-handle.net.dummy.cn  
no-p-address:194.111.43.1

**MODIFY EU NAMESERVER**  
**Example 1:** modify eu-na  
subject: modify.eu-na [your reference id]  
no-handle.net.dummy.eu  
no-p-address:194.111.43.1

Keywords: nameserver, modify-domain

Last update: 2011-08-11 15:42

# Nameservers Support

Introduction

With this request you can send a question to the support team at [jabber.com](mailto:jabber.com). Only questions, which are sent to the e-mail gateway are accepted.

ATTENTION

Please, make sure that you sign your message with the request sent by you to [jabber.com](mailto:jabber.com) during your header registration. Please, also make sure not to include any characters that are not part of the 7-bit ASCII standard and do not use trailing blanks (i.e. every non-blank line has to end with a non-whitespace character).

Request fields

mailto:subject support [your reference id]

Example 1

```
subject support [your reference id]
-----BEGIN PGP SIGNED MESSAGE-----
Hash: SHA1

Enter your question here.
Don't forget to sign it, too!

-----BEGIN PGP SIGNATURE-----
Version: GnuPG v1.3.2 (GNU/Linux)
Comment: For info see http://www.gnupg.org
iQIChwEABAAQAAABQAAJhRwOnZuLjM0MmCwAAQBP3d3WOC8LW
dAgQdF0C8LWOC8LWOC8LW
=JfMz
-----END PGP SIGNATURE-----
```

Keywords: support,PGP

# Other

Last update: 2011-08-11 15:43

# Other