

Joker.com FAQ

Table of Content

Macros	2
What is a macro?	2
E-mail Address	3
.com/.net Contacts	4
.com Contacts	6
.net Contacts	8
.org Contacts	10
.info Contacts	12
.biz Contacts	14
.mobi Contacts	17
.name Contacts	20
.us Contacts	22
.de Contacts	25
.cn Contacts	28
.eu Contacts	31
Valid domain names	34
Nameserver	35
Zonefile entries	36
IP	38
Domain renewal	39
Country code	40
Language code	46
.me Contacts	48

Macros

What is a macro?

A macro is used within the definition of a request.

A macro starts with an @.

Example: @start or @end or @file

Every time you find a macro, please check the definition of this macro for further information.

Keywords: macro definition

Last update: 2007-04-02 15:20

Macros

E-mail Address

@mail
This means an email address in the following format:
Valid values (containing only):
foo@bar.com
foo@bar.com#1
foo@bar.com#12

Invalid values:
Here: Name: john@foo.com,
Name@foo.com (Name:Name)

Valid values: (only enter bar, bar on only):
foo@bar.com

Invalid values:
Here: Name: john@foo.com,
Name@foo.com (Name:Name)

foo@bar.com#12

Keywords: email address

Last update: 2011-08-11 15:34

Macros .com/.net Contacts

new-handle (explicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created and we will add a numerical suffix to the email address that starts with "0" and increases by "1" for every existing contact with such a emailaddress in the JOKER-DATABASE.

ATTENTION:

The name of the request field depends on the contact. If you want to create a contact for the owner-contact, you have to replace the "." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "." at the beginning of the fieldname with "billing-contact".

request field	used values	required
*idnumber	[1-9]	yes
*name	{JOKER+HQ} @C	yes, if individual = Y
*firstname	{JOKER+HQ} @C	yes, if individual = Y
*title	{JOKER+HQ} @C	no
*organization	{JOKER+HQ} @C	yes, if individual = N
*address-1	{JOKER+HQ} @C	yes
*address-2	{JOKER+HQ} @C	no
*postalcode	{JOKER+HQ} @C	yes
*city	{JOKER+HQ} @C	yes
*state	{JOKER+HQ} @C	no
*country		yes
*email	@cont	yes
*phone	{JOKER+HQ} @C	yes
*fax	{JOKER+HQ} @C	no

An existing contact (@cont or @same-as) (cont.net only)

This means an existing contact handle in the JOKER-DATABASE.

Example:

```
owner-contact-handle.foo@bar.com#1
admin-contact-handle.foo@bar.com
tech-contact-handle.foo@bar.com#1
billing-contact-handle.foo@bar.com#1
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle.same-as-owner-contact
tech-contact-handle.same-as-admin-contact
billing-contact-handle.same-as-tech-contact
```

The @same-as macro always replaces the value for the specified contact handle with the email address of the makrotaget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for (cont.net) requests, contact handles for (link) contacts are not allowed. If you are referencing to a shortcut the CONTACT-NAME, you will get an error.

Macros

Last update: 2007-04-17 22:05

Macros

.com Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CCOM-<number>.

e.g. CCOM-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no

Macros

".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact ([@comcont](#) or [@same-as](#)) (.com only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:CCOM-176269
admin-contact-handle:CCOM-176229
tech-contact-handle:CCOM-176269
billing-contact-handle:CCOM-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .com-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @comcont @same-as admin tech billing

Last update: 2015-11-09 17:47

Macros

.net Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CNET-<number>, e.g. CNET-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes

Macros

".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@netcont or @same-as) (.net only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:CNET-176269
admin-contact-handle:CNET-176229
tech-contact-handle:CNET-176269
billing-contact-handle:CNET-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .net-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @netcont @same-as admin tech billing

Last update: 2015-11-09 17:48

Macros

.org Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CORG-<number>, e.g. CORG-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes

Macros

".."-city	[[\x20-\x7e]{1,80}	yes
".."-state	[[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (**@orgcont** or **@same-as**) (.org only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:CORG-176269
admin-contact-handle:CORG-176229
tech-contact-handle:CORG-176269
billing-contact-handle:CORG-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .org-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @orgcont @same-as admin tech billing

Last update: 2015-11-09 17:49

Macros

.info Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format C<number>-LRMS, e.g. C176269-LRMS.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no

Macros

".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@infocont or @same-as) (.info only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:C176269-LRMS  
admin-contact-handle:CAFI-007  
tech-contact-handle:C176269-LRMS  
billing-contact-handle:CAFI-008
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .info-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @infocont @same-as admin tech billing

Last update: 2015-11-09 17:49

Macros

.biz Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created.

ATTENTION

According to the rules of NEULEVEL, the fieldlength for most of the requestfields are limited to 30 characters. Please check very carefully the definitions of the request fields.

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

Please, keep in mind, that if you are using the concatenation of **fname** and **lname**, you have to care that the sum of both fields should not be longer than 30 characters.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
---------------	--------------	----------

Macros

".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,30}	no, if name is given
".."-fname	[\x20-\x7e]{0,30}	no, if name is given
".."-name	[\x20-\x7e]{0,30}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,30}	no
".."-organization	[\x20-\x7e]{0,30}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,30}	yes
".."-address-2	[\x20-\x7e]{0,30}	no
".."-address-3	[\x20-\x7e]{0,30}	no
".."-postal-code	[\x20-\x7e]{1,10}	yes
".."-city	[\x20-\x7e]{1,30}	yes
".."-state	[\x20-\x7e]{0,30}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,17}	yes
".."-fax	[[\x20-\x7e]{0,17}	no

An existing contact (@bizcont or @same-as) (.biz only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle: CNEU-12345
admin-contact-handle: CNEU-12345
tech-contact-handle: CNEU-12345
billing-contact-handle: CNEU-12345

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

Macros

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .biz-requests the contact handles for (.com/.net/.org/.info)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Note that for .biz-requests the contacthandles for (.info)-contacts are not allowed. If you referencing to a shortcut like C176269-LRMS, you will get an error.

Keywords: new-handle @bizcont @same-as admin tech billing

Last update: 2015-11-09 17:51

Macros

.mobi Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COMO-<number>, e.g. COMO-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

Macros

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact ([@mobicont](#) or [@same-as](#)) (.mobi only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:COMO-176269
admin-contact-handle:COMO-176229
tech-contact-handle:COMO-176269
billing-contact-handle:COMO-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

Macros

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .mobi-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @mobicont @same-as admin tech billing owner

Last update: 2015-11-09 17:50

Macros

.name Contacts

new-handle (explicit creation of a new contact)

This means the addition of a new contact. If a contact with the provided email address exists in the JOKER_CONTACTS table, a new contact will be created. The reference for the created handle is following the format CNM-*countdown*, e.g. CNM-17628.

ATTENTION

The name of the request field depends on the contact. If you want to create a contact for the owner-contact, you have to replace the "." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory. If you do not provide the **frame** and **frames**. You have to provide the request field **name**. If **frame** and **frames** are not found. This is very important for the whole output. Everywhere a field **person** is shown. If you are using the request field **name**, the whole is showing the value for **name**, regardless the content of the request fields **frame** and **frames**. If you do not provide the request field **name** but you are providing the request fields **frame** and **frames**, the whole is showing the concatenation of these fields.

There is also a new request field called **address-2** within the contact definition. This field is not mandatory. It is simply the 3rd line of the address.

Request Field	Def. Name	Output
contactname	NA	NA
name	000-00000000	NA, if name is given
name	000-00000000	NA, if name is given
name	000-00000000	NA, if frame AND/OR frames are not given
name	000-00000000	NA
organization	000-00000000	NA, if organization is
address-1	000-00000000	NA
address-2	000-00000000	NA
address-3	000-00000000	NA
contactcode	000-00000000	NA
city	000-00000000	NA
state	000-00000000	NA

Macros

OWNER	OWNER	OWNER
ADMIN	ADMIN	ADMIN
TECH	TECH	TECH
BILLING	BILLING	BILLING

An existing contact (@namecont or @same-as) (name only)

This means an existing contact handle in the JOKER DATABASE.

Example:

```
owner-contact-handle-CHAM-171228  
admin-contact-handle-CHAM-171228  
tech-contact-handle-CHAM-171228  
billing-contact-handle-CHAM-171228
```

In case you have entered a non-existing contact handle, the system will send you an email.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The @same-as syntax always replaces the value for the specified contact handle with the email address of the referenced contact. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for same requests the contact handles for (user:net) contacts are not allowed. If you are referencing to a shortcut like here@joker.net, you will get an error.

Keywords: new-handle @namecont @same-as admin tech billing owner

Last update: 2007-06-21 11:11

Macros

.us Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COUS-<number>, e.g. COUS-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes

Macros

".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@uscont or @same-as) (.us only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:COUS-176269
admin-contact-handle:COUS-176229
tech-contact-handle:COUS-176269
billing-contact-handle:COUS-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

Macros

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .us-requests the contact handles for (.com/.net)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @uscont @same-as admin tech billing owner

Last update: 2015-11-09 17:51

Macros

.de Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format CODE-<number>, e.g. CODE-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given

Macros

".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	yes, but for admin-c and tech-c only

An existing contact (@decont or @same-as) (.de only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

owner-contact-handle:CODE-176269

admin-contact-handle:CODE-176229

tech-contact-handle:CODE-176269

billing-contact-handle:CODE-176269

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

Macros

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .de-requests the contact handles for (.com/.net/.org/.info/.biz/.cn)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @decont @same-as admin tech billing owner

Last update: 2015-11-09 17:50

Macros

.cn Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COCN-<number>, e.g. COCN-176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fnamelname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes

Macros

".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@cncont or @same-as) (.cn only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:COCN-176269
admin-contact-handle:COCN-176229
tech-contact-handle:COCN-176269
billing-contact-handle:COCN-176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

Macros

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .cn-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @cncont @same-as admin tech billing owner

Last update: 2015-11-09 17:51

Macros

.eu Contacts

new-handle (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format C<number>, e.g. C176269.

ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname** and **lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field **name**, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but you are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
---------------	--------------	----------

Macros

".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname and/or lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

An existing contact (@uscont or @same-as) (.us only)

This means an existing contact handle in the JOKER-DATABASE.

Examples:

```
owner-contact-handle:C176269
admin-contact-handle:C176229
tech-contact-handle:C176269
billing-contact-handle:C176269
```

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```


Macros

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .eu-requests the contact handles for (.com/.net/.org/.info/.biz/.de/.us)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

Keywords: new-handle @eucont @same-as admin tech billing owner

Last update: 2015-11-09 17:52

Macros

Valid domain names

@dom - a valid domain name under .com/.net

@orgdom - a valid domain name under .org

@infodom - a valid domain name under .info

@dedom - a valid domain name under .de

@cndom - a valid domain name under .cn

@eudom - a valid domain name under .eu

@usdom - a valid domain name under .us

@fqdn - a valid domain name under .com/.net/.org/.info/.mobi/.name/.biz/.de/.cn/.eu/.us

Keywords: @dom @orgdom @infodom @dedom @cndom @eudom @usdom @fqdn

Last update: 2007-03-28 15:45

Macros

Nameserver

@ns - the definition of an existing nameserver

You have to provide a valid nameserver handle. Implicit nameserver creation is not allowed.

Examples:

ns1.foo.bar.net
ns2.foo.bar.net

ns3.foo.bar.net

Keywords: @ns nameserver

Last update: 2015-11-09 17:53

Macros

Zonefile entries

@a_record

[a hostprefix without the domainname]:[IP-Address]

- trailing dots at the hostprefix are deleted
- an "@" will be expanded to the domainname

Example1:

a:www:194.233.101.99

Example2:

a:@:194.233.101.99

@mx_record

[a hostprefix without the domainname]:[priority]:[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" as the value of the hostprefix will be expanded to the domain name

Example 1:

mx:www:50:mail.hansnose.net

Example 2:

mx:www:90:mail.hansnose.net

Example 3:

mx:@:50:mail.hansnose.net

Example 4:

mx:@:90:mail.hansnose.net

@cname_record

[a hostprefix without the domainname]:[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" for the hostprefix is not supported within a CNAME-Record

Macros

Example 1:

cname:www:mail.hansnose.net

Example 2:

cname:www2:mail.hansnose.net

@url_record

[a hostprefix without the domainname]::[a full qualified hostname]

- trailing dots at the hostprefix are deleted
- an "@" as the value of the hostprefix will be expanded to the domain name

Example 1:

url:www:http://some.redirector.com

Example 2:

url:www2:http://some.redirector.com:9002

Example 3:

url:www3:https://some.redirector.com

Example 4:

url:www4:https://some.redirector.com:9002

Keywords: @a_record @mx_record @cname_record @url_record

Last update: 2007-04-20 14:49

Macros IP

@ip - a valid ip address

IP addresses within the following ranges are NOT valid:

Ã,

IP	
10.0.0.0	10.255.255.255
172.16.0.0	172.31.255.255
192.168.0.0	192.168.255.255
172.31.0.0	172.31.255.255

Keywords: @ip

Last update: 2007-04-02 16:24

Macros

Domain renewal

@renew

Here you have to provide the domain name and the renewal period or the desired expiration year on one line. You have to separate the domain name and renewal period/expire year with an ":" (ASCII 058). The maximum for the renewal period is 9 years.

Examples:

```
domain1:blafasel.com:2  
domain2:hansnose.net:3  
domain2:hansnose.info:2005  
domain2:hansnose.biz:2
```

Attention:

If you are using the expire year and the current expire year of the domain is equal or greater than the provided value for that field, the request will not be processed.

Keywords: @renew

Last update: 2007-03-28 16:12

Macros

Last update: 2007-04-17 22:12

Macros

Language code

@**language** - one of the following language codes

Languagecode	Language
AFR	Afrikaans
ALB	Albanian
ARA	Arabic
ARM	Armenian
AZE	Azerbaijani
BAQ	Basque
BUL	Bulgarian
BUR	Burmese
CAT	Catalan
CHI	Chinese
CZE	Czech
DAN	Danish
DUT	Dutch
ENG	English
EST	Estonian
FAO	Faroese
FIN	Finnish
FRE	French
GEO	Georgian
GER	German
HEB	Hebrew
HIN	Hindi
HUN	Hungarian
ICE	Icelandic
ITA	Italian
JPN	Japanese
KOR	Korean
KUR	Kurdish
LAO	Lao
LAV	Latvian
LIT	Lithuanian
MAC	Macedonian
MAL	Malayalm
NEP	Nepali
NOR	Norwegian
PER	Persian
POL	Polish
POR	Portuguese
RUM	Romanian
RUS	Russian
SAN	Sanskirt
SCC	Serbian
SCR	Croatian

Macros

SLO	Slovak
SLV	Slovenian
SPA	Spanish
SWA	Swahili
SWE	Swedish
SYR	Syriac
TAM	Tamil
THA	Thai
TIB	Tibetan
TUR	Turkish
UKR	Ukrainian
URD	Urdu
UZB	Uzbek
VIE	Vietnamese
ZHO	Chinese

Keywords: @language language code

Last update: 2015-11-09 17:46

Macros .me Contacts

new-handle (explicit creation of a new contact)

This means the definition of a new contact: if a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COME-number, e.g. COME-174289.

ATTENTION

The name of the request field depends on the contact: if you want to create a contact for the owner-contact, you have to replace the "-" at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the "-" at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the "-" at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the "-" at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **firstname**. You have to provide the request field **name**. If **firstname** and **lastname** are not found. This is very important for the whole output. Everywhere a field **person** is shown. If you are using the request field **name**, the whole is showing the value for **name**, regardless the content of the request fields **firstname** and **lastname**. If you do not provide the request field **name** but you are providing the request fields **firstname** and **lastname**, the whole is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request field	request value	response
new-handle	16	16
name	COM-174289	ok, if name is given
firstname	COM-174289	ok, if name is given
lastname	COM-174289	ok, if lastname and/or firstname are not given
name	COM-174289	ok, if address is given
address-1	COM-174289	ok, if address is given
address-2	COM-174289	ok, if address is given
address-3	COM-174289	ok, if address is given
city	COM-174289	ok, if address is given
state	COM-174289	ok, if address is given
country	COM-174289	ok, if address is given
zip	COM-174289	ok, if address is given

Macros

NAME	DESCRIPTION	EXAMPLE
NAME	DESCRIPTION	EXAMPLE

An existing contact (@mecont or @same-as (me only))

This means an existing contact handle in the JOKER DATABASE.

Examples:

```
owner-contact-handle:COMB-112345  
admin-contact-handle:COMB-112345  
tech-contact-handle:COMB-112345  
billing-contact-handle:COMB-112345
```

In case you have entered a non-existing contact handle, the system will send you an error.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

```
admin-contact-handle:same-as-owner-contact
```

```
tech-contact-handle:same-as-admin-contact
```

```
billing-contact-handle:same-as-tech-contact
```

The @same-as makes always replace the value for the specified contact handle with the email address of the macrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .me-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like here@joker.com, you will get an error.

Keywords: new-handle @mecont @same-as admin tech billing owner

Last update: 2008-08-14 11:46

Macros