

Joker.com FAQ

Table of Content

Domains	2
Create an order	2
Modify a domain	26
Renew a domain	32
Transfer a domain	36
Delete a domain	39
List domains	41
Lock a domain	43
Unlock a domain	44
Get Auth-id	45
Grant Roles/Domain Permissions, Internal Transfer	46

Domains

Create an order

Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

- xxx

- asia

- me

With this request you can register one or more domains.

You have to provide the following information within the request:

- domain name(s),
- owner-contact-handle,
- admin-contact-handle,
- tech-contact-handle,
- billing-contact-handle,
- nameserver information,
- additional services, if required.

You can register up to 501 domains with one request.

If you register more than one domain with a request, all domains registered with this request will have the same contact and nameserver structure.

There are two new requestfields within this request:

- name

Domains

- address-3

ATTENTION

Please, refer to the table for the corresponding contact handles.

TLD	Contact handle
com	CCOM-<number>
net	CNET-<number>
org	CORG-<number>
info	C<number>-LRMS
biz	CNEU-<number>
mobi	COMO-<number>
name	CNAM-<number>
us	COUS-<number>
de	CODE-<number>
cn	COCN-<number>
eu	C<number>
me	COME-<number>
asia	COAS-<number>
xxx	CONX-<number>

Request fields

mailsubject: create <tld>-order [your reference id]

Definition of this request

tld	request field		
	domains[0..500]	period	language[0..500]
com	[a-z0-9-]{1,63}\.com	^([1..9]{1})\$	@language
net	[a-z0-9-]{1,63}\.net	^([1..9]{1})\$	
org	[a-z0-9-]{1,63}\.org	^([1..9]{1})\$	
info	[a-z0-9-]{1,63}\.info	^([1..9]{1})\$	
biz	[a-z0-9][a-z0-9-]{1,6	^([1..9]{1})\$	

Domains

	1}[a-z0-9]\.biz		
mobi	[a-z0-9]{1,63}\.mobi	^([1..9]{1})\$	
name	[a-z0-9]{1,63}\.name	^([2..9]{1})\$	
us	[a-z0-9]{1,63}\.us	^([2..9]{1})\$	
de	[a-z0-9]{1,63}\.de	^([1..9]{1})\$	
cn	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.cn	^([1..9]{1})\$	
eu	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.eu	^([1..9]{1})\$	
me	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.me	^([1..9]{1})\$	
asia	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.asia	^([1..9]{1})\$	
xxx	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.xxx	^([1..9]{1})\$	
required	yes	yes	no (IDN domains only)

tld	owner-contact-handle	admin-contact-handle	tech-contact-handle	billing-contact-handle
com			@comcont	
net			@netcont	
org			@orgcont	
info			@infocont	
biz			@decont	
mobi			@mobicont	
name			@namecont	
us			@uscont	
de			@bizcont	
cn			@cncont	
eu			@eucont	
me			@mecont	
asia			@asiacon	
required			yes	

tld	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle
<tld>				@ns		
required	yes	yes			no	

Domains

.COM order

Example 1: create com-order with implicit contact-handle-creation of the owner-contact

subject: create com-order [your reference id]

```
domains0:xn--hans-mller-feb.com
language0:AFR
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

Example 2: create com-order with implicit nameserver-creation

subject: create com-order [your reference id]

```
domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

Example 3: create com-order with implicit contact-handle-creation of all contacts

Domains

subject: create com-order [your reference id]

domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.NET order

Domains

Example 1: create net-order with implicit contact-handle-creation of the owner-contact

subject: create net-order [your reference id]

```
domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

Example 2: create net-order with implicit nameserver-creation

subject: create net-order [your reference id]

```
domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

Example 3: create net-order with implicit contact-handle-creation of all contacts

subject: create net-order [your reference id]

```
domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
```

Domains

domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.ORG order

Example 1: create org-order with implicit contact-handle-creation of the owner-contact

subject: create org-order [your reference id]

Domains

```
domains0:xn--hans-mller-feb.org
language0:AFR
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

Example 2: create org-order with implicit nameserver-creation

```
subject: create org-order [your reference id]
```

```
domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-handle:CORG-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

Example 3: create org-order with implicit contact-handle-creation of all contacts

```
subject: create org-order [your reference id]
```

```
domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
```

Domains

owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.INFO order

Example 1: create info-order with implicit contact-handle-creation of the owner-contact

subject: create info-order [your reference id]

domains0:xn--hans-mlller-feb.info
language0:AFR
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2

Domains

owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C282828-LRMS
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create info-order with implicit nameserver-creation

subject: create info-order [your reference id]

domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-handle:C176269-LRMS
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C176219-LRMS
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create info-order with implicit contact-handle-creation of all contacts

subject: create info-order [your reference id]

domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y

Domains

admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.BIZ order

Example 1: create biz-order with implicit contact-handle-creation of the owner-contact

domains0:xn--hans-mller-feb.biz
language0:AFR
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo

Domains

admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create biz-order with implicit nameserver-creation

subject: create biz-order [your reference id]

domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-handle:CNEU-123
admin-contact-handle:CNEU-124
tech-contact-handle:CNEU-125
billing-contact-handle:CNEU-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create biz-order with implicit contact-handle-creation of all contacts

subject: create biz-order [your reference id]

domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz

Domains

domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.MOBI ORDER

Example 1: create mobi-order with implicit contact-handle-creation of the owner-contact

subject: create mobi-order [your reference id]

domains0:xn--hans-mller-feb.mobi
language0:AFR
domains1:minus-10a.mobi

Domains

domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create mobi-order with implicit nameserver-creation

subject: create mobi-order [your reference id]

domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-handle:COMO-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create mobi-order with implicit contact-handle-creation of all contacts

subject: create mobi-order [your reference id]

domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey

Domains

owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.NAME ORDER

Example 1: create name-order with implicit contact-handle-creation of the owner-contact

subject: create name-order [your reference id]

domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-email:gonzo@nose.net

Domains

owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create name-order with implicit nameserver-creation

subject: create name-order [your reference id]

domains0:minus-109.name
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-handle:CNAM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create name-order with implicit contact-handle-creation of all contacts

subject: create name-order [your reference id]

domains0:minus-109.name
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo

Domains

admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.US ORDER

Example 1: create us-order with implicit contact-handle-creation of the owner-contact

subject: create us-order [your reference id]

domains0:xn--hans-mller-feb.us
language0:AFR
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact

Domains

tech-contact-handle:same-as-admin-contact
billing-contact-handle:COUS-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create us-order with implicit nameserver-creation

subject: create us-order [your reference id]

domains0:minus-109.us
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-handle:COUS-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COUS-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create us-order with implicit contact-handle-creation of all contacts

subject: create us-order [your reference id]

domains0:minus-109.us
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi

Domains

tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.DE ORDER

Example 1: create de-order with implicit contact-handle-creation of the owner-contact

subject: create de-order [your reference id]

domains0:minus-10x.de
language0:GER
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nase
owner-contact-address-1:Musterstrasse 11
owner-contact-postal-code:4711
owner-contact-city:Musterhausen
owner-contact-country:DE
owner-contact-phone:49 13383794 504040
owner-contact-fax:49 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CODE-1007
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create net-order with implicit nameserver-creation

subject: create de-order [your reference id]

Domains

domains0:minus-109.de
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-handle:CODE-1007
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CODE-1007
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create net-order with implicit contact-handle-creation of all contacts

subject: create de-order [your reference id]

domains0:minus-109.de
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nase
owner-contact-address-1:Musterstrasse 11
owner-contact-postal-code:4711
owner-contact-city:Musterhausen
owner-contact-country:DE
owner-contact-phone:49 13383794 504040
owner-contact-fax:49 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nase
admin-contact-address-1:Musterstrasse 11
admin-contact-postal-code:4711
admin-contact-city:Musterhausen
admin-contact-country:DE
admin-contact-phone:49 13383794 504040
admin-contact-fax:49 13383794 504040
tech-contact-email:gonzo@nose.net
tech-contact-individual:Y
tech-contact-fname:gonzo
tech-contact-lname:nase
tech-contact-address-1:Musterstrasse 11
tech-contact-postal-code:4711
tech-contact-city:Musterhausen
tech-contact-country:DE
tech-contact-phone:49 13383794 504040
tech-contact-fax:49 13383794 504040
billing-contact-email:gonzo@nose.net

Domains

billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nase
billing-contact-address-1:Musterstrasse 11
billing-contact-postal-code:4711
billing-contact-city:Musterhausen
billing-contact-country:DE
billing-contact-phone:49 13383794 504040
billing-contact-fax:49 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.CN ORDER

Example 1: create cn-order with implicit contact-handle-creation of the owner-contact

subject: create cn-order [your reference id]

domains0:xn--hans-mller-feb.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net

Domains

billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create cn-order using existing cn-handles

subject: create cn-order [your reference id]

domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-handle:COCN-123
admin-contact-handle:COCN-124
tech-contact-handle:COCN-125
billing-contact-handle:COCN-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create cn-order with backreferences using @same-as

subject: create cn-order [your reference id]

domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
ns1-domain-name:nsxx1.gonzo.net

Domains

ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.EU ORDER

Example 1: create eu-order with implicit contact-handle-creation of all contacts

subject: create eu-order [your reference id]

domains0:xn--hans-mller-feb.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1

Domains

ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create eu-order using existing .eu-handles

subject: create eu-order [your reference id]

domains0:minus-109.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-handle:C123123
admin-contact-handle:C123124
tech-contact-handle:C123125
billing-contact-handle:C123126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create eu-order with backreferences using @same-as

subject: create eu-order [your reference id]

domains0:minus-109.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Keywords: create, order, registration

Last update: 2015-07-29 12:02

Domains

Modify a domain

Introduction

modify <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

- xxx

- asia

- me

With this request you can modify existing domains. You have to provide the following information within the

Domains

request:

- the domainname,
- handle(s) you want to change. (handles from the info-system are not valid)

The system will ignore not specified handles, so you have to provide only the handles, you would like to change.

Changes within the owner-contact

In case of changing the owner-contact-handle, the system checks, if lname and/or fname and/or organization differ from the original owner-contact-handle. If there are differences these changes will be ignored.

Request fields

mailsubject: modify <tld>-domain [your reference id]

Definition of this request

request-field	valid values		required
tld	com net org info mobi name us de	biz eu	yes
sld	[a-z0-9-]{1,63}	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]	yes
owner-contact-handle	Please, refer to the table below for the valid values.		no
admin-contact-handle			no
tech-contact-handle			no

Domains

billing-contact-handle		no
ns1-handle	@ns	no
ns2-handle		no
ns3-handle		no
ns4-handle		no
ns5-handle		no
ns6-handle		no

tld	contact handle
com	@comcont
net	@netcont
org	@orgcont
info	@infocont
biz	@bizcont
mobi	@mobicont
name	@namecont
us	@uscont
de	@decont
cn	@cncont
eu	@eucont

Example 1: modify com-domain

subject: modify domain [your reference id]

sld:gonzo
tld:com
admin-contact-handle:gonzo@nose.com#0
tech-contact-handle:hans@nose.com
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: modify net-domain

subject: modify net-domain [your reference id]

sld:gonzo
tld:net
admin-contact-handle:CNET-1234
tech-contact-handle:CNET-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Domains

Example 3: modify org-domain

subject: modify net-domain [your reference id]

sld:gonzo
tld:org
admin-contact-handle:CORG-1234
tech-contact-handle:CORG-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 4: modify info-domain

subject: modify info-domain [your reference id]

sld:gonzo
tld:info
admin-contact-handle:C112234-LRMS
tech-contact-handle:C112244-LRMS
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

OR

modify info-domain (new naming convention for info-handles)

subject: modify info-domain [your reference id]

sld:gonzo
tld:info
admin-contact-handle:C112244-LRMS
tech-contact-handle:CAFI-007
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 5: modify biz-domain

subject: modify biz-domain [your reference id]

sld:gonzo
tld:biz
admin-contact-handle:CNEU-11224
tech-contact-handle:CNEU-112244
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 6: modify mobi-domain

Domains

subject: modify mobi-domain [your reference id]

sld:gonzo
tld:mobi
admin-contact-handle:COMO-1234
tech-contact-handle:COMO-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 7: modify name-domain

subject: modify name-domain [your reference id]

sld:gonzo
tld:name
admin-contact-handle:CNAM-1234
tech-contact-handle:CNAM-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 8: modify us-domain

subject: modify us-domain [your reference id]

sld:gonzo
tld:us
admin-contact-handle:COUS-1234
tech-contact-handle:COUS-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 9: modify de-domain

subject: modify de-domain [your reference id]

sld:gonzo
tld:de
admin-contact-handle:CODE-1234
tech-contact-handle:CODE-1234
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Example 10: modify cn-contact

subject: modify cn-contact [your reference id]

Domains

handle:COCN-1235
address-1:horsefair mews
postal-code:4711
city:romsey
country:DE
phone:44 13383794 504040

Example 11: modify eu-domain

subject: modify eu-domain [your reference id]

sld:gonzo
tld:eu
admin-contact-handle:C112244
tech-contact-handle:C112244
ns1-handle:ns1.gonzo.net
ns2-handle:ns2.gonzo.net

Keywords: modify-domain, nameserver, contacts

Last update: 2015-07-29 12:02

Domains

Renew a domain

Introduction

Renew <ID>-domain

Valid values for <ID>

- com
- net
- org
- info
- biz
- mobi
- name
- us
- ca
- cn

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s)
- the renewalperiod or the desired expirationyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.

If the sum of the expire time and the renewal time is more than 10 years, we will reject your request.

This request is not working for domains, which are located on the old system. For these domains you have to check the documentation of the old system.

If you provide the expire year, this request will be rejected, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew-request is sent twice by mistake.

Request fields

mailto:subject: renew <ID>-domain [your reference ID]

Domains

Definition of this request

You have to provide the domain name and the renewal period or the desired expire year using the format "YYYY" on one line. You have to separate each field with a " " (ASCII 32). The maximum for the renewal period is 9 years.

domain	renewal period	expire
example.com	1	

COM renewal

Example 1: renew 1 domain for 1 year using the field period
subject: renew com-domain {your reference id}
domain@minus-100.com.1

Example 2: renew 5 domains for 4 years using the field period
subject: renew com-domain {your reference id}
domain@minus-100.com.4
domain@minus-110.com.4
domain@minus-120.com.4
domain@minus-130.com.4
domain@minus-140.com.4

Example 3: renew 5 domains for different years using the field period
subject: renew com-domain {your reference id}
domain@minus-100.com.1
domain@minus-110.com.2
domain@minus-120.com.3
domain@minus-130.com.4
domain@minus-140.com.5

Example 4: renew 1 domain using the field expiration year
subject: renew com-domain {your reference id}
domain@minus-100.com.2005

NET Renewal

Example 1: renew 1 domain for 1 year using the field period
subject: renew net-domain {your reference id}
domain@minus-100.net.1

Example 2: renew 5 domains for 4 years using the field period
subject: renew net-domain {your reference id}
domain@minus-100.net.4
domain@minus-110.net.4
domain@minus-120.net.4
domain@minus-130.net.4
domain@minus-140.net.4

Example 3: renew 5 domains for different years using the field period
subject: renew net-domain {your reference id}
domain@minus-100.net.1
domain@minus-110.net.2
domain@minus-120.net.3
domain@minus-130.net.4
domain@minus-140.net.5

Example 4: renew 1 domain using the field expiration year
subject: renew net-domain {your reference id}
domain@minus-100.net.2005

ORG Renewal

Example 1: renew 1 domain for 1 year using the field period
subject: renew org-domain {your reference id}
domain@minus-100.org.1

Example 2: renew 5 domains for 4 years using the field period
subject: renew org-domain {your reference id}
domain@minus-100.org.4
domain@minus-110.org.4
domain@minus-120.org.4
domain@minus-130.org.4
domain@minus-140.org.4

Example 3: renew 5 domains for different years using the field period
subject: renew org-domain {your reference id}
domain@minus-100.org.1
domain@minus-110.org.2
domain@minus-120.org.3
domain@minus-130.org.4
domain@minus-140.org.5

Example 4: renew 1 domain using the field expiration year
subject: renew org-domain {your reference id}
domain@minus-100.org.2005

INFO Renewal

Example 1: renew 1 domain for 1 year using the field period
subject: renew info-domain {your reference id}
domain@minus-100.info.1

Example 2: renew 5 domains for 4 years using the field period
subject: renew info-domain {your reference id}
domain@minus-100.info.4
domain@minus-110.info.4
domain@minus-120.info.4
domain@minus-130.info.4
domain@minus-140.info.4

Example 3: renew 5 domains for different years using the field period
subject: renew info-domain {your reference id}
domain@minus-100.info.1
domain@minus-110.info.2
domain@minus-120.info.3
domain@minus-130.info.4
domain@minus-140.info.5

Example 4: renew 1 domain using the field expiration year
subject: renew info-domain {your reference id}
domain@minus-100.info.2005

Domains

BIZ Renewal
Example 1: renew 1 domain for 1 year using the field period
subject: renew biz-domain [your reference id]
domainid: minuo-100.biz.1

Example 2: renew 5 domains for 4 years using the field period
subject: renew biz-domain [your reference id]
domainid: minuo-100.biz.4
domainid: minuo-110.biz.4
domainid: minuo-120.biz.4
domainid: minuo-130.biz.4
domainid: minuo-140.biz.4

Example 3: renew 5 domains for different years using the field period
subject: renew biz-domain [your reference id]
domainid: minuo-100.biz.1
domainid: minuo-110.biz.2
domainid: minuo-120.biz.3
domainid: minuo-130.biz.4
domainid: minuo-140.biz.5

Example 4: renew 1 domain using the field expirationyear
subject: renew biz-domain [your reference id]
domainid: minuo-100.biz.2005

NAME Renewal
Example 1: renew 1 domain for 1 year using the field period
subject: renew name-domain [your reference id]
domainid: minuo-100.name.1

Example 2: renew 5 domains for 4 years using the field period
subject: renew name-domain [your reference id]
domainid: minuo-100.name.4
domainid: minuo-110.name.4
domainid: minuo-120.name.4
domainid: minuo-130.name.4
domainid: minuo-140.name.4

Example 3: renew 5 domains for different years using the field period
subject: renew name-domain [your reference id]
domainid: minuo-100.name.1
domainid: minuo-110.name.2
domainid: minuo-120.name.3
domainid: minuo-130.name.4
domainid: minuo-140.name.5

Example 4: renew 1 domain using the field expirationyear
subject: renew name-domain [your reference id]
domainid: minuo-100.name.2005

US Renewal
Example 1: renew 1 domain for 1 year using the field period
subject: renew us-domain [your reference id]
domainid: minuo-100.us.1

Example 2: renew 5 domains for 4 years using the field period
subject: renew us-domain [your reference id]
domainid: minuo-100.us.4
domainid: minuo-110.us.4
domainid: minuo-120.us.4
domainid: minuo-130.us.4
domainid: minuo-140.us.4

Example 3: renew 5 domains for different years using the field period
subject: renew us-domain [your reference id]
domainid: minuo-100.us.1
domainid: minuo-110.us.2
domainid: minuo-120.us.3
domainid: minuo-130.us.4
domainid: minuo-140.us.5

Example 4: renew 1 domain using the field expiry year
subject: renew us-domain [your reference id]
domainid: minuo-100.us.2005

DE Renewal
Example 1: renew 1 domain for 1 year using the field period
subject: renew de-domain [your reference id]
domainid: minuo-100.de.1

Example 2: renew 5 domains for 4 years using the field period
subject: renew de-domain [your reference id]
domainid: minuo-100.de.4
domainid: minuo-110.de.4
domainid: minuo-120.de.4
domainid: minuo-130.de.4
domainid: minuo-140.de.4

Example 3: renew 5 domains for different years using the field period
subject: renew de-domain [your reference id]
domainid: minuo-100.de.1
domainid: minuo-110.de.2
domainid: minuo-120.de.3
domainid: minuo-130.de.4
domainid: minuo-140.de.5

Example 4: renew 1 domain using the field expirationyear
subject: renew de-domain [your reference id]
domainid: minuo-100.de.2005

CA Renewal
Example 1: renew 1 domain for 1 year using the field period
subject: renew ca-domain [your reference id]
domainid: minuo-100.ca.1

Example 2: renew 5 domains for 4 years using the field period
subject: renew ca-domain [your reference id]
domainid: minuo-100.ca.4
domainid: minuo-110.ca.4
domainid: minuo-120.ca.4
domainid: minuo-130.ca.4
domainid: minuo-140.ca.4

Example 3: renew 5 domains for different years using the field period
subject: renew ca-domain [your reference id]
domainid: minuo-100.ca.1
domainid: minuo-110.ca.2
domainid: minuo-120.ca.3
domainid: minuo-130.ca.4
domainid: minuo-140.ca.5

Example 4: renew 1 domain using the field expiry year
subject: renew ca-domain [your reference id]
domainid: minuo-100.ca.2005

Keywords: renew, renewal

Domains

Last update: 2011-08-11 14:18

Domains

Transfer a domain

Introduction

Transfer .com domain

Valid values for .com:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- ca
- co

With this request you can transfer a domain from 1 registrar to Joker.com.
You have to provide the following information within the request:

- the domain name,
- the auth-Id,
- the billing-contact-handle.

You can transfer 1 .com domain with one request.

If you transfer a domain to Joker.com the domain will be renewed for one year.

As you can see, we don't need information about the owner-contact. We will detect this information from the which of the current registrar and we will create the contact-handle for the owner-contact automatically.

You need to provide us with a so-called auth-Id. You have to ask the current registrar for this auth-Id. If you provide an invalid auth-Id, the transfer will be declined by the current registrar.

As you can see, we need the billing-contact-handle. We recommend using a billing-handle with the email-address of your "joker-email". If you use a contact-handle with a different e-mail than your joker e-mail, you can't administer the transferred domain using the webinterface and the person with access to the email, which is shown in the provided billing-handle will have access using the web-interface.

If you don't have a .com contact-handle with your "joker-email", you have to create a com-handle using the "create com-contact" request.

Domains

```
domain@mouse-100.org  
auth-id=02023A48
```

```
billig-comcast-handels-COEG-1234
```

```
TRANSFER INFO DOMAIN  
Example 1: transfer info-domain  
subject: transfer info-domain [your reference id]  
domain@mouse-100.de  
auth-id=02023A48  
billig-comcast-handels-CITUSG-LRMS
```

```
TRANSFER BIZ DOMAIN  
Example 1: transfer biz-domain  
subject: transfer biz-domain [your reference id]  
domain@mouse-100.biz  
auth-id=02023A48  
billig-comcast-handels-CNEU-123
```

```
TRANSFER NAME DOMAIN  
Example 1: transfer name-domain  
subject: transfer name-domain [your reference id]  
domain@mouse-100.name  
auth-id=02023A48
```

```
billig-comcast-handels-CNAM-1234
```

```
TRANSFER US DOMAIN  
Example 1: transfer us-domain  
subject: transfer us-domain [your reference id]  
domain@mouse-100.us  
auth-id=02023A48
```

```
billig-comcast-handels-COUS-1234
```

```
TRANSFER DE DOMAIN  
Example 1: transfer de-domain  
subject: transfer de-domain [your reference id]  
domain@mouse-100.de  
auth-id=02023A48  
billig-comcast-handels-CODE-1234
```

```
TRANSFER CN DOMAIN  
Example 1: transfer cn-domain  
subject: transfer cn-domain [your reference id]  
domain@mouse-100.cn  
auth-id=02023A48  
billig-comcast-handels-COON-1234
```

Keywords: transfer, auth-id

Last update: 2011-08-11 14:14

Domains

Delete a domain

Introduction

With this request you can delete a domain at joker.com.

You have to provide the following information within the request:

- domain name(s).
- the special flag force.

ATTENTION

If you delete a domain within the first 72 hours after the registration, the registration fee will be refunded to your account.

If joker.com receives the delete request more than 72 hours after the registration, you have to provide the flag "force": 1, in order to accept that the registration fee will not be refunded to your account. If you do not send the "force": 1 in such a case, the request will be rejected.

Request fields

mailsubject: delete domain [your reference id]

Definition of this request

Please, do not forget to provide the domain name and the force-flag set to 1 if the domain is older 72h.

id	mailsubject	mailto
1	delete domain [your reference id]	webmaster@joker.com
2	delete domain [your reference id]	webmaster@joker.com
3	delete domain [your reference id]	webmaster@joker.com

Domains

DELETE COM DOMAIN

Example 1: delete a domain during the first 72 hours after registration
subject: delete domain [your reference id]

tld:com
sld:frezel

Example 2: delete a domain after the first 72 hours after registration
subject: delete domain [your reference id]

tld:com
sld:frezel
force:1

Example 3: delete a domain only for the case that a refund is possible!
subject: delete domain [your reference id]

tld:com
sld:frezel
force:0

Keywords: delete-domain

Last update: 2011-08-11 15:45

Domains

List domains

Introduction

list domains

With this request you can get a list (lexicographically sorted) of all the domains, you have currently registered at joker.com.
You have to provide the target registry within the request:

cto = cto.net

com = .net

net = .net

org = .org

info = .info

biz = .biz

mod = .mod

name = .mod

co = .co

co = .co

co = .co

co = .co

LIMITATIONS

- Only 20,000 domains are listed. If you have more than 20,000 domains under 1 registry at joker.com, you have to track the domain names yourself.
- In case you have more than 20,000 domains at joker.com under 1 registry, this request will not work for you. The listing would be incomplete and it will be missing random domains.
- This request works only with the new joker.com system.

Request fields

url=subject list domains [your reference id]

Definition of the request:

Field Name	Field Values	Example
url	subject list domains [your reference id]	url

LIST DOMAINS

Example 1: list domains for .com-domains
subject list domains [your reference id]
target=com

Example 2: list domains for .net-domains
subject list domains [your reference id]
target=net

Example 3: list domains for .org-domains
subject list domains [your reference id]
target=org

Example 4: list domains for .info-domains
subject list domains [your reference id]
target=info

Example 5: list domains for .biz-domains
subject list domains [your reference id]
target=biz

Domains

Example 6: list domains for .de-domains
subject: list domains [your reference ID]
target: de

Example 7: list domains for .cn-domains
subject: list domains [your reference ID]
target: cn

Keywords: list-domains

Last update: 2011-08-11 15:44

Domains

Lock a domain

Introduction

Lock domain

With this request you can lock a domain in order to prevent fraudulent transfer attempts. If a domain is locked, each transfer request from a foreign registrar will be declined.

You have to provide the following information within the request:

● domain name

You can lock 1 domain with one request.

Request fields

mailto:subject: lock domain [your reference id]

Definition of this request

Request field	Request value	Request type
subject	lock domain [your reference id]	text

Example 1: lock a domain

subject: lock domain [your reference id]

ipdn.milvus-100.com

Keywords: lock-domain, protection

Last update: 2011-08-11 15:46

Domains

Unlock a domain

Introduction

unlock domain

With this request you can unlock a domain. If you want to transfer a domain to a foreign registrar, the domain has to be unlocked.

You have to provide the following information within the request:

● domain name

You can unlock 1 domain with one request.

Request fields

mailsubject: unlock domain [your reference id]

Definitions of the request

Field	Example	Required
mailsubject	unlock domain [your reference id]	Yes

Example 1: unlock a domain
subject: unlock domain [your reference id]
typ:unlock-150.com

Keywords: unlock-domain, protection

Last update: 2011-08-11 15:46

Domains

Get Auth-id

Introduction

With this request you can retrieve the auth-id for a particular domain. That request is needed only for the TLDs: org/inu/az.

You have to provide the following information within the request:

- domain name

You can retrieve the auth-id for 1 domain with one request.

Request fields

mailto:subject: get-auth-id [your-reference-id]

Definition of the request

Field Name	Field Value	Field Name	Field Value	Field Name	Field Value	Field Name	Field Value	Field Name	Field Value	Field Name	Field Value	Field Name	Field Value
subject	get-auth-id [your-reference-id]	subject	get-auth-id [your-reference-id]	subject	get-auth-id [your-reference-id]	subject	get-auth-id [your-reference-id]	subject	get-auth-id [your-reference-id]	subject	get-auth-id [your-reference-id]	subject	get-auth-id [your-reference-id]

Example 1: retrieve the auth-id for a .org-domain
subject: get-auth-id [your-reference-id]
to: jupiter@100.org

Example 2: retrieve the auth-id for a .az-domain
subject: get-auth-id [your-reference-id]
to: jupiter@100.az

Example 3: retrieve the auth-id for a .in-domain
subject: get-auth-id [your-reference-id]
to: jupiter@100.in

Keywords: transfer, auth-id

Last update: 2011-08-11 15:46

Domains

Grant Roles/Domain Permissions, Internal Transfer

Introduction

With this request you can assign [roles/permissions of domains](#) to other Joker.com users. The special role "creator" is an equivalent to an internal transfer of that domain to another Joker.com user. In this case, the domain is assigned to the receiving account, including all rights and permissions on this domain.

There are two variants to use this functionality. If the user id (Joker.com user account id) is given, and the account id matches the associated email address, the role is applied immediately - there will be no request for confirmation on the receiver's side. In case the user id is not given, but only the email address, the transaction has to be acknowledged by the receiver. For this, he will get an email, containing a link and a key. Either the link has to be clicked, or the key has to be applied using Joker.com (or Transfer). This can also be used for users which do not yet have a

Joker.com account

You have to provide the following parameters:

- domain name (the domain you want to grant somebody else permissions on)
- destination client email (the email address of the user you want to receive permissions)

The following parameters are optional:

- destination client id (ID of Joker.com account - always shown in the upper right on Joker.com, also conforms to "header id" - must match the destination client email)
- desired role (type of permission you want to assign to "client email" - help: "client id" - one of "admin@joker.com", "creator" means "all permissions" and is equivalent to an internal transfer or "assignment" - also see [links](#))

Request fields

mailto:joker-internal-transfer [your reference id]

Definition of this request

Valid values for client_email: @Joker.com ID

Parameter Name	Value	Required
client_email	[+45-932] 4321-1234	yes
destination-client-email	@email	yes
destination-client-id	[5-9]	no
desired-role	admin@joker.com (if omitted, default is "creator")	no

Example 1: assign "admin" role to user 12345 (demo)

Domains

subject: jkdn-internal-transfer (pour référence id)

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

destination-client-id:123456

desired-role:billing

Example 2: assign 'creator'-role to user 'example-user@gmail.com' (internal transfer with invitation)

subject: jkdn-internal-transfer (pour référence id)

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

desired-role:creator

Keywords: grants, roles, contacts, permissions, invitations

Last update: 2011-08-17 09:35

Domains