

# Joker.com FAQ

## Table of Content

<b>Domains</b> .....	2
Create an order .....	2
Modify a domain .....	27
Renew a domain .....	33
Transfer a domain .....	37
Delete a domain .....	40
List domains .....	42
Lock a domain .....	44
Unlock a domain .....	45
Get Auth-id .....	46
Grant Roles/Domain Permissions, Internal Transfer .....	47

# Domains

## Create an order

### Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
  
- xxx
  
- asia
  
- me

With this request you can register one or more domains.

You have to provide the following information within the request:

- domain name(s),
- owner-contact-handle,
- admin-contact-handle,
- tech-contact-handle,
- billing-contact-handle,
- nameserver information,
- additional services, if required.

You can register up to 501 domains with one request.

If you register more than one domain with a request, all domains registered with this request will have the same contact and nameserver structure.

There are two new requestfields within this request:

- name

# Domains

- address-3

## ATTENTION

Please, refer to the table for the corresponding contact handles.

TLD	Contact handle
com	CCOM-<number>
net	CNET-<number>
org	CORG-<number>
info	C<number>-LRMS
biz	CNEU-<number>
mobi	COMO-<number>
name	CNAM-<number>
us	COUS-<number>
de	CODE-<number>
cn	COCN-<number>
eu	C<number>
me	COME-<number>
asia	COAS-<number>
xxx	CONX-<number>

### Request fields

mailsubject: create <tld>-order [your reference id]

Definition of this request

tld	request field		
	domains[0..500]	period	language[0..500]
com	[a-z0-9]{1,63}\.com	^([1..9]{1})\$	<a href="#">@language</a>
net	[a-z0-9]{1,63}\.net	^([1..9]{1})\$	
org	[a-z0-9]{1,63}\.org	^([1..9]{1})\$	
info	[a-z0-9]{1,63}\.info	^([1..9]{1})\$	
biz		^([1..9]{1})\$	

# Domains

mobi	[a-z0-9-]{1,63}\.mobi	^([1..9]{1})\$	
name		^[2..9]{1}\$	
us	[a-z0-9-]{1,63}\.us	^[2..9]{1}\$	
de	[a-z0-9-]{1,63}\.de	^[1..9]{1}\$	
cn		^[1..9]{1}\$	
eu		^[1..9]{1}\$	
me		^[1..9]{1}\$	
asia		^[1..9]{1}\$	
xxx		^[1..9]{1}\$	
required	yes	yes	no (IDN domains only)

tld				
com				<a href="#">@comcont</a>
net				<a href="#">@netcont</a>
org				<a href="#">@orgcont</a>
info				<a href="#">@infocont</a>
biz				<a href="#">@decont</a>
mobi				<a href="#">@mobicont</a>
name				<a href="#">@namecont</a>
us				<a href="#">@uscont</a>
de				<a href="#">@bizcont</a>
cn				<a href="#">@cncont</a>
eu				<a href="#">@eucont</a>
me				<a href="#">@mecont</a>

# Domains

asia	@asiacon
required	yes

tld	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle
<tld>	<a href="#">@ns</a>					
required	yes	yes	no			

## .COM order

**Example 1:** create com-order with implicit contact-handle-creation of the owner-contact

subject: create com-order [your reference id]

domains0:xn--hans-mller-feb.com  
language0:AFR  
domains1:minus-10a.com  
domains2:minus-10b.com  
domains3:minus-10c.com  
domains4:minus-10d.com  
domains5:minus-10e.com  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CCOM-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create com-order with implicit nameserver-creation

subject: create com-order [your reference id]

domains0:minus-109.com  
domains1:minus-10a.com  
domains2:minus-10b.com  
domains3:minus-10c.com  
domains4:minus-10d.com  
domains5:minus-10e.com

# Domains

period:2  
owner-contact-handle:CCOM-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CCOM-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create com-order with implicit contact-handle-creation of all contacts

subject: create com-order [your reference id]

domains0:minus-109.com  
domains1:minus-10a.com  
domains2:minus-10b.com  
domains3:minus-10c.com  
domains4:minus-10d.com  
domains5:minus-10e.com  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net

# Domains

ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .NET order

**Example 1:** create net-order with implicit contact-handle-creation of the owner-contact

subject: create net-order [your reference id]

domains0:xn--hans-mller-feb.net  
language0:AFR  
domains1:minus-10a.net  
domains2:minus-10b.net  
domains3:minus-10c.net  
domains4:minus-10d.net  
domains5:minus-10e.net  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CCOM-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create net-order with implicit nameserver-creation

subject: create net-order [your reference id]

domains0:minus-109.net  
domains1:minus-10a.net  
domains2:minus-10b.net  
domains3:minus-10c.net  
domains4:minus-10d.net  
domains5:minus-10e.net  
period:2  
owner-contact-handle:CCOM-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CCOM-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1

# Domains

ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create net-order with implicit contact-handle-creation of all contacts

subject: create net-order [your reference id]

domains0:minus-109.net  
domains1:minus-10a.net  
domains2:minus-10b.net  
domains3:minus-10c.net  
domains4:minus-10d.net  
domains5:minus-10e.net  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2



# Domains

## .ORG order

**Example 1:** create org-order with implicit contact-handle-creation of the owner-contact

subject: create org-order [your reference id]

```
domains0:xn--hans-mller-feb.org
language0:AFR
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

**Example 2:** create org-order with implicit nameserver-creation

subject: create org-order [your reference id]

```
domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-handle:CORG-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

**Example 3:** create org-order with implicit contact-handle-creation of all contacts

subject: create org-order [your reference id]

# Domains

domains0:minus-109.org  
domains1:minus-10a.org  
domains2:minus-10b.org  
domains3:minus-10c.org  
domains4:minus-10d.org  
domains5:minus-10e.org  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## **.INFO order**

**Example 1:** create info-order with implicit contact-handle-creation of the owner-contact

# Domains

subject: create info-order [your reference id]

```
domains0:xn--hans-mller-feb.info
language0:AFR
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C282828-LRMS
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

**Example 2:** create info-order with implicit nameserver-creation

subject: create info-order [your reference id]

```
domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-handle:C176269-LRMS
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C176219-LRMS
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

**Example 3:** create info-order with implicit contact-handle-creation of all contacts

subject: create info-order [your reference id]

```
domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
```

# Domains

owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## **.BIZ order**

**Example 1:** create biz-order with implicit contact-handle-creation of the owner-contact

domains0:xn--hans-mller-feb.biz  
language0:AFR  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz  
domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-email:hans@nose.net

# Domains

owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 2:** create biz-order with implicit nameserver-creation

subject: create biz-order [your reference id]

domains0:minus-109.biz  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz  
domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-handle:CNEU-123  
admin-contact-handle:CNEU-124  
tech-contact-handle:CNEU-125  
billing-contact-handle:CNEU-126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net

# Domains

ns2-ip-address:194.201.101.2

**Example 3:** create biz-order with implicit contact-handle-creation of all contacts

subject: create biz-order [your reference id]

domains0:minus-109.biz  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz  
domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

# Domains

## .MOBI ORDER

**Example 1:** create mobi-order with implicit contact-handle-creation of the owner-contact

subject: create mobi-order [your reference id]

```
domains0:xn--hans-mller-feb.mobi
language0:AFR
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

**Example 2:** create mobi-order with implicit nameserver-creation

subject: create mobi-order [your reference id]

```
domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-handle:COMO-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

**Example 3:** create mobi-order with implicit contact-handle-creation of all contacts

subject: create mobi-order [your reference id]

```
domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
```

# Domains

domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .NAME ORDER

**Example 1:** create name-order with implicit contact-handle-creation of the owner-contact

subject: create name-order [your reference id]



# Domains

```
domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

**Example 2:** create name-order with implicit nameserver-creation

```
subject: create name-order [your reference id]
```

```
domains0:minus-109.name
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-handle:CNAM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

**Example 3:** create name-order with implicit contact-handle-creation of all contacts

```
subject: create name-order [your reference id]
```

```
domains0:minus-109.name
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
```

# Domains

owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .US ORDER

**Example 1:** create us-order with implicit contact-handle-creation of the owner-contact

subject: create us-order [your reference id]

domains0:xn--hans-mller-feb.us  
language0:AFR  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-email:gonzo@nose.net

# Domains

owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COUS-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create us-order with implicit nameserver-creation

subject: create us-order [your reference id]

domains0:minus-109.us  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-handle:COUS-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COUS-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create us-order with implicit contact-handle-creation of all contacts

subject: create us-order [your reference id]

domains0:minus-109.us  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo

# Domains

admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .DE ORDER

**Example 1:** create de-order with implicit contact-handle-creation of the owner-contact

subject: create de-order [your reference id]

domains0:minus-10x.de  
language0:GER  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nase  
owner-contact-address-1:Musterstrasse 11  
owner-contact-postal-code:4711  
owner-contact-city:Musterhausen  
owner-contact-country:DE  
owner-contact-phone:49 13383794 504040  
owner-contact-fax:49 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact

# Domains

billing-contact-handle:CODE-1007

ns1-handle:ns.gonzo.net

ns2-handle:ns2.gonzo.net

**Example 2:** create net-order with implicit nameserver-creation

subject: create de-order [your reference id]

domains0:minus-109.de

domains1:minus-10a.de

domains2:minus-10b.de

domains3:minus-10c.de

domains4:minus-10d.de

domains5:minus-10e.de

period:2

owner-contact-handle:CODE-1007

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:CODE-1007

ns1-domain-name:nsxx1.gonzo.net

ns1-ip-address:194.201.101.1

ns2-domain-name:nsxx1.gonzo.net

ns2-ip-address:194.201.101.2

**Example 3:** create net-order with implicit contact-handle-creation of all contacts

subject: create de-order [your reference id]

domains0:minus-109.de

domains1:minus-10a.de

domains2:minus-10b.de

domains3:minus-10c.de

domains4:minus-10d.de

domains5:minus-10e.de

period:2

owner-contact-email:gonzo@nose.net

owner-contact-individual:Y

owner-contact-fname:gonzo

owner-contact-lname:nase

owner-contact-address-1:Musterstrasse 11

owner-contact-postal-code:4711

owner-contact-city:Musterhausen

owner-contact-country:DE

owner-contact-phone:49 13383794 504040

owner-contact-fax:49 13383794 504040

admin-contact-email:gonzo@nose.net

admin-contact-individual:Y

admin-contact-fname:gonzo

admin-contact-lname:nase

admin-contact-address-1:Musterstrasse 11

admin-contact-postal-code:4711

admin-contact-city:Musterhausen

admin-contact-country:DE

admin-contact-phone:49 13383794 504040

admin-contact-fax:49 13383794 504040

tech-contact-email:gonzo@nose.net

tech-contact-individual:Y

# Domains

tech-contact-fname:gonzo  
tech-contact-lname:nase  
tech-contact-address-1:Musterstrasse 11  
tech-contact-postal-code:4711  
tech-contact-city:Musterhausen  
tech-contact-country:DE  
tech-contact-phone:49 13383794 504040  
tech-contact-fax:49 13383794 504040  
billing-contact-email:gonzo@nose.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nase  
billing-contact-address-1:Musterstrasse 11  
billing-contact-postal-code:4711  
billing-contact-city:Musterhausen  
billing-contact-country:DE  
billing-contact-phone:49 13383794 504040  
billing-contact-fax:49 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .CN ORDER

**Example 1:** create cn-order with implicit contact-handle-creation of the owner-contact

subject: create cn-order [your reference id]

domains0:xn--hans-mller-feb.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net

# Domains

```
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

## Example 2: create cn-order using existing cn-handles

```
subject: create cn-order [your reference id]
```

```
domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-handle:COCN-123
admin-contact-handle:COCN-124
tech-contact-handle:COCN-125
billing-contact-handle:COCN-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

## Example 3: create cn-order with backreferences using @same-as

```
subject: create cn-order [your reference id]
```

```
domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
```

# Domains

owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:same-as-tech-contact  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .EU ORDER

**Example 1:** create eu-order with implicit contact-handle-creation of all contacts

subject: create eu-order [your reference id]

domains0:xn--hans-mller-feb.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y



# Domains

billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 2:** create eu-order using existing .eu-handles

subject: create eu-order [your reference id]

domains0:minus-109.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-handle:C123123  
admin-contact-handle:C123124  
tech-contact-handle:C123125  
billing-contact-handle:C123126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create eu-order with backreferences using @same-as

subject: create eu-order [your reference id]

domains0:minus-109.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:same-as-tech-contact  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1

# Domains

ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

Keywords: create, order, registration

Last update: 2015-07-29 12:02

# Domains

## Modify a domain

### Introduction

modify <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
  
- xxx
  
- asia
  
- me

With this request you can modify existing domains. You have to provide the following information within the

# Domains

request:

- the domainname,
- handle(s) you want to change. (handles from the info-system are not valid)

The system will ignore not specified handles, so you have to provide only the handles, you would like to change.

## Changes within the owner-contact

In case of changing the owner-contact-handle, the system checks, if lname and/or fname and/or organization differ from the original owner-contact-handle. If there are differences these changes will be ignored.

## Request fields

mailsubject: modify <tld>-domain [your reference id]

Definition of this request

request-field	valid values		required
tld		biz eu	yes
sld	[a-z0-9-]{1,63}		yes

# Domains

owner-contact-handle	Please, refer to the table below for the valid values.	no
admin-contact-handle		no
tech-contact-handle		no
billing-contact-handle		no
ns1-handle	<a href="#">@ns</a>	no
ns2-handle		no
ns3-handle		no
ns4-handle		no
ns5-handle		no
ns6-handle		no

tld	contact handle
com	<a href="#">@comcont</a>
net	<a href="#">@netcont</a>
org	<a href="#">@orgcont</a>
info	<a href="#">@infocont</a>
biz	<a href="#">@bizcont</a>
mobi	<a href="#">@mobicont</a>
name	<a href="#">@namecont</a>
us	<a href="#">@uscont</a>
de	<a href="#">@decont</a>
cn	<a href="#">@cncont</a>
eu	<a href="#">@eucont</a>

## Example 1: modify com-domain

subject: modify domain [your reference id]

sld:gonzo  
 tld:com  
 admin-contact-handle:gonzo@nose.com#0  
 tech-contact-handle:hans@nose.com  
 ns1-handle:ns1.gonzo.net  
 ns2-handle:ns2.gonzo.net

## Example 2: modify net-domain

subject: modify net-domain [your reference id]

sld:gonzo  
 tld:net  
 admin-contact-handle:CNET-1234  
 tech-contact-handle:CNET-1234  
 ns1-handle:ns1.gonzo.net

# Domains

ns2-handle:ns2.gonzo.net

## **Example 3:** modify org-domain

subject: modify net-domain [your reference id]

sld:gonzo  
tld:org  
admin-contact-handle:CORG-1234  
tech-contact-handle:CORG-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 4:** modify info-domain

subject: modify info-domain [your reference id]

sld:gonzo  
tld:info  
admin-contact-handle:C112234-LRMS  
tech-contact-handle:C112244-LRMS  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

OR

modify info-domain (new naming convention for info-handles)

subject: modify info-domain [your reference id]

sld:gonzo  
tld:info  
admin-contact-handle:C112244-LRMS  
tech-contact-handle:CAFI-007  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 5:** modify biz-domain

subject: modify biz-domain [your reference id]

sld:gonzo  
tld:biz  
admin-contact-handle:CNEU-11224  
tech-contact-handle:CNEU-112244  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

# Domains

## **Example 6:** modify mobi-domain

subject: modify mobi-domain [your reference id]

sld:gonzo  
tld:mobi  
admin-contact-handle:COMO-1234  
tech-contact-handle:COMO-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 7:** modify name-domain

subject: modify name-domain [your reference id]

sld:gonzo  
tld:name  
admin-contact-handle:CNAM-1234  
tech-contact-handle:CNAM-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 8:** modify us-domain

subject: modify us-domain [your reference id]

sld:gonzo  
tld:us  
admin-contact-handle:COUS-1234  
tech-contact-handle:COUS-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 9:** modify de-domain

subject: modify de-domain [your reference id]

sld:gonzo  
tld:de  
admin-contact-handle:CODE-1234  
tech-contact-handle:CODE-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 10:** modify cn-contact

# Domains

subject: modify cn-contact [your reference id]

handle:COCN-1235  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## **Example 11:** modify eu-domain

subject: modify eu-domain [your reference id]

sld:gonzo  
tld:eu  
admin-contact-handle:C112244  
tech-contact-handle:C112244  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

Keywords: modify-domain, nameserver, contacts

Last update: 2015-07-29 12:02



# Domains

## Renew a domain

Introduction

renew <id>-domain

Valid values for <id>

- com
- net
- org
- info
- biz
- mobi
- name
- us
- ca
- cn

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s)
- the renewalperiod or the desired expirationyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.

If the sum of the expire time and the renewal time is more than 10 years, we will reject your request.

This request is not working for domains, which are located on the old system. For these domains you have to check the documentation of the old system.

If you provide the expire year, this request will reject, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew request is sent twice by mistake.

Request fields

mailto:renew <id>-domain [your reference ID]

# Domains

## Definition of the request

You have to provide the domain name and the renewal period or the desired expiry year using the format "YYYY" on one line. You have to separate each field with a "-" (ASCII 0x2D). The maximum for the renewal period is 9 years.

domain	renewal period	expiry year
example.com	5	2025

## COM renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew-com-domain {your reference id}  
domain@minu-08.com.1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew-com-domain {your reference id}

domain@minu-08.com.4  
domain@minu-10.com.4  
domain@minu-12.com.4  
domain@minu-15.com.4  
domain@minu-18.com.4

**Example 3:** renew 5 domains for different years using the field period

subject: renew-com-domain {your reference id}

domain@minu-08.com.1  
domain@minu-10.com.2  
domain@minu-12.com.3  
domain@minu-15.com.4  
domain@minu-18.com.5

**Example 4:** renew 1 domain using the field expiryyear

subject: renew-com-domain {your reference id}  
domain@minu-08.com.2005

## NET Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew-net-domain {your reference id}  
domain@minu-08.net.1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew-net-domain {your reference id}

domain@minu-08.net.4  
domain@minu-10.net.4  
domain@minu-12.net.4  
domain@minu-15.net.4  
domain@minu-18.net.4

**Example 3:** renew 5 domains for different years using the field period

subject: renew-net-domain {your reference id}

domain@minu-08.net.1  
domain@minu-10.net.2  
domain@minu-12.net.3  
domain@minu-15.net.4  
domain@minu-18.net.5

**Example 4:** renew 1 domain using the field expiryyear

subject: renew-net-domain {your reference id}  
domain@minu-08.net.2005

## ORG Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew-org-domain {your reference id}  
domain@minu-08.org.1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew-org-domain {your reference id}

domain@minu-08.org.4  
domain@minu-10.org.4  
domain@minu-12.org.4  
domain@minu-15.org.4  
domain@minu-18.org.4

**Example 3:** renew 5 domains for different years using the field period

subject: renew-org-domain {your reference id}

domain@minu-08.org.1  
domain@minu-10.org.2  
domain@minu-12.org.3  
domain@minu-15.org.4  
domain@minu-18.org.5

**Example 4:** renew 1 domain using the field expiryyear

subject: renew-org-domain {your reference id}  
domain@minu-08.org.2005

## INFO Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew-info-domain {your reference id}  
domain@minu-08.info.1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew-info-domain {your reference id}

domain@minu-08.info.4  
domain@minu-10.info.4  
domain@minu-12.info.4  
domain@minu-15.info.4  
domain@minu-18.info.4

**Example 3:** renew 5 domains for different years using the field period

subject: renew-info-domain {your reference id}

domain@minu-08.info.1  
domain@minu-10.info.2  
domain@minu-12.info.3  
domain@minu-15.info.4  
domain@minu-18.info.5

# Domains

## Example 4: renew 1 domain using the field expirationyear

subject: renew .nl-domain [your reference id]  
domainid: minusc-100-nl-2005

## DEZ Renewal

### Example 1: renew 1 domain for 1 year using the field period

subject: renew .bz-domain [your reference id]  
domainid: minusc-100-bz-1

### Example 2: renew 5 domains for 4 years using the field period

subject: renew .bz-domain [your reference id]

domainid: minusc-100-bz-4  
domainid: minusc-110-bz-4  
domainid: minusc-120-bz-4  
domainid: minusc-130-bz-4  
domainid: minusc-140-bz-4

### Example 3: renew 5 domains for different years using the field period

subject: renew .bz-domain [your reference id]

domainid: minusc-100-bz-1  
domainid: minusc-110-bz-2  
domainid: minusc-120-bz-3  
domainid: minusc-130-bz-4  
domainid: minusc-140-bz-5

## Example 4: renew 1 domain using the field expirationyear

subject: renew .bz-domain [your reference id]  
domainid: minusc-100-bz-2005

## NAME Renewal

### Example 1: renew 1 domain for 1 year using the field period

subject: renew .name-domain [your reference id]  
domainid: minusc-100-name-1

### Example 2: renew 5 domains for 4 years using the field period

subject: renew .name-domain [your reference id]

domainid: minusc-100-name-4  
domainid: minusc-110-name-4  
domainid: minusc-120-name-4  
domainid: minusc-130-name-4  
domainid: minusc-140-name-4

### Example 3: renew 5 domains for different years using the field period

subject: renew .name-domain [your reference id]

domainid: minusc-100-name-1  
domainid: minusc-110-name-2  
domainid: minusc-120-name-3  
domainid: minusc-130-name-4  
domainid: minusc-140-name-5

## Example 4: renew 1 domain using the field expirationyear

subject: renew .name-domain [your reference id]

domainid: minusc-100-name-2005

## US Renewal

### Example 1: renew 1 domain for 1 year using the field period

subject: renew .us-domain [your reference id]  
domainid: minusc-100-us-1

### Example 2: renew 5 domains for 4 years using the field period

subject: renew .us-domain [your reference id]

domainid: minusc-100-us-4  
domainid: minusc-110-us-4  
domainid: minusc-120-us-4  
domainid: minusc-130-us-4  
domainid: minusc-140-us-4

### Example 3: renew 5 domains for different years using the field period

subject: renew .us-domain [your reference id]

domainid: minusc-100-us-1  
domainid: minusc-110-us-2  
domainid: minusc-120-us-3  
domainid: minusc-130-us-4  
domainid: minusc-140-us-5

## Example 4: renew 1 domain using the field expiration year

subject: renew .us-domain [your reference id]  
domainid: minusc-100-us-2005

## DE Renewal

### Example 1: renew 1 domain for 1 year using the field period

subject: renew .de-domain [your reference id]  
domainid: minusc-100-de-1

### Example 2: renew 5 domains for 4 years using the field period

subject: renew .de-domain [your reference id]

domainid: minusc-100-de-4  
domainid: minusc-110-de-4  
domainid: minusc-120-de-4  
domainid: minusc-130-de-4  
domainid: minusc-140-de-4

### Example 3: renew 5 domains for different years using the field period

subject: renew .de-domain [your reference id]

domainid: minusc-100-de-1  
domainid: minusc-110-de-2  
domainid: minusc-120-de-3  
domainid: minusc-130-de-4  
domainid: minusc-140-de-5

## Example 4: renew 1 domain using the field expirationyear

subject: renew .de-domain [your reference id]

domainid: minusc-100-de-2005

## CA Renewal

### Example 1: renew 1 domain for 1 year using the field period

subject: renew .ca-domain [your reference id]  
domainid: minusc-100-ca-1

### Example 2: renew 5 domains for 4 years using the field period

subject: renew .ca-domain [your reference id]

domainid: minusc-100-ca-4  
domainid: minusc-110-ca-4  
domainid: minusc-120-ca-4  
domainid: minusc-130-ca-4  
domainid: minusc-140-ca-4

### Example 3: renew 5 domains for different years using the field period

subject: renew .ca-domain [your reference id]

domainid: minusc-100-ca-1  
domainid: minusc-110-ca-2  
domainid: minusc-120-ca-3  
domainid: minusc-130-ca-4  
domainid: minusc-140-ca-5

## Example 4: renew 1 domain using the field expire year

subject: renew .ca-domain [your reference id]  
domainid: minusc-100-ca-2005

Keywords: renew, renewal

# Domains

Last update: 2011-08-11 14:18

# Domains

## Transfer a domain

Introduction

transfer-into-domain

Valid values for <id>

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- co

With this request you can transfer a domain from 1 registrar to Joker.com.  
You have to provide the following information within the request:

- the domain name,
- the sub-id,
- the billing contact handle,

You can transfer 1 com domain with one request.

If you transfer a domain to Joker.com the domain will be renewed for one year.

As you can see, we don't need information about the owner-contact. We will detect this information from the whois of the current registrar and we will create the contact handle for the owner-contact automatically.

You need to provide us with a so-called auth-id. You have to ask the current registrar for this auth-id. If you provide an invalid auth-id, the transfer will be declined by the current registrar.

As you can see, we need the billing contact handle. We recommend using a billing handle with the email address of your "joker-email". If you use a contact handle with a different email than your joker-email, you can't administer the transferred domain using the webinterface and the person with access to the email, which is shown in the provided billing handle will have access using the web-interface.

If you don't have a com contact handle with your "joker-email", you have to create a com-handle using the "create-com-contact" request.



# Domains

TRANSFER INFO DOMAIN  
**Example 1:** transfer info-domain  
subject: transfer info-domain [your reference id]  
domainid: miquap-100-0a  
auth-id: 00000AAGL  
billing-control-handle: C1HE200-1234

TRANSFER BIZ DOMAIN  
**Example 1:** transfer biz-domain  
subject: transfer biz-domain [your reference id]  
domainid: miquap-100-0a  
auth-id: 00000AAGL  
billing-control-handle: C1HEU-123

TRANSFER NAME DOMAIN  
**Example 1:** transfer name-domain  
subject: transfer name-domain [your reference id]  
domainid: miquap-100-name  
auth-id: 00000AAGL  
billing-control-handle: C1NAM-1234

TRANSFER US DOMAIN  
**Example 1:** transfer us-domain  
subject: transfer us-domain [your reference id]  
domainid: miquap-100-us  
auth-id: 00000AAGL  
billing-control-handle: C1US-1234

TRANSFER DE DOMAIN  
**Example 1:** transfer de-domain  
subject: transfer de-domain [your reference id]  
domainid: miquap-100-de  
auth-id: 00000AAGL  
billing-control-handle: C1DDE-1234  
TRANSFER CO DOMAIN  
**Example 1:** transfer co-domain  
subject: transfer co-domain [your reference id]  
domainid: miquap-100-co  
auth-id: 00000AAGL  
billing-control-handle: C1CO-1234

Keywords: transfer, auth-id

Last update: 2011-08-11 14:14

# Domains

## Delete a domain

### Introduction

With this request you can delete a domain at Joker.com.

You have to provide the following information within the request:

- domain name(s).
- the special flag force.

### ATTENTION

If you delete a domain within the first 72 hours after the registration, the registration-fee will be refunded to your account.

If Joker.com receives the delete-request more than 72 hours after the registration, you have to provide the flag "force": "1", in order to accept that the registration-fee will not be refunded to your account. If you do not send the "force": "1" in such a case, the request will be rejected.

### Request fields

mailsubject: delete domain [your reference id]

Definition of the request

Please, do not forget to provide the domain name and the force-flag set to 1 if the domain is older 72h.

Request field	Request value	Response
mailsubject	delete domain [your reference id]	OK
force	1	OK



# Domains

## DELETE COM DOMAIN

**Example 1:** delete a domain during the first 72 hours after registration  
subject: delete domain [your reference id]

tld:com  
sld:frezel

**Example 2:** delete a domain after the first 72 hours after registration  
subject: delete domain [your reference id]

tld:com  
sld:frezel  
force:1

**Example 3:** delete a domain only for the case that a refund is possible!  
subject: delete domain [your reference id]

tld:com  
sld:frezel  
force:0

Keywords: delete-domain

Last update: 2011-08-11 15:45

# Domains

## List domains

### Introduction

### Get domains

With this request you can get a list (chronologically sorted) of all the domains you have currently registered at joker.com. You have to provide the target registry within the request:

OTB = OTB.NET

COM = .NET

NET = .NET

ORG = .ORG

INFO = .INFO

SEC = .SEC

MOB = .MOB

NAME = .MOB

CH = .CH

CH = .CH

EU = .EU

UK = .UK

### LISTEXAMPLES

- Only 20,000 domains are listed. If you have more than 20,000 domains under 1 registry at joker.com, you have to track the domain names yourself.
- In case you have more than 20,000 domains at joker.com under 1 registry, this request will not work for you. The listing would be incomplete and it will be missing random domains.
- This request works only with the new joker.com system.

### Request fields

multiple: list domains [your reference id]

Definition of the request:

Field Name	Field Name	Field Name
multiple	multiple	multiple

### LISTEXAMPLES

Example 1: list domains for .com domains

subject: list domains [your reference id]

target:com

Example 2: list domains for .net domains

subject: list domains [your reference id]

target:net

Example 3: list domains for .org domains

subject: list domains [your reference id]

target:org

Example 4: list domains for .info domains

subject: list domains [your reference id]

target:info

Example 5: list domains for .sec domains

subject: list domains [your reference id]

target:sec

Example 6: list domains for .ch domains

subject: list domains [your reference id]

target:ch

# Domains

Example 7: list domains for .cn domains  
subject: list domains [your reference ID]  
begin:cn

Keywords: list-domains

Last update: 2011-08-11 15:44

# Domains

## Lock a domain

Introduction

lock domain

With this request you can lock a domain in order to prevent fraudulent transfer attempts. If a domain is locked, each transfer request from a foreign registrar will be declined.

You have to provide the following information within the request:

● domain name

You can lock 1 domain with one request.

Request fields

subject: lock domain [your reference id]

Definition of this request

field name	field value	field type
subject	lock domain [your reference id]	text

Example 1: lock a domain

subject: lock domain [your reference id]

subject: lock domain [your reference id]

Keywords: lock-domain, protection

Last update: 2011-08-11 15:46

# Domains

## Unlock a domain

Introduction

unlock domain

With this request you can unlock a domain. If you want to transfer a domain to a foreign registrar, the domain has to be unlocked.

You have to provide the following information within the request:

● domain name

You can unlock 1 domain with one request.

Request fields

subject: unlock domain [your reference id]

Definitions of the request

field	description	example
subject	subject: unlock domain [your reference id]	subject: unlock domain [your reference id]

Example 1: unlock a domain  
subject: unlock domain [your reference id]  
ipn-mhuw-100.com

Keywords: unlock-domain, protection

Last update: 2011-08-11 15:46

# Domains

## Get Auth-id

### Introduction

With this request you can retrieve the auth-id for a particular domain. That request is needed only for the TLDs: org/inU/az.

You have to provide the following information within the request:

- domain name

You can retrieve the auth-id for 1 domain with one request.

### Request fields

mailto:subject: get-auth-id [your-reference-id]

### Definition of the request

Field Name	Field Value	Field Name	Field Value	Field Name	Field Value	Field Name	Field Value	Field Name	Field Value
to	<a href="#">[domain]</a>	subject	<a href="#">[domain]</a>	subject	<a href="#">[domain]</a>	subject	<a href="#">[domain]</a>	subject	<a href="#">[domain]</a>

### Example 1: retrieve the auth-id for a .org-domain

mailto:subject: get-auth-id [your-reference-id]  
to:ip@inUaz-100.org

### Example 2: retrieve the auth-id for a .biz-domain

mailto:subject: get-auth-id [your-reference-id]  
to:ip@inUaz-100.biz

### Example 3: retrieve the auth-id for a .az-domain

mailto:subject: get-auth-id [your-reference-id]  
to:ip@inUaz-100.az

Keywords: transfer, auth-id

Last update: 2011-08-11 15:46

# Domains

## Grant Roles/Domain Permissions, Internal Transfer

**Introduction**

With this request you can assign [roles/permissions of domains](#) to other Joker.com users. The special role "creator" is an equivalent to an internal transfer of that domain to another Joker.com user. In this case, the domain is assigned to the receiving account, including all rights and permissions on the domain.

There are two variants to use this functionality: If the user id (Joker.com user account id) is given, and the account id matches the associated email address, the role is applied immediately - there will be no request for confirmation on the receiver's side. In case the user id is not given, but only the email address, the transaction has to be acknowledged by the receiver. For this, he will get an email, containing a link and a key. Either the link has to be clicked, or the key has to be applied using Joker.com (or Transfer). This can also be used for users which do not yet have a

Joker.com account.

You have to provide the following parameters:

- domain name (the domain you want to grant somebody else permissions on)
- destination client email (the email address of the user you want to receive permissions)

The following parameters are optional:

- destination client id (ID of Joker.com account - always shown in the upper right on Joker.com, also conforms to "header id" - must match the destination client email)
- desired role (type of permission you want to assign to "client email" resp. "client id" - one of "admin@jcb@joker.com", "creator" means "all permissions" and is equivalent to an internal transfer of "assignment" - also see [table 1](#))

**Request fields**

MultiSubject: joker-internal-transfer [your reference id]

Definition of the request

Valid values for roles: all Joker.com IDs

Parameter	Default value	Required
id	[+id-9-93-632-+id-]	no
destination-client-email	<a href="#">@email</a>	yes
destination-client-id	[+id-]	no
desired-role	admin@jcb@joker.com (if omitted, default is "creator")	no

Example 1: assign billing-role to user 123456 (demo)

# Domains

subject: jaker-email-transfer pour reference id

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

destination-client-id:123456

desired-role:billing

## Example 2:

assign 'creator'-role to user 'example-user@gmail.com' (internal transfer with invitation)

subject: jaker-email-transfer pour reference id

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

desired-role:creator

Keywords: grants, roles, contacts, permissions, invitations

Last update: 2011-08-17 09:35



# Domains