

Joker.com FAQ

Table of Content

Nameservers	2
Create a nameserver	2
Modify a nameserver	5

Nameservers

Create a nameserver

Introduction

create -rdns

Valid values for rdns:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- ca
- co
- me

With this request you can create an entry for a nameserver in the Joker.com database. If a nameserver is created, you can reference this nameserver using the hostname during a "Create order" request.

ATTENTION:

Only nameservers, which Joker.com is responsible for, will be shown with the ip-address in the whole output.

If you submit a "create-nd" request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code domain, the values for the ip-addresses are ignored.

Request fields

mailsubject: create -rdns -rdns [local reference id]

Field Name	Field Values	Required
create-nd-domain	Example: www.joker.com	no
create-nd-ip		no

Nameservers

```
CREATE COM NAMESPACE
Example 1: create com-ns
subject: create com-ns [your reference id]
no-domain-name ns1.dummy.com
no-ip-address 194.111.43.1
```

```
CREATE NET NAMESPACE
Example 1: create net-ns
subject: create net-ns [your reference id]
no-domain-name ns1.dummy.net
no-ip-address 194.111.43.1
```

```
CREATE ORG NAMESPACE
Example 1: create org-ns
subject: create org-ns [your reference id]
no-domain-name ns1.dummy.org
no-ip-address 194.111.43.1
```

```
CREATE INFO NAMESPACE
Example 1: create info-ns
subject: create info-ns [your reference id]
no-domain-name ns1.dummy.info
no-ip-address 194.111.43.1
```

```
CREATE BIZ NAMESPACE
Example 1: create biz-ns
subject: create biz-ns [your reference id]
no-domain-name ns1.dummy.biz
no-ip-address 194.111.43.1
```

```
CREATE NAME NAMESPACE
Example 1: create name-ns
subject: create name-ns [your reference id]
no-domain-name ns1.dummy.name
no-ip-address 194.111.43.1
```

```
CREATE US NAMESPACE
Example 1: create us-ns
subject: create us-ns [your reference id]
no-domain-name ns1.dummy.us
no-ip-address 194.111.43.1
```

```
CREATE DE NAMESPACE
Example 1: create de-ns
subject: create de-ns [your reference id]
no-domain-name ns1.dummy.de
no-ip-address 194.111.43.1
```

```
CREATE CN NAMESPACE
Example 1: create cn-ns
subject: create cn-ns [your reference id]
no-domain-name ns1.dummy.cn
no-ip-address 194.111.43.1
```

```
CREATE EU NAMESPACE
Example 1: create eu-ns
subject: create eu-ns [your reference id]
no-domain-name ns1.dummy.eu
no-ip-address 194.111.43.1
```

Nameservers

Keywords: nameserver, modify domain

Last update: 2011-08-11 15:42

Nameservers

Modify a nameserver

Introduction

modify-ids-ns

Valid values for <id>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- ru

With this request you can change the ip-address of a nameserver in the Joker.com database.

ATTENTION:

Only nameservers, which Joker.com is responsible for, will be shown with the ip-address in the whole-output, so only these nameservers could be changed.

If you submit a "modify-ns" request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code-domain, this request will be ignored.

Request fields

mailto:modify-ids-ns [your reference id]

Definition of this request

Request field	Old domain	Request
reference	example.com	example.com
ip-address	192.168.1.1	192.168.1.1

MODIFY COM NAMESERVER

Example 1: modify-com-ns

subject: modify-com-ns [your reference id]

ip-address: 192.168.1.1

ip-address: 192.168.1.1

Nameservers

MODIFY NET NAMESERVER
Example 1: modify net-na
subject: modify.com-na [your reference id]
no-handle:net,dummy.com
no-p-address:194.111.42.1

MODIFY ORG NAMESERVER
Example 1: modify org-na
subject: modify.org-na [your reference id]
no-handle:net,dummy.org
no-p-address:194.111.42.1

MODIFY INFO NAMESERVER
Example 1: modify info-na
subject: modify.info-na [your reference id]
no-handle:net,dummy.info
no-p-address:194.111.42.1

MODIFY BIZ NAMESERVER
Example 1: modify biz-na
subject: modify.biz-na [your reference id]
no-handle:net,dummy.biz no-p-address:194.111.42.1

MODIFY NAME NAMESERVER
Example 1: modify name-na
subject: modify.name-na [your reference id]
no-handle:net,dummy.name
no-p-address:194.111.42.1

MODIFY US NAMESERVER
Example 1: modify us-na
subject: modify.us-na [your reference id]
no-handle:net,dummy.us
no-p-address:194.111.42.1

MODIFY DE NAMESERVER
Example 1: modify de-na
subject: modify.de-na [your reference id]
no-handle:net,dummy.de
no-p-address:194.111.42.1

MODIFY CN NAMESERVER
Example 1: modify cn-na
subject: modify.cn-na [your reference id]
no-handle:net,dummy.cn
no-p-address:194.111.42.1

MODIFY EU NAMESERVER
Example 1: modify eu-na
subject: modify.eu-na [your reference id]
no-handle:net,dummy.eu
no-p-address:194.111.42.1

Keywords: nameserver, modify-domain

Last update: 2011-08-11 15:42

Nameservers