

# Account and Handling result-list

## Accepts:

*pending*

get results of requests still in progress

*showall*  
*period*  
*date*

get all results incl. deletes using result-delete  
get results for specified period of days (default 7)  
get results received on (or before) specified date  
date is specified, parameter "period" will be  
date (instead of today) and defaults to 1

*offset*  
*limit*  
*status*  
*count-only*

start displaying results from specified position  
only get number of results specified by limit  
get results having specified status (ack/nack)  
when set to 1, only count number of records  
single line in format "Records: N"

All following filters may use patterns ("\*" and "?")

*rtype*

get results for requests of specified type (domain, register/etc)

*objid*

get results for specified object ids (domain, contacts, hosts)

*procid*

get results for specified proc-id

*svtrid*

get results for specified SvTrId

*cltrid*

get results for specified ClTrId

## Returns:

List of answers from joker.com (one per line):

```
TimeStamp SvTrId Proc-ID request-type status ClTrId
```

## Where:

TimeStamp: The time when request was made, YYYYMMDDHHMMSS

SvTrID: Tracking-Id associated with this request.

Proc-ID: Proc-Id associated with this request.

request-type: The type of the request.

request-object: The object name (host, domain or contact handle)

# Account and Handling

status: ack, nack or ?, where ack means that request was completed successfully.

ClTrId: User specified transaction ID, or "-" if nothing was provided by the user

Example:

<https://dmapi.joker.com/request/result-list?auth-sid=20ddb8c3b2ea758dcf9fa4c7f46c0784>

Unique solution ID: #1017

Author: Joker.com

Last update: 2019-12-18 15:56